View NSN Online: https://aerobasegroup.com/nsn/6140-01-294-6528

POWER-SONIC CORP -- RECHARGEABLE BATTERY -- 6140-01-294-6528

======== Product Identification ============

Product ID:RECHARGEABLE BATTERY

MSDS Date:01/14/1990

FSC:6140

NIIN:01-294-6528

MSDS Number: BQFGC === Responsible Party ===

Company Name: POWER-SONIC CORP

Address:3106 SPRING ST

Box:5242

City:REDWOOD CITY

State:CA

ZIP:94063-3929

Country:US

Info Phone Num:415-364-5001

Emergency Phone Num:415-364-5001

CAG E:56309

=== Contractor Identification ===

Company Name: BATTERY OUTLET INC

Address:1608 CAMPOSTELLA RD

Box:City:CHESAPEAKE

State:VA ZIP:23324 Country:US

Phone:757-545-4442

CAGE:0FGN2

Company Name: POWER-SONIC CORP

Address:3106 SPRING ST

Box:5242

City:REDWOOD CITY

State:CA

ZIP:94063-3929 Country:US

Phone:650-364-5001

CAGE:56309

Company Name:TNR TECHNICAL INC Address:301 CENTRAL PARK DR

Box:City:SANFORD

State:FL ZIP:32771 Country:US

Phone:407-321-3011

CAGE:1HJ92

====== Composition/Informati

on on Ingredients =======

Ingred Name: SULFURIC ACID (SARA III)

CAS:7664-93-9

RTECS #:WS5600000 Fraction by Wt: 17% %

Other REC Limits: NONE SPECIFIED

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000 Fraction by Wt: 60% %

Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:LEAD OXIDE

CAS:1314-41-6 RTECS #:OG54

25000

Fraction by Wt: 20% %

Other REC Limits: NONE SPECIFIED

=========== Hazards Identification =================


LD50 LC50 Mixture:NOT SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EXPOSURE OCCURS ONLY IF BATTERY CASING IS BROKEN. ACUTE:SULFURIC ACID MAY CAUSE IRRITATION OF EYES, NOSE AND THROAT, MAY DAMAGE EYES OR CAUSE SEVERE BURNS OF EYES AND SKI N.

CHRONIC: REPEATED CONTACT C AUSES IRRITATION AND SKIN BURNS. CHRONIC: TEETH EROSION, INFLAMMATION OF THE NOSE, THROAT AND BRONCHIAL TUBES.

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:INHALED: NASAL AND RESPIRATORY IRRITATION FROM SULFUR OXIDE FUMES. CONTACT WITH SKIN OR EYES: BURNS, SKIN IRRITATION AND EYE DAMAGE. SKIN:IRRITATION AND BURNS. INGESTION: STOMACH IRRITA



BEFORE REUSE. Supplemental Safety and Health PROTECT AGAINST CRACKING OF CASE MATERIAL. ADHERE TO PROPER CHARGING PROCEDURES.
========= Physical/Chemical Properties ============
HCC:Z4 Appearance and Odor:RECTANGULAR/SQUARE IN SHAPE. ORANGE IN COLOR. NO ODOR.
========== Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES SOLVENTS MAY DISSOLVE CASE MATERIAL. Stability Condition to Avoid:SEVERE OVERCHARGING, PHYSICAL DAM AGE.
Hazardous Decomposition Products:SULFURIC ACID ON DECOMPOSITION WILL PRODUCE TOXIC SULFUR DIOXIDE. Conditions to Avoid Polymerization:WILL NOT OCCUR.
========= Disposal Considerations ============
Waste Disposal Methods:SEND FOR RECLAMATION OR DISPOSE OF ALL WASTES IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.
========= MSDS Transport Information ==============
Transport Information:49CFR 173.159 (D): A NON-SPILLABLE WET ELECTRIC STORAGE BATTERY IS EXCEPTED FROM ALL OTHER REQUIREMENTS OF THIS SUBCHAPTER IF: 1.THE BATTERY IS PROTECTED AGAINST SHORT CIRCUIT; 2. FOR BATTERIES MANUF ACTURED AFTER SEPTEMBER 30,1995, THE BATTERY

Transport Information:49CFR 173.159 (D): A NON-SPILLABLE WET ELECTRIC STORAGE BATTERY IS EXCEPTED FROM ALL OTHER REQUIREMENTS OF THIS SUBCHAPTER IF: 1.THE BATTERY IS PROTECTED AGAINST SHORT CIRCUIT; 2. FOR BATTERIES MANUF ACTURED AFTER SEPTEMBER 30,1995, THE BATTERY AND THE OUTER PACKAGING MUST BE PLAINLY AND DURABLY MARKED "NONSPILLABLE" OR "NONSPILLABLE BATTERY". 3. THE BATTERY MUST BE CAPABLE OF WITHSTANDING THE FO LLOWING TWO TESTS WITHOUT LEAKAGE OF BATTERY FLUID FROM THE BATTERY: (I) VIBRATION TEST; (II) PRESSURE DIFFERENTIA

L TEST. PER MFR THESE BATTERIES CONFORM TO THE ABOVE REGULATIONS & IATA SPEC PROV A67 AND ARE, THEREFORE, NOT REGULATED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek comp

etent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.