View NSN Online: https://aerobasegroup.com/nsn/6550-01-037-4733

DU PONT E I DE NEMOURS AND CO INC -- TOTAL PROTEIN (TP) TEST PACKS,701333901 - 6550-01-037-4733

Product ID:TOTAL PROTEIN (TP) TEST PACKS,701333901 MSDS Date:08/01/1989 FSC:6550 NIIN:01-037-4733 **MSDS Number: BQGRQ** === Responsible Party === Company Name: DU PONT E I DE NEMOURS AND CO INC Address: BIOMEDICAL PRODUCTS DEPT, GLASGOW SITE City:WILMINGTON State:DE ZIP:1 9898 Country:US Info Phone Num:800-441-9250/302-453-2311 Emergency Phone Num:800-441-3637/302-453-2311 CAGE:52246 === Contractor Identification === Company Name: DU PONT E I DE NEMOURS AND CO INC Address: BIOMEDICAL PRODUCTS DEPT, GLASGOW SITE Box:City:WILMINGTON State:DE ZIP:19898 Country:US Phone:800-441-3637/302-453-2311 CAGE:52246 Ingred Name:SODIUM HYDROXIDE (SARA III)/POTASSIUM SODIUM TARTRATE SOLUTION CAS:1310-73-2 RTECS #:WB4900000 Other REC Limits:NONE RECOMMENDED OSHA PEL:2 MG/M3 ACGIH TLV:C 2 MG/M3; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: CUPRIC SULFATE, PENTAHYDRATE/SOLUTION CAS:7758-99-8 RTECS #:GL8900000 Other REC Limits:NONE RECOMMENDED OSHA PEL:1 MG/M3 ACGIH TLV:1MG/M3

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:AC UTE- CORROSIVE. CAN CAUSE PERMANENT

EYE DAMAGE. CAN CAUSE SKIN BURNS ON PROLONGED CONTACT. NOT A HAZARD BY INHALATION. CAN CAUSE DAMGE TO DIGESTIVE SYSTEM. CHRONIC- NONE KNOWN.

Effects of Overexposure:CORROSIVE. CAN CAUSE PERMANENT EYE DAMAGE. CAN CAUSE SKIN BURNS ON PROLONGED CONTACT. NOT A HAZARD BY INHALATION. CAN CAUSE DAMGE TO DIGESTIVE SYSTEM. Medical Cond Aggravated by Exposure:NONE KNOWN

First Aid:

GET MEDICAL ATTENTION. SKIN: IMMEDIATELY FLUSH WITH PLENTY OF WATER. EYE: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. INHALED: REMOVE TO FRESH AIR. ORAL: DO NOT INDUCE VOMITING. IF CONSCIOUS, DRINK LARGE AMOUNT OF WATER.CALL A PHYSICIAN.

Flash Point:NONE

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED C

ONTAINERS.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND SELF CONTAINED BREATHING APPARATUS. EVACUATE PERSONNEL TO A SAFE AREA, UPWIND OF FIRE.

Unusual Fire/Explosion Hazard:CARBON MONOXIDE, CARBON DIOXIDE, NITROGEN OXIDES AND SULFUR OXIDES

Spill Release Procedures: CONTAIN LEAKING MATERIAL. COVER WITH AN ABSORBENT MATERIAL. DISCARD IN AN APPROVED CONTAINER.

======= Handlin

Handling and Storage Precautions:STORAGE- STORE UNOPENED PACKS AT 2-8C. DO NOT FREEZE. USED PACKS CONTAIN HUMAN FLUIDS; HANDLE WITH APPROPRIATE CARE.

Other Precautions:DO NOT EXPOSE UNPRPOCESSED PACKS TO TEMPERATURES ABOVE 35C OR TO DIRECT SUNLIGHT. DO NOT KEEP EXPOSED PACKS AT ROOM TEMPERATURES (15-25C) FOR MORE THAN 8 HOURS. WASH THOROUGHLY AFTER HANDLING. AVOID C ONTACT WITH EYES, SKIN AND CLOTHING.

======= Exposure Controls/P

ersonal Protection =========

HCC:B1 Solubility in Water:SOLUBLE Appea rance and Odor:PROCESSED PACK IS VIOLET TO PURPLE LIQUID WITH NO ODOR

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:EXCESSIVE HEAT Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, NITROGEN OXIDES AND SULFUR OXIDES

Waste Disposal Methods: DISPOSE OF IN CONFORMITY WITH LOCAL, STATE AND

FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.