

DEFT INC CHEMICAL COATING DIV -- CAT, 1-COAT, TT-P-2756, 36375 PC 03GY369CAT --
8010-01-354-0964

===== Product Identification =====

Product ID:CAT, 1-COAT, TT-P-2756, 36375 PC 03GY369CAT

MSDS Date:05/24/1991

FSC:8010

NIIN:01-354-0964

Kit Part:Y

MSDS Number: BQGWY

=== Responsible Party ===

Company Name:DEFT INC CHEMICAL COATING DIV

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

C

Country:US

Info Phone Num:714-474-0400

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:NORM GAUL

CAGE:33461

=== Contractor Identification ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC ISOCYANATE (HEXAMETHYLENE DIISOCYANATE [HDI] CAS:
822-06-0; FREE MONOMER CONTENT LESS THAN .5%)

CAS:28182-81-2

RTECS #:HQ91700

00

Fraction by Wt: 60%

Other REC Limits:MOBAY:CEILING.02 PPM

ACGIH TLV:TWA: 0.005 PPM

Ingred Name:ETHYL 3-ETHOXYPROPIONATE (VAPOR PRESSURE .7 MM HG @ 68F)

CAS:763-69-9

RTECS #:UF3325000

Fraction by Wt: 20%

Other REC Limits:50 PPM;STEL 100 PPM

Ingred Name:N-BUTYL ACETATE (VAPOR PRESSURE 13 MM HG @ 68F)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:150 PPM/STEL 200 PPM

ACGIH TLV:150 PPM/STEL 200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred N

ame:VOC: 399 G/L

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE; EYES, NOSE, THROAT IRRIT &

ACUTE NERV SYS DEPRESSN. INHAL: HEADACHES, DIZZINESS, STAGGERING,
DIFFICULT BREATHING, CONFUSION, UNCONSCIOUSNESS, COMA. SKIN: IRRIT
(SWELLING, REDNESS, RASH). EYES: IRRIT (T

EARING, REDNESS, SWELLING

W/STINGING). INGEST: IRRIT, CORROSIVE TO GI TRACT. ASPIRATION
(VOMIT)-CHEM PNEUMONITIS.

Effects of Overexposure:CHRONIC; AS A RESULT OF PREVIOUS REPEATED

OVEREXPOSURE OR A SINGLE LARGE DOSE, CERTAIN INDIVIDUALS WILL
DEVELOP ISOCYANATE SENSITIZATION WHICH WILL CAUSE THEM TO REACT TO
A LATER EXPOSURE OF ISOCYANATE LEVELS WELL BELOW THE TLV VALUE OF
ISOCYANATES.

Medical Cond Aggravated by Exposure:ASTHMA AND ANY OTHER RESPIRATORY
DISORDERS. SKI

N ALLERGIES, ECZEMA AND DERMATITIS. ISOCYANATE SENSITIZATION.

=====
===== First Aid Measures =====

First Aid:INHAL: MOVE TO FRESH AIR. RESTORE BREATHING. ASTHMATIC TYPE SYMPTOMS MAY DEVELOP (IMMED/DELAYED). GET MED AID. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREAS WITH SOAP & WATER. WASH CONTAMINATED CLOTHES BEFORE REUSE. EYES: FLUSH WITH LUKEWARM WATER (LOW PRESSURE) 15 MIN, LIFTING EYELIDS. GET MED AID. INGEST: DONT INDUCE VOMITING. DO NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON. GET MED AID.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:76.0F,24.4C
Lower Limits:1.05
Upper Limits:7.60
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG
Fire Fighting Procedures:USE FULL PROTECT CLOTH/FIREFIGHT EQUIP W/SCBA. WATER MAY BE USED TO COOL CLSD CNTNRS (PREVENT PRESS BLDUP/AUTOIGNIT/EXPLOS). HDI/IRRIT VAPOR GENERATED BY FIRE.
Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD. KEEP FROM HEAT/IGNIT SOURCE. CLSD CNTNR MAY EXPLODE W/HEAT. APPLIC TO HOT SURFACE REQ SPECIAL PRECAUTION. OVEREXPOSURE TO DECOMP PROD-HLTH HZD.

=====
===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES). VENTILATE AREA. CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN BUILDINGS IN COMPLIANCE WITH OSHA 1910.106. AVOID STORING NEAR HIGH TEMPS/IGNITION SOURCE. STORE IN CLOSED CONTAINER IN WELL VENTILATED AREA.
Other Precautions:KEEP CNTNR TIGHT/UPRIGHT (PREVENT LEAK). PREVENT PROLONGD VAPOR BREATHING. PROLONGD OVEREXPOSURE MAY CAUSE ALLERGIC REACTION. AVOID SKIN/EYE CONTACT. DONT INGEST.DONT HANDLE TILL MFR PRECAUTIONS READ/ UNDERSTOOD. SMOKE IN SMOK

ING AREAS ONLY.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RESPIRATOR RECOMMENDED FOR USE IN ORGANIC VAPOR ENVIRONMENT (AIR PURIFYING/FRESH AIR SUPPLIED). OBSERVE OSHA RESPIRATOR REGULATIONS. VAPOR PARTIC RESPIRATOR (TC23C) MAY BE USED WHEN AIR MONITORING SHOWS VAPOR LEVELS BELOW 10X TLV/PEL.

Ventilation:EXHAUST VENTILATION TO KEEP AIRBORNE CONCENTRATION (HDI, POLYISOCYANATES, SOLVENT) BELOW TLVS. REMOVE IGNITION SOURCES.

Protective Gloves:COTTON, NEOPRENE, RUBBER, POLYETHYLENE

Eye Protection:CHEM GOGGLES,FACESHLDs,SPLSH GRDS,SDSHLD

Other Protective Equipment:THE USE OF LONG SLEEVE AND LONG LEG CLOTHING RECOMMENDED. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOM.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:260 TO 460F

Vapor Density:> AIR

Spec G

Gravity:1.03121

Evaporation Rate & Reference:0.47 X N-BUTYL ACETATE

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER LIQUID WITH SOLVENT ODOR

Percent Volatiles by Volume:41.5

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS AND SURFACE ACTIVE MATERIALS.

Stability Condition to Avoid:CONTACT WITH MOISTURE, MATERIAL WHICH REACT WITH ISOCYANATES AND HIGH TEMPERATURES.

Hazardous Decomposition Products:BY HIGH HEAT/TEMPERATURE: CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN, TRACES OF HCN AND HDI.

Conditions to Avoid Polymerization:CONTACT WITH MOISTURE, MATERIALS WHICH REACT WITH ISOCYANATES AND HIGH TEMPERATURES.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS MUST BE HANDLED WITH CARE

ARE, DUE TO PRODUCT RESIDUE & FLAMMABLE VAPOR. DONT
INCINERATE CLOSED CONTAINER. EPA HZD WASTE #: D001, F003,
F005,IGNITABLE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek
competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.