

DU PONT E I DE NEMOURS & CO INC -- ETHYL ALCOHOL, 95% -- 6505-00-104-9000

=====  
Product Identification  
=====

Product ID:ETHYL ALCOHOL, 95%

MSDS Date:09/01/1990

FSC:6505

NIIN:00-104-9000

MSDS Number: BQKMC

=== Responsible Party ===

Company Name:DU PONT E I DE NEMOURS & CO INC

Address:1007 MARKET STREET

Box:1635

City:WILMINGTON

State:DE

ZIP:19899

Country:US

Info Phone Num:800-441-3637(MEDICAL) OR C

HEMTREC

Emergency Phone Num:800-441-7515

CAGE:18873

=== Contractor Identification ===

Company Name:E.I. DUPONT DE NEMOURS & CO

Address:1007 MARKET STREET

Box:City:WILMINGTON

State:DE

ZIP:19898

Country:US

Phone:800-441-7515;800-441-9442

CAGE:18873

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 95%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9293

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====  
=====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 7060 MG/KG (ETHANOL)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION MAY CAUSE IRRITATION OF UPPER RESPIRATORY TRACT. SKIN CONTACT MAY CAUSE MILD REDNESS AND BURNING. EYE CONTACT MAY CAUSE IMMEDIATE BURNING AND STINGING WITH TEMPORARY INJURY OF THE CORNEAL EPITHELIUM & HYPEREMIA OF THE CONJUNCTIVA.INGESTION MAY CAUSE STIMULATION FOLLOWED BY INTOXICATION.

Explanation of Carcinogenicity:THIS PRODUCT IS NOT LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN, MUTAGEN, TERATOGEN OR NEUROTOXIN.

Effects of Overexposure:MAY CAUSE EYE, SKIN & RESPIRATORY TRACT IRRITATION. CAUSES CNS DEPRESSION WITH HEADACHE, DIZZINESS, TREMORS, FATIGUE, VISUAL IMPAIRMENT, MUSCULAR INCOORDINATION,

SLOWING OF REACTION TIME, SENSORY DISTURBANCES, SLURRING OF SPEECH, FLUSHING OF THE FACE, DILATED PUPILS, RAPID PULSE, NAUSEA, VOMITING, SWEATING & DIURESIS.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE SKIN, EYE, RESPIRATORY TRACT, LIVER OR KIDNEY MAY BE AT INCREASED RISK FROM EXPOSURE.

=====  
===== First Aid Measures =====  
=====

First Aid:EYES: IMMEDIATELY FLUSH WITH RUNNING WATER FOR AT LEAST 15

MINUTES WHILE LIFTING EYELIDS. GET IMMEDIATE MEDICAL ATTENTION.

SKIN: FLUSH WITH RUNNING WATER WHILE REMOVING CONTAMINATED CLOTHING AND SHOES . GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR.

IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====  
=====

Flash Point Method:CC

Flash Point:63.0F,17

.2C

Autoignition Temp:Autoignition Temp Text:685F

Lower Limits:3.3

Upper Limits:19

Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL OR POLYMER FOAM. WATER MAY BE INEFFECTIVE.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. USE WATER TO COOL FIRE EXPOSED CONTAINERS AND DILUTE SPILLS.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON SAND OR VERMICULITE & PLACE IN CLOSED CONTAINER FOR DISPOSAL. SHUT OFF ALL SOURCES OF IGNITION. EVACUATE AREA. VENTILATE AREA & WASH SPILL SITE AFTER MATERIAL PICKUP IS COMPLETE. WEAR SCBA, RUBBER BOOTS AND HEAVY RUBBER GLOVES.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A FLAMMABLE LIQUID STORAGE

ROOM OR CABINET. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions:MAKE FREQUENT CAREFUL LEAKAGE INSPECTIONS. ISOLATE FROM OXIDIZERS, CHEMICALS CAPABLE OF SPONTANEOUS HEATING, MATERIALS REACTING WITH AIR OR MOISTURE TO LIBERATE HEAT, IGNITION SOURCES AND EXPLOSIVES. KEEP OUT OF DIRECT SUN & AWAY FROM HEAT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF

VENTILATION DOES NOT MAINTAIN INHALATION

EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED RESPIRATORS.

RESPIRATORS SHOULD BE SELECTED BASED ON THE FORM AND CONCENTRATION OF CONTAMINANT IN AIR & IN ACCORDANCE WITH OSHA (29 CFR 1910.134).

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE.

LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA NOT VENTED.

Protective Gloves:NEOPRENE, NITRILE, PVC OR NATURAL RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Othe

Protective Equipment: EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS. CAUTION: FOR MANUFACTURING, PROCESSING, REPACKING OR INDUSTRIAL USE. NOT FOR HOUSEHOLD USE.

CONTAINER IS HAZARDOUS WHEN EMPTY. EMPTIED CONTAINERS RETAIN RESIDUAL LIQUID AND VAPOR. FOLLOW PRECAUTIONS ON LABEL AND IN MSDS.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt: B.P. Text: 172F, 78C

Melt/Freeze Pt: M.P/F.P Text: -202F, -130C

Vapor Pres: 40

Vapor Density: 1.58

Spec Gravity: 0.812

Evaporation Rate & Reference: 1.7 (N-BUTYL ACETATE=1)

Solubility in Water: COMPLETE

Appearance and Odor: CLEAR, COLORLESS LIQUID. ALCOHOLIC ODOR.

Percent Volatiles by Volume: 100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS, PEROXIDES, ACIDS, ACID CHLORIDES, ACID ANHYDRIDES AND ALKALI METALS

Stability Condition to Avoid: HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods: BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN

AFTERBURNER AND SCRUBBER BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. DISPOSE IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for it.

ts use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.