

PRATT AND LAMBERT INC -- LAC ACR TAN 30219 ID 794022 -- 8010-00-066-9440

=====  
Product Identification  
=====

Product ID:LAC ACR TAN 30219 ID 794022

MSDS Date:09/23/1992

FSC:8010

NIIN:00-066-9440

MSDS Number: BQLZB

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:7

16-873-6000 DOT EMER 8002553924

Preparer's Name:W. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CYCLOHEXANONE (SOLVENT) (SARA III) (VAPOR PRESSURE 2 MM HG  
@ 20C) (SKIN) (LFL 1.1)

CAS:108-94-1

RTECS #:GW1050000

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

OSHA PEL:S, 50

PPM  
ACGIH TLV:S, 25 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (SOLVENT) (SARA III) (VAPOR PRESSURE 70  
MM HG @ 20C) (LFL 2.0; UFL 10.0)

CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 20%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:200 PPM/STEL 300 PPM  
ACGIH TLV:200 PPM/STEL 300 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SOLVENT) (SARA III) (VAPOR PRESSURE 22 MM HG @  
20C) (LFL 1.7; UFL 7.1)

CAS:108-88-3  
RTECS #:XS5250000  
Frac  
tion by Wt: 10%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ACRYLATE (SARA III) (SKIN) (VAPOR PRESSURE 29 MM HG @  
20C) (LFL 1.0; UFL 14.0)

CAS:140-88-5  
RTECS #:AT0700000  
Fraction by Wt: 10%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:S,25 PPM/15 STEL  
ACGIH TLV:5 PPM/15 STEL,A2 93  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:BUTYL BENZYL PHTHALATE (ADDITIVE) (SARA III) (LFL 0.3)  
CAS:85-68-

RTECS #:TH9990000

Fraction by Wt: 115F) AND SOURCES  
OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY  
WELDING/ CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON  
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORD W/FED, STATE & LOCAL  
LAWS/REGS. INCINERATE IN EPA PERMITTED FACILITY. DON'T INCINERATE  
CLSD CNTNR. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMM MAT'L. CONTAM  
AB

SORB MAY BE DISPOSED IN A HZD WASTE LANDFILL. RCRA  
CLASSIFICATION: D001.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume resp  
onsibility for the suitability of this information to their  
particular situation.