

PRATT AND LAMBERT INC -- LAC ACR WHITE 17875 ID 794716 -- 8010-00-935-6608

=====
Product Identification
=====

Product ID:LAC ACR WHITE 17875 ID 794716

MSDS Date:09/24/1992

FSC:8010

NIIN:00-935-6608

MSDS Number: BQMHC

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone N

um:873-6000 DOT EMER 8002553924

Preparer's Name:W. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:CYCLOHEXANONE (SOLVENT) (SARA III) (VAPOR PRESSURE 2 MM HG
@ 20C) (LFL 1.1)

CAS:108-94-1

RTECS #:GW1050000

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

OSHA PEL:S, 50 PPM

ACG

IH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SOLVENT) (SARA III) (VAPOR PRESSURE 22 MM HG @ 20C) (LFL 1.7; UFL 7.1)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ACRYLATE (SARA III) (VAPOR PRESSURE 29 MM HG @ 20C) (SKIN) (LFL 1.0; UFL 14.0)

CAS:140-88-5

RTECS #:AT0700000

Fraction by Wt: 15%

Other REC

Limits:NONE SPECIFIED

OSHA PEL:S,25 PPM/15 STEL

ACGIH TLV:5 PPM/15 STEL,A2 93

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE (PIGMENT)

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:METHYL ETHYL KETONE (SOLVENT) (SARA III) (VAPOR PRESSURE 70 MM HG @ 20C) (LFL 2.0; UFL 10.0)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

OSHA PE

L:200 PPM/STEL 300 PPM
ACGIH TLV:200 PPM/STEL 300 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingrid Name:BUTYL BENZYL PHTHALATE (ADDITIVE) (SARA III) (LFL 0.3)
CAS:85-68-7
RTECS #:TH9990000
Fraction by Wt: AIR
Spec Gravity:1.1
pH:4-7
Viscosity:>200 CST
Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER
Solubility in Water:SLIGHT
Appearance and Odor:LIQUID, SOLVENT ODOR
Percent Volatiles by Volume:69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>115F) AND SOURCES OF IGNITION.
Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY WELDING/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORD W/FED, STATE & LOCAL LAWS/REGS. INCINERATE IN EPA PERMITTED FACILITY. DON'T INCINERATE
CLSD CNTNR. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMM MAT'L. CONTAM ABSORB MAY BE DISPOSED IN A HZD WASTE LANDFILL. RCRA CLASSIFICATION: D001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing th

is

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.