

PRATT AND LAMBERT INC; INDUSTRIAL COATINGS DIV -- LAC ACR RED 11136 ID 794104 --
8010-00-935-7062

=====
===== Product Identification =====

Product ID:LAC ACR RED 11136 ID 794104
MSDS Date:09/24/1992
FSC:8010
NIIN:00-935-7062
MSDS Number: BQMHD
=== Responsible Party ===
Company Name:PRATT AND LAMBERT INC; INDUSTRIAL COATINGS DIV
Box:2153
City:WICHITA
State:KS
ZIP:67201
Country:US
Info Phone Num:316-733-
1361
Emergency Phone Num:716-873-6000/DOT: 800-255-3924
Preparer's Name:W. A. ELLISON
CAGE:61196
=== Contractor Identification ===
Company Name:PRATT AND LAMBERT INC
Box:6027
City:CLEVELAND
State:OH
ZIP:44101-1027
Country:US
Phone:216-566-2902
CAGE:61196

=====
===== Composition/Information on Ingredients =====

Ingred Name:CYCLOHEXANONE (SOLVENT) (SARA III) (VAPOR PRESSURE 2 MM HG
@ 20C) (LFL 1.1)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 20%
Other REC Limits:NONE SPECIFIE

D

OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (SOLVENT) (SARA III) (VAPOR PRESSURE 70
MM HG @ 20C) (LFL 2.0; UFL 10.0)

CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/STEL 300 PPM
ACGIH TLV:200 PPM/STEL 300 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SOLVENT) (SARA III) (VAPOR PRESSURE 22 MM HG @
20C) (LFL 1.7; UFL 7.1)

CAS:108-88-3
RTECS
#:XS5250000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ACRYLATE (SARA III) (VAPOR PRESSURE 29 MM HG @ 20C)
(SKIN) (LFL 1.0; UFL 14.0)

CAS:140-88-5
RTECS #:AT0700000
Fraction by Wt: 15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S,25 PPM/15 STEL
ACGIH TLV:5 PPM/15 STEL,A2 93
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:BUTYL BENZYL PHTHALATE (ADDITIVE) (SARA III) (

LFL 0.3)

CAS:85-68-7

RTECS #:TH9990000

Fraction by Wt: 200 CST

Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:72

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>115F) AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING, W

ILL PRODUCE SMOKE, CARBON

MONOXIDE, AND CARBON DIOXIDE. OXIDES OF CHROMIUM AND LEAD MAY BE GENERATED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORD W/FED, STATE, LOCAL LAWS/REGS.

INCINERATE IN EPA PERMITTED FACILITY. DONT INCINERATE CLOSED

CONTAINERS. OBEY PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS.

DISPOSE OF CONTAM ABSORB NT IN HAZARDOUS WASTE LANDFILL. RCRA D001, D008.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.