View NSN Online: https://aerobasegroup.com/nsn/6850-01-292-5188

HAARTZ-MASON, INC. -- N-450-9 THINNER/CLEANER -- 6850-01-292-5188

Product ID:N-450-9 THINNER/CLEANER MSDS Date:12/01/1989 FSC:6850 NIIN:01-292-5188 MSDS Number: BQMLM === Responsible Party === Company Name: HAARTZ-MASON, INC. Address:270 PLEASANT STREET Box:322 **City:WATERTOWN** State:MA ZIP:02172 Country:US Info Phone Num:617-926-2300 Emergency Phone Num:617-926-23 00 CAGE:84697 === Contractor Identification === Company Name: HAARTZ-MASON, INC. Address:270 PLEASANT STREET Box:322 **City:WATERTOWN** State:MA ZIP:02172 Country:US Phone:617-926-2300 CAGE:84697 Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 50.0% Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM/150 STEL

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

ACGIH TLV:100 PPM/150STEL;9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 50.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 2737 MG/KG (MEK) Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acu te and Chronic:FLAMMABLE! HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. MAY CAUSE INJURY TO EYES. INHALATION: RESPIRATORY TRACT IRRITANT AND ANESTHETIC, MAY CAUSE NARCOSIS IN HIGH CONCENTRATION. CAUSES CNS D EPRESSION. Effects of Overexposure:EYES:SEVERE IRRITATION, REDNESS, INJURY. SKIN:IRRITATION. INHALATION: COUGHING, UNCONSCIOUSNES, NARCOSIS , CNS DEPRESSION. INGEST:NAUSEA, VOMITING, LIVER AND/OR KIDNEY DAMAGE. Medical Cond Aggravated by Exposure:ANY ALLERGY,

ECZEMA, SKIN

CONDITION, PRE-EXISTING LIVER AND KIDNEY DISORDERS.

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE CPR IF NOT BREATHING. GET MEDICAL ATTENTION IMMEDIATELY. EYE: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELID. GET MEDICAL ATTENTION IMMEDIATELY. SKIN: WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS.

GET MEDICAL ATTENTION IMMEDIATELY.

Flash Point Method:SCC Flash Point:32F/0C Lower Limits:1.0 Upper Limits:11.5 Extinguishing Media:FOAM, CARBON DIOXIDE, OR DRY CHEMICAL Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:SOLVENT VAPORS MAY TRAVEL CONSIDERA

BLE DISTANCES AND FLASH BACK FROM A SOURCE OF IGNITION.

Spill Release Procedures: REMOVE IGNITION SOURCES. SMALL SPILL: WIPE WITH RAGS OR TOWELS. LARGE SPILLS: EVACUATE AREA. WEAR NIOSH APPROVED RESPIRATOR. VENTILATE AREA. DIKE TO RETAIN FLUID. PUMP UP FREE LIQUID. RESIDUE WILL EVAPO RATE QUICKLY. DO NOT FLUSH TO SEWER OR WATERWAY. Neutralizing Agent:NONE _____ Handling and Storage Precautions: KEEP AND STORE IN COOL, DRY PLACE AWAY FROM IGNITION SOURCES. GROUND DURING TRANSFER. Other Precautions: REPEATED & PROLONGED OVEREXPOSURE TO SOLVENTS MAY CAUSE BRAIN AND NERVOUS SYSTEM DAMAGE. INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. Respiratory Protection: USE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS IF TLV IS EXCEEDED OR WHEN SPRAYING OR USING IN C ONFINED SPACES. Ventilation: MECHANICAL EXHAUST TO MAINTAIN AIR CONTAMINANT LEVELS BELOW TLV. Protective Gloves: RUBBER, PVA, NITRILE. Eye Protection: SAFETY GLASSES WITH SIDE SHIELDS/GOGGLES Other Protective Equipment: AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IS RECOMMENDED. PROTECTIVE CLOTHING AS REQUIRED FOR TASK AT HAND. Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplementa I Safety and Health HCC:F2 Boiling Pt:=79.4C, 175.F Vapor Pres:>1 Vapor Density:>1 Spec Gravity:0.84 Evaporation Rate & amp; Reference:>1 (N-BUTYL ACETATE=1) Solubility in Water: PARTIAL Appearance and Odor: COLORLESS, CLEAR LIQUID WITH CHARACTERISTIC ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRO

NG MINERAL ACIDS, STRONG ALKALIS AND HALOGENS. Stability Condition to Avoid:SPARKS, OPEN FLAMES OR HOT SURFACE Hazardous Decomposition Products:CARBON MONOXIDE & DIOXIDE

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH APPLICABLE LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense

. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.