

UNKNOWN/DEFENSE DEPOT, OGDEN, UT PROCURED -- BRAKE LINING -- 2530-00-141-8544
===== Product Identification =====

Product ID: BRAKE LINING

MSDS Date: 04/29/1993

FSC: 2530

NIIN: 00-141-8544

MSDS Number: BQMYG

=== Responsible Party ===

Company Name: UNKNOWN/DEFENSE DEPOT, OGDEN, UT PROCURED

Country: US

Preparer's Name: DOD HMIS/DGSC-SSH

CAGE: KO226

=== Contractor Identification ===

Company Name: UNKNOWN/DEFENSE

NSE DEPOT, OGDEN, UT PROCURED

Country: US

CAGE: KO226

===== Composition/Information on Ingredients =====

Ingred Name: ASBESTOS, CHRYSOTILE

CAS: 12001-29-5

RTECS #: CI6478500

OSHA PEL: 0.2 FIBERS/CC

ACGIH TLV: 2 FIBERS/CC; A1; 9192

Ingred Name: GENERIC "MSDS". SPECIFIC ASBESTOS TYPE NOT KNOWN. ONE CITED IS ASSUMED. INFORMATION BASED ON "DLSC TIR"

RTECS #: 9999999ZZ

===== Hazards Identification =====

Routes of Entry: Inhalation: YES Skin: NO Ingestion: NO

Reports of Carcinogenicity: NTP: YES IARC: YES OSHA: YES

Health Hazards Acute and Chronic: ACUTE: NO ACUTE EFFECTS ARE KNOWN;

CHRONIC: DUST FROM ABRASIVE ACTIONS (E.G. CUTTING, MACHINING, FILING, ETC.) MAY CONTAIN ASBESTOS FIBERS. CHRONIC OVEREXPOSURE TO AIRBORNE FIBERS MAY LEAD TO ASBESTOSIS AND MESOTHELIOMA. SMOKING COMBINED WITH FIBER INHALATION GREATLY INCREASES LUNG CANCER RISK!

Explanation of Carcinogenicity: OVEREXPOSURE TO AIRBORNE CONCENTRATIONS OF ASBESTOS M

AY LEAD TO ASBESTOSIS AND MESOTHELIOMA.

Effects of Overexposure:INHALATION: INHALATION OF AIRBORNE DUST CONTAINING ASBESTOS FIBERS ON REPEATED EXPOSURE MAY CAUSE OR CAN LEAD TO ASBESTOSIS / MESOTHELIOMA. SKIN: UNKNOWN. EYES: POTENTIAL IRRITATION FROM AIRBORNE DUST . INGESTION: UNKNOWN.

Medical Cond Aggravated by Exposure:RESPIRATORY DEFICIENCIES DUE TO REPEATED INHALATION OF AIRBORNE FIBERS.

=====
===== First Aid Measures =====

First Aid:INHALATI

ON: REMOVE TO FRESH AIR. OBTAIN MEDICAL ADVICE. SKIN: WASH EXPOSED AREA WITH SOAP AND WATER. EYES: FLOOD WITH WATER. IF IRRITATION OCCURS, GET MEDICAL ATTENTION. INGESTION: CONSULT A PHYSICIAN . OTHER: CHANGE CLOTHING AS REQUIRED TOAVOID CARRYING DUST PARTICLES INTO OTHER AREAS.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:MATERIAL IS NOT FLAMMABLE ; USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Proced

ures:COMBUSTION PRODUCTS OF THIS MATERIAL MAY BE TOXIC. USE A SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES INVOLVING CHEMCIAL PRODUCTS.

Unusual Fire/Explosion Hazard:MAY RELEASE ASBESTOS FIBERS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION. VACUUM OR WET CLEAN IF DUST IS INVOLVED. ANY VACUUM SYSTEM SHOULD BE EQUIPPED WITH AN OUTLET "HEPA" FILTER TO PREVENT REINTRODUCING ASBESTOS FIBERS

TO THE ATMOSPHERE.

Neutralizing Agent:NOT APPLICABLE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:HANDLE IN A MATTER TO MINIMIZE FORMATION OR RETENTION OF AIRBORNE DUST. USE PROPER PERSONAL PROTECTION FOR TASK AT HAND.

Other Precautions:AS MANUFACTURED, LOCKED-IN ASBESTOS MAY NOT PRESENT A HAZARD. ONLY WHEN THE ITEM IS SUBJECTED TO ABRASIVE ACTIONS & DUST IS GENERATED, THEN ASBESTOS FIBERS MAY BE RELEASED AND BECOME

A

IRBORNE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURES EXCEED ESTABLISHED LIMITS, A NIOSH APPROVED RESPIRATOR FOR ASBESTOS SHOULD BE USED. CONSULT YOUR SAFETY OFFICE/INDUSTRIAL HYGIENIST PERSONNEL FOR GUIDANCE FOR THE TASK AT HAND.

Ventilation:LOCAL EXHAUST IS RECOMMENDED IN SITUATIONS WHERE DUST IS GENERATED BY ABRASIVE ACTIONS, ABRASION OR OTHER MEANS.

Protective Gloves:RUBBER IF FRIABLE

Eye Protection:DUST-RESISTANT G

OGGLES, IF FRIABLE

Other Protective Equipment:AS REQUIRED FOR TASK AT HAND, AND THE GUIDANCE SET FORTH BY YOUR SAFETY OFFICE OR INDUSTRIAL HYGIENIST PERSONNEL.

Work Hygienic Practices:DO NOT INHALE DUST CREATED BY ABRADING ACTIONS. USE FULL PROTECTION AGAINST AIRBORNE FIBERS.AVOID AIRBORNE DUST CREATION

Supplemental Safety and Health

GENERIC "MSDS" CREATED FOR "NSN" REQUESTED BY "DDOU". IF MANUFACTURER BECOMES KNOWN, A MSDS WILL BE OBTAINED FOR MATERIAL PROCURED UNDER THI

S NSN AND THIS GENERIC "MSDS" WILL BE REMOVED.

=====
===== Physical/Chemical Properties =====

HCC:T6

Evaporation Rate & Reference:NONE

Solubility in Water:NOT SOLUBLE

Appearance and Odor:BRAKE LINING

Percent Volatiles by Volume:NONE

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE KNOWN

Stability Condition to Avoid:DO NOT BREATHE ASBESTOS FIBERS.

Hazardous Decomposition Products:MAY RELEASE ASBESTOS

FIBERS AND

PRODUCE TOXIC FUMES.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DUST SHOULD BE HANDLED AS A HAZARDOUS AIR POLLUTANT. USE LANDFILLS APPROVED FOR ASBESTOS DISPOSAL. NOTE IF ITEM UNDER CONSIDERATION FOR DISPOSAL IS "FRIABLE OR NON-FRIABLE". OBSERVE ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the De

partment

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.