View NSN Online: https://aerobasegroup.com/nsn/9140-00-247-4364

FARSTAD OIL INC -- DIESEL FUEL 1/FUEL OIL 1,3501/4195 -- 9140-00-247-4364

Product ID: DIESEL FUEL 1/FUEL OIL 1,3501/4195 MSDS Date:01/01/1991 FSC:9140 NIIN:00-247-4364 MSDS Number: BQMZJ === Responsible Party === Company Name: FARSTAD OIL INC Address:COUNTY RD 19 N Box:1842 City:MINOT State:ND ZIP:58702 Country:US Info Phone Num:701-852-1194 **Emergency Phone Num:70** 1-852-1194/800-424-9300(CHEMTREC) CAGE:3R470 === Contractor Identification === Company Name: FARSTAD OIL INC Address:COUNTY RD 19 N Box:1842 City:MINOT State:ND ZIP:58701 Country:US CAGE:3R470 Ingred Name: AROMATIC & PARAFFINIC HYDROCARBONS Fraction by Wt: >90% Other REC Limits:NONE RECOMMENDED Ingred Name:NAPHTHALENE (SARA III)

CAS:91-20-3 RTECS #:QJ0525000 Fraction by Wt: 3% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 PPM /15 STEL ACGIH TLV:10 PPM/15 STEL; 9293 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN. Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE-MAY CAUSE EYE IRRITATION, REDNESS, BLURRED VISION. PROLONGED/REPEATED SKIN CONTACT CAN CAUSE IRRITATION, DEFATTING & DERMATITIS. EXCESSIVE INHALATION OF VAPORS CAN CAUSE DIZZINESS, WEAKNESS, FATIGUE, NA USEA, HEADACHE, UNCONSCIOUSNESS. ORAL: VOMITING, DIARRHEA. ASPIRATION HAZARD.CHRONIC-NAPHTHALENE MAY DAMAGE KIDNEY & BLOOD. Explanation of Carcinogenicity: CAUSES LIVER TUMORS IN MICE. NIOSH **RECOMMENDS WHOLE DIESEL EXHAUST BE REGARDED AS A "POTENTIAL** OCCUPATIONAL CARCINOGEN". Effects of Overexposure: MAY CAUSE EYE IRRITATION, REDNESS, BLURRED VISION.PROLONGED/REPEATED SKIN CONTACT CAN CAUSE **IRRITATION, DEFATTING & DERMATITIS. EXCESSI VE INHALATION OF VAPORS** CAN CAUSE DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, H EADACHE, UNCONSCIOUSNESS. ORAL: VOMITING, DIARRHEA. ASPIRATION HAZARD.REPEATED EXPOSURE TO NAPHTHALENE DAMAGES KIDNEY & BLOOD Medical Cond Aggravated by Exposure: PRE-EXISTING DERMATITIS MAY BE AGGRAVATED.

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST.SKIN:WASH WITH SOAP & WATER.EYE:FLUSH WITH WATER FOR 15 MINUTES,HOLDING EYELIDS OPE

N.INHALED:REMOVE TO FRESH AIR & PROVIDE OXYGEN/CPR IF NEEDED.ORAL:DO NOT IN DUCE VOMITING.IF CONSCIOUS,DRINK TWO GLASSES OF WATER.CALL A PHYSICIAN.NOTE TO PHYSICAIN:ACTIVATED CHARCOAL SLURRY MAY BE ADMINISTERED.SUSPEND 50 GM ACTIVATED CHARCAOL/400 ML WATER.USE 5ML/KG(350 MAX)

Flash Point Method:TCC Flash Point:115F,46C Autoignition Temp:Autoignition Temp Text:410F Lower Limits:0.5 Upper Limits:6 Extinguishing

Media:CARBON DIOXIDE, FOAM/DRY CHEMICAL. WATER/FOAM MAY	
CAUSE FROTHING & CAN BE DANGEROUS IF SPRAYED INTO HOT, BURN	ING
LIQUID.	

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard:FORMS CARBON MONOXIDE,CARBON DIOXIDE & OTEHR MATERIALS.VAPORS CAN FORM EXPLOSIVE MIXTURE WITH AIR.VAPORS HEAVIER THAN AIR,CAN TRAVEL TO PILOT LIGHT & FLASH BACK

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS.VENTILATE AREA.DIKE SPILL.PREVENT LIQUID FROM ENTERING SEWERS/WATERWAYS.REMOVE SOURCES OF IGNITION.SOAK UP WITH SAWDUST,SAND,OIL DRY OR USE EXPLOSION-PROOF PUMPS.TRANSFER TO SUITABLE CONTAINERS FOR DISPOSAL.

Handling and Storage Precautions: STORAGE-STORE IN COOL VENTILATED AREA

AWAY FROM FLAME,SPARKS,HEAT & STRONG OXIDIZING AGENTS. Other Precautions:USE ONLY IN WELL VENTILATED AREA. DO NOT WELD, HEAT OR DRILL CONTAINER. EMPTY CONTAINER STILL CONTAIN HAZARDOUS/EXPLOSIVE VAPOR/LIQUID. DO NOT USE PRESSURE TO EMPTY DRUM OR EXPLOSION MAY RESULT. TOXIC FUMES MAY ACCUMULATE AND CAUSE DEATH.

Respiratory Protection:USE NIOSH-APPROVED RESPIRATORY PROTECTIVE EQUIPMENT FOR CLEANING LARGE SPILLS OR ENTRY INTO LARGE TANKS, VESSELS OR OTHER CONFINED SPACES. Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S). Protective Gloves:IMPERVIOUS SUCH AS NITRILE RUBBER Eye Protection:CHEMICAL SAFETY GLASSES/GOGGLES Other Protective Equipment:EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. Supplemental Safet y and Health

AVOID BREATHING VAPORS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. REMOVE CONTAMINATED CLOTHING PROMPTLY. KEEP OUT OF REACH OF CHILDREN.

HCC:F3 Boiling Pt:=166.C, 330.8F Vapor Pres:2 @ 68F Vapor Density:>1 Spec Gravity:0.81 Solubility in Water:INSOLUBLE Appearance and Odor:CLEAR LIQUID - PARAFFINIC ODOR

======== Stability and Re

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HIGH HEAT, SPARKS, STATIC ELECTRICITY, OPEN FLAMES AND OTHER SOURCES OF IGNITION (IF MATERIAL IS HEATED/VAPORS PRESENT) Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS SUCH AS CARBON MONOXIDE, CARBON DIOXIDE AND OTEHR TOXIC COMPOUNDS.

Waste Disposal Methods:TREATMENT, STORAGE,

TRANSPORTATION AND DISPOSAL

MUST BE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT FLUSH TO SURFACE WATER OR SANITARY SEWER SYSTEM. IT IS AN IGNITAB LE HAZARDOUS WASTE (RCRA).

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.