

ASHLAND PETROLEUM CO DIV OF ASHLAND OIL INC -- GASOLINE UNLEADED -- 9130-00-264-6218
===== Product Identification =====

Product ID:GASOLINE UNLEADED

MSDS Date:05/31/1989

FSC:9130

NIIN:00-264-6218

MSDS Number: BQNPK

=== Responsible Party ===

Company Name:ASHLAND PETROLEUM CO DIV OF ASHLAND OIL INC

Address:1409 WINCHESTER AVE

Box:391

City:ASHLAND

State:KY

ZIP:41114

Country:US

Info Phone Num:606-329

-3333

Emergency Phone Num:800-274-5263

CAGE:81355

=== Contractor Identification ===

Company Name:ASHLAND INC

Address:1409 WINCHESTER AVE

Box:391

City:ASHLAND

State:KY

ZIP:41114

Country:US

Phone:800-622-6846

CAGE:81355

===== Composition/Information on Ingredients =====

Ingred Name:GASOLINE

CAS:8006-61-9

RTECS #:LX3300000

Fraction by Wt: >95%

Other REC Limits:NONE SPECIFIED BY M.

OSHA PEL:300 PPM/500 STEL

ACGIH TLV:300 PPM/500STEL;9192

Ingred Name:BENZENE (SARA III)

CAS:71-43-

2

RTECS #:CY1400000
Fraction by Wt: 1-5%
OSHA PEL:1PPM/5STEL;1910.1028
ACGIH TLV:10 PPM; A2; 9192
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 3-7%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 3.8-9.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100
PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:P-XYLENE (P-DIMETHYLBENZENE) (SARA III)
CAS:106-42-3
RTECS #:ZE2625000
Fraction by Wt: 0.8-2.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:1,2,4-TRIMETHYLBENZENE (SARA III)
CAS:95-63-6
RTECS #:DC3325000
Fraction by Wt: 1-4%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:25 PPM
ACGIH TLV:25 PPM; 929

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
 Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
 Health Hazards Acute and Chronic:ACUTE-INHALATION:CNS DEPRESSION,
 IRRITATION OF RESPIRATORY TRACT. EYE:IRRITATION. SKIN:IRRITATION.
 INGESTION:GI DISTURBANCES, ASPIRATION PNEUMONITIS.
 CHRONIC:DERMATITIS, PNEUMONITIS, PULMONARY EDEMA, ANEMIA, LIVER &
 KIDNEY DAMAGE.

Explanation of Carcinogenicity:

CONTAINS B [71-43-2] WHICH IS

LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure:EYE:SEVERE IRRITATION, REDNESS, TEARING, BLURRED
 VISION; SKIN:IRRITATION, DEFATTING, DERMATITIS; INHALE: NASAL AND
 RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, ETC.;
 INGEST: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure:RESPIRATORY DISORDERS.

===== First Aid Measures =====

=====

First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED.
 EYE CONTACT:FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. SKIN
 CONTACT:WASH WITH SOAP AND WATER. GET MED ATTENTION IF SYMPTOMS
 PERSIST. INGESTION:DO NOT INDUCE VOMITING, DRINK 1-2 GLASSES OF
 WATER. GET MEDICAL HELP IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:-40F/-40C

Lower Limits:1.5

Extinguishing Media:USE CARBON DIOX
 IDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WITH A
 FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN
 FIGHTING FIRES.

Unusual Fire/Explosion Hazard:MATERIAL IS HIGHLY VOLATILE & READILY
 GIVES OFF VAPORS WHICH MAY TRAVEL ALONG THE GROUND OR BE MOVED BY
 VENTILATION & IGNITED BY PILOT LIGHTS, SPARKS, ETC.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: ELEMENAT

E ALL SOURCES OF IGNITION

AND ABSORB LIQUID ON VERMICULITE, INERT ABSORBENT, ETC, AND
TRANSFER TO HOOD. LARGE SPILL: ELEMIMATE IGNITION SOURCES. DIKE
AREA TO CONTAIN. PUMP LIQUID TO SALVAGE TANK FOR LATER DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS & OPEN
FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE. USE OR STORE ONLY
WITH ADEQU
ATE VENTILATION.

Other Precautions:DO NOT TRANSFER TO UNLABELED CONTAINERS. DO NOT USE
CUTTING OR WELDING TORCH ON THIS CONTAINER. KEEP OUT OF REACH OF
THE CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A NIOSH APPROVED AIR SUPPLIED RESPIRATOR IF
TLV IS EXCEEDED.

Ventilation:PROVIDE SUFFICIENT MECHANICAL VENTILATION AND/OR LOCAL
EXHAUST TO KEEP BELOW TLV.

Protective Gloves:NEOPRENE, NITRILE, RUBBER TYPES.

Eye Protection:

CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:CLOTHING AND BOOTS.

Work Hygienic Practices:DO NOT EAT, DRINK OR SMOKE WHILE WORKING WITH
THIS PRODUCT.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:70F/21C

Vapor Pres:325 MMHG

Spec Gravity:0.74

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:CLEAR LIQUID, GASOLINE ODOR.

Percent Volatiles by Volume:100

=====
===== Stability an

d Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: HIGH HEAT, OPEN FLAMES AND OTHER SOURCES
OF IGNITION

Hazardous Decomposition Products: NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods: RECLAIM, INCENERATE OR DISPOSE OF IN ACCORDANCE
WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.