View NSN Online: https://aerobasegroup.com/nsn/6850-00-294-0860

Product ID:SILICONE SPRAY LUBRICANT, E-1211 MSDS Date:03/12/1992 FSC:6850 NIIN:00-294-0860 **MSDS Number: BQNQM** === Responsible Party === Company Name:NOCO CO Address:23300 MERCANTILE ROAD City:CLEVELAND State:OH ZIP:44122-5921 Country:US Info Phone Num:216-464-8131 Emergency Phone Num:216-464-8131 CA GE:54095 === Contractor Identification === Company Name:NOCO CO Address:23300 MERCANTILE RD Box:City:CLEVELAND State:OH ZIP:44122-5921 Country:US Phone:216-464-8131 CAGE:54095

Ingred Name:N-HEPTANE CAS:142-82-5 RTECS #:MI7700000 Fraction by Wt: 13% Other REC Limits:NONE RECOMMENDED OSHA PEL:500 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 5% Other RE C Limits:NONE RECOMMENDED OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9293

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC CAS:64742-65-0 RTECS #:PY8038500 Fraction by Wt: 3% Other REC Limits:NONE RECOMMENDED ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:SILICON FLUID CAS:63148-62-9 Fraction by Wt: 3% Other REC Limits:NONE RECOMMENDED

Ingred Name:PROPANE CAS:74-98-6 RTECS #:TX2275000 Fraction by Wt: 14% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:ASPH YXIANT; 9293

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 61% Other REC Limits:NONE RECOMMENDED

Ingred Name:NON HAZARDOUS INGREDIENT Fraction by Wt: 1% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:MAY CAUSE DIZZINESS OR NARCOSIS IN HIGH CONCENTRATIONS. WILL CAUSE DEFATT

 ING OF SKIN. EFFECTS ARE REVERSIBLE. LONG TERM EXPOSURE (YEARS) TO HIGH CONCENTRATIONS OF VAPOR MAY CAUSE LUNG, LIVER OR KIDNEY DAMAGE. THE SOLVENTS LISTED HAVE BEEN REPORTED TO AFFECT THE CENTRAL NERVOUS SYSTEM. Explanation of Carcinogenicity:PRESENTLY NOT ON ANY LIST. Effects of Overexposure:INHALATION-DIFFICULTY BREATHING. SKIN-REDNESS. INGESTION-VOMITING. Medical Cond Aggravated by Exposure:HEART DISEASE; RESPIRATORY DISORDERS.
<pre>====================================</pre>
First Aid:GIVE OXYGEN - DO NOT INDUCE VOMITING - GASTRIC LAVAGE - WASH EYES AND SKIN WITH WATER.
======================================
Flash Point Method:TOC Flash Point:-40F,-40C Autoignition Temp:Autoignition Temp Text:UNKNON Lower Limits:1.8 Upper Limits:12.0 Extinguishing Media:USE WATER FOG, DRY CHEMICAL OR CARBON DIOXIDE. Fire Fighting Procedures:AEROSOL CANS MAY RUPTURE WHEN HEATED. Unusual Fire/Explosion Hazard:HEATED CANS MAY BURST.
======================================
Spill Release Procedures: USE ABSORBENT SWEEPING COMPOUND TO SOAK UP MATERIAL. PUT INTO CONTAINER. DISPOSE AS HAZARDOUS WASTE.
======================================
 Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPRAKS OR OPEN FLAME. STORE AT TEMPERATURE BELOW 120F. Other Precautions:WHEN SPRAYING MORE THAN ONE HALF CAN CONTINOUSLY OR MORE THAN ONE CAN CONSTRUCTIVELY , USE NIOSH APPROVED RESPIRATOR.
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS IF ABOVE TLV LIMIT EXCEEDING. Ventilation:LOCAL EXHAUST: YES. Protective Gloves:NONE REQUIRED IF SPRAYING. Eye Protection:WEAR EYE PROTECTION. Other Protective Equipment:LONG SLEEVE AND LONG PANTS. Work Hygienic Practices:DO NOT SMOKE WHILE USING. WASH HANDS AFETR USE. Supplemental Safety and Health NONE

/Chemical Properties ==============

HCC:F8 Boiling Pt:B.P. Text:40-212F Vapor Pres:64 Vapor Density:4.0 Spec Gravity:0.8 Evaporation Rate & amp; Reference: