

PATCH RUBBER COMPANY -- PATCHBOND -- 2640-00-404-0754

===== Product Identification =====

Product ID:PATCHBOND

MSDS Date:01/09/1992

FSC:2640

NIIN:00-404-0754

Kit Part:Y

MSDS Number: BQQFK

=== Responsible Party ===

Company Name:PATCH RUBBER COMPANY

Box:H

City:ROANOKE RAPIDS

State:NC

ZIP:27870

Country:US

Info Phone Num:919-536-2574

Emergency Phone Num:919-536-2574,CHEMTREC 800-424-9300

CAGE:FO808

==

= Contractor Identification ===

Company Name:MYERS TIRE SUPPLY

Address:1293 SOUTH MAIN STREET

Box:City:AKRON

State:OH

ZIP:44301

Country:US

Phone:216-253-5592, FAX: 216-253-1882

CAGE:85803

Company Name:PATCH RUBBER CO

Address:BECKER INDUSTRIAL PARK

Box:H

City:ROANOKE RAPIDS

State:NC

ZIP:27870

Country:US

Phone:919-536-2574/800-424-9300(CHEMTREC)

CAGE:17124

Company Name:PATCH RUBBER COMPANY

Box:H

City:ROANOKE RAPIDS

State:NC

ZIP:27870

Phone:(919) 536-2574

CAGE:FO808

===== Composition/Info

Information on Ingredients =====

Ingredient Name: METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS: 71-55-6

RTECS #: KJ2975000

Fraction by Wt: 96-98%

Other REC Limits: NONE SPECIFIED BY M.

OSHA PEL: 350 PPM/450 STEL

ACGIH TLV: 350 PPM/450 STEL; 9293

EPA Rpt Qty: 1000 LBS

DOT Rpt Qty: 1000 LBS

Ozone Depleting Chemical: 1

===== Hazards Identification =====

LD50 LC50 Mixture: ORAL LD50 (RAT): 10-12 G/KG

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Report

Effects of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: INHALATION: CNS DEPRESSION & DAMAGE, RESPIRATORY SYSTEM IRRITATION, UNCONSCIOUSNESS, DEATH.

EYES: IRRITATION. SKIN: IRRITATION, DERMATITIS. INGESTION:

IRRITATION OF MOUTH AND GI TRACT, ASPIRATION INTO LUNGS MAY LEAD TO CHEMICAL PNEUMONITIS WHICH IS POTENTIALLY FATAL.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: INHALATION: COUGHING, DIZZINESS, NAUSEA, LIGHTEADEDNESS, HEADACHE, LOSS

OF COORDINATION & EQUILIBRIUM,

UNCONSCIOUSNESS & DEATH. EYES: DISCOMFORT, PAIN, IRRITATION.

SKIN: IRRITATION. INGESTION: NAUSEA, VOMITING, DIARRHEA.

Medical Condition Aggravated by Exposure: NONE KNOWN.

===== First Aid Measures =====

First Aid: INHALATION: REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED.

EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. SKIN CONTACT: WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST.

INGESTION: DO NOT INDUCE VOMITING, DRINK 1-2 GLASSES OF WATER. GET MEDICAL HELP IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point: NONE

Lower Limits: 7%

Upper Limits: 15%

Extinguishing Media: WATER, DRY CHEMICAL, OR CO2.

Fire Fighting Procedures: FIRE FIGHTERS, WEAR NIOSH/MSHA APPROVED

PRESSURE-DEMAND, SELF-CONTAINED BREATHING APPARATUS FOR POSSIBLE EXPOSURE TO HYDROGEN CHLORIDE & TRACES OF PHOSGENE.

Unusual Fire/Explosion Hazard: VAPORS IN

A CONFINED/POORLY VENTILATED

AREA CAN IGNITE UPON CONTACT W/A HIGH ENERGY SPARK/FLAME/HIGH INTENSITY SOURCE OF HEAT. THIS CAN OCCUR AT 7-15% BY VOLUME

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE/VENTILATE AREA. WEAR PROTECTIVE EQUIP. RECOVER ON ABSORBENTS (SAWDUST/VERMICULITE). SWEEP INTO CLOSED CONTAINERS FOR DISPOSAL. AFTER ALL VISIBLE TRACES ARE REMOVED, WET VACUUM THE AREA. IF AREA IS POROUS, REMOVE & PLACE IN

CLOSED CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. STORE ONLY IN CLOSED, PROPERLY LABELED CONTAINERS. DON'T USE W/ALUMINUM. USE W/ADEQUATE VENTILATION.

Other Precautions:DON'T USE CURING/WELDING TORCHES ON DRUMS UNLESS PROPERLY PURGED/CLEANED. AVOID CONTACT W/EYES/SKIN/BREATHING VAPORS. NOT SUITABLE FOR VAPOR DEGREASING. AVOID MIXING W/CAUSTIC SODA/POTASH/OXIDIZING MATERIALS. SHOCK SENSITIVE COMPOUNDS FORM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF >TLV, USE A HALF OR FULL FACEPIECE ORGANIC VAPOR CHEMICAL CARTRIDGE OR CANISTER RESPIRATOR. USE SCBA OR FULL FACEPIECE AIRLINE RESPIRATOR W/AUXILIARY SCBA OPERATED IN THE PRESSURE-DEMAND MODE. RESPIRATORS MUST BE APPROVED BY NIOSH/MSHA.

Ventilation:LOCAL EXHAUST/MECHANICAL: AS APPROPRIATE TO KEEP