

BARNEBEY-& SUTCLIFFE CO SUB OF CVI INC -- VIRGIN ACTIVATED CARBON -- 4440-00-355-7755

=====
Product Identification
=====

Product ID:VIRGIN ACTIVATED CARBON

MSDS Date:01/01/1987

FSC:4440

NIIN:00-355-7755

MSDS Number: BQSDV

=== Responsible Party ===

Company Name:BARNEBEY-& SUTCLIFFE CO SUB OF CVI INC

Address:835 N CASSADY AVE

Box:2526

City:COLUMBUS

State:OH

ZIP:43216

Country:US

Info Phone Num:614-2

58-9501

Emergency Phone Num:614-451-2392

Preparer's Name:MOHAMMED A. BAYATT

CAGE:LO287

=== Contractor Identification ===

Company Name:AERO-DRI CORP DIV DAVEY COMPRESSOR

Address:REPLACED BY AERO-DRI DIV OF KECO IND

Box:City:CINCINNATI

State:OH

Country:US

CAGE:52966

Company Name:AERO-DRI CORP DIV KECO INDUSTRIES INC

Address:7375 INDUSTRIAL RD

Box:City:FLORENCE

State:KY

ZIP:41042

Country:US

Phone:606-525-2102

CAGE:82990

Company Name:BARNEBEY SUTCLIFFE CORP

Address:835 N CASSADY AVE

Box:City:COLUMBU

S
State:OH
ZIP:43219-2203
Country:US
Phone:614-258-9501
CAGE:85335
Company Name:BARNEBEY-& SUTCLIFFE CO SUB OF CVI INC
Address:835 N CASSADY AVE
Box:2526
City:COLUMBUS
State:OH
ZIP:43216
Country:US
Phone:614-258-9501
CAGE:LO287

=====
Composition/Information on Ingredients
=====

Ingred Name:GRAPHITE, SYNTHETIC (CARBON)
CAS:7440-44-0
RTECS #:FF5250100
Fraction by Wt: 80-97%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name:WATE
R
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 2-8%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ASH
Fraction by Wt: 1-12%
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INHALATION OF DUST MAY CAUSE
RESPIRATORY IRRITATION. EYE CONTACT MAY CAUSE MINOR IRRITATION.
NON-TOXIC THROUGH

SKIN CONTACT; SKIN ABSORPTION, OR INGESTION.

CHRONIC: NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity:NO INGREDIENT IS LISTED BY NTP, IARC, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:INHALED: COUGHING, SNEEZING, SHORTNESS OF BREATH. EYES: REDNESS, ITCHING, DISCOMFORT.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALED: MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS

PERSIST. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES, HOLD LIDS OPEN. SEE DOCTOR IF SYMPTOMS PERSIST. SKIN: WASH WITH SOAP AND WATER. SEE DOCTOR IF SYMPTOMS DEVELOP. INGESTED:NONE UNLESS SYMPTOMS DEVELOP. IF SYMPTOMS DEVELOP, SEE DOCTOR.

=====
===== Fire Fighting Measures =====

Extinguishing Media:MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE GEAR.

Unusual

Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER. DUST MAY BE COMBUSTIBLE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SWEEP UP, AVOIDING CREATING DUST, AND PLACE IN A CONTAINER FOR LATER DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:SINCE WET ACTIVATED CARBON ABSORBS OXYGEN, DO NOT ENTER CLOSED VESSELS WITHOUT SC

BA. HIGH BED

TEMPERATURE DURING KETONE ABSORPTION MAY CAUSE BED FIRE.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.IF ENGINEERING CONTROLS OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR FOR DUST OR SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IN ACCORDANCE WITH 29 CFR 1910.134.

Ventilation:NONE NORMALLY REQUIRED.

Protective Glo

ves:DISPOSABLE RUBBER OR LATEX

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING,
DRINKING, OR SMOKING.

Supplemental Safety and Health

PRODUCT IS CONTAINED IN A STEEL CARTRIDGE, NSN IS FOR SYTEM OF
CARTRIDGE AND DESSICANT (ACTIVATED CHARCOAL OR CARBON). MSDS IS FOR
DESSICANT. SYSTEM IS CONSIDERED AN ARTICLE.

===== Physical/Chemical Properties =====

=====

HCC:N1

Spec Gravity:0.3 (WATER=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK IRREGULAR GRANULES W/O ODOR IN A STEEL
CARTRIDGE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

KETONES IN AIR

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:MANUFACTURER RECOMMENDS INCINE
RATION OR SANITARY

LANDFILL. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice
to verify and

assume responsibility for the suitability of this information to their
particular situation.