

JAMAK FABRICATION INC, DBA PORTER SEAL CO -- SOLASIL 2200 -- 5970-00-449-5161
===== Product Identification =====

Product ID: SOLASIL 2200

MSDS Date: 04/30/1993

FSC: 5970

NIIN: 00-449-5161

Kit Part: Y

MSDS Number: BQSDZ

=== Responsible Party ===

Company Name: JAMAK FABRICATION INC, DBA PORTER SEAL CO

Address: 1401 NORTH BOWIE DRIVE

City: WEATHERFORD

State: TX

ZIP: 76086

Country: US

Info Phone Num: 817-594-877

1

Emergency Phone Num: 817-594-8771

CAGE: 1EF46

=== Contractor Identification ===

Company Name: JAMAK FABRICATION INC, DBA PORTER SEAL CO

Address: 1401 NORTH BOWIE DRIVE

Box: City: WEATHERFORD

State: TX

ZIP: 76086

Country: US

Phone: 817-594-8771

CAGE: 1EF46

Company Name: PORTER SEAL CO

Address: 1401 N BOWIE DR

Box: City: WEATHERFORD

State: TX

ZIP: 76086

Country: US

Phone: 817-594-8771

CAGE: 4F044

===== Composition/Information on Ingredients =====

Ingred Name: IRON OXIDE/FERRIC OXIDE

CAS: 1309-37-1

RTECS #:NO7400000
Fraction by Wt: 30%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5 MG/M3(FE),B2; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE AND CHRONIC - NO ADVERSE
EFFECTS.
Effects of Overexposure:NONE
Medical Cond Aggravated by Exposure:NOT KNOWN.

===== First Aid Measure

s =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS DEVELOP. EYE/SKIN:FLUSH
WITH WATER. INHALED:UNLIKELY. INGESTION:DO NOT INDUCE VOMITING. IF
CONSCIOUS, DRINK LARGE AMOUNT OF WATER AND GET MEDICAL ATTENTION.
NEVER GIV E ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Extinguishing Media:CARBON DIOXIDE OR FOAM
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
SELF CONTAINED
BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NOT KNOWN

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE USING ABSORBENT MATERIALS.
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM STRONG OXIDIZING
AGENTS.
Other Precautions:WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respirat

ory Protection:NO SPECIAL REQUIREMENTS
Ventilation:NO SPECIAL REQUIREMENTS
Protective Gloves:NO SPECIAL REQUIREMENTS
Eye Protection:SAFETY GOGGLES
Other Protective Equipment:EYE WASH STATION, EMERGENCY SHOWER, NORMAL
WORK CLOTHING COVERING ARMS AND LEGS
Work Hygienic Practices:NORMAL PRACTICES FOR A LABORATORY.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1
Spec Gravity:1.50
Solubility in Water:NIL
Appearance and Odor:RED PASTE WITH SLIGHT ETHANOL ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS
Stability Condition to Avoid:EXCESSIVE HEAT
Hazardous Decomposition Products:SILICON DIOXIDE AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE
AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.