View NSN Online: https://aerobasegroup.com/nsn/9140-00-273-2394

Product ID:DISTILLATE FUELS MSDS Date:02/01/1989 FSC:9140 NIIN:00-273-2394 **MSDS Number: BQWKS** === Responsible Party === Company Name: FARMLAND INDUSTRIES, INC., BULK PERTOLEUM DIV. Box:7305 City:KANSAS CITY State:MO ZIP:64116-0005 Country:US Info Phone Num:316-251-4000 **Emergency Ph** one Num:316-251-4000 CAGE:6G072 === Contractor Identification === Company Name: FARMLAND INDUSTRIES, INC., BULK PERTOLEUM PROD DIV. Box:7305 City:KANSAS CITY State:MO ZIP:64116-0005 Country:US Phone:316-251-4000, CHEMTREC 800-424-9300 CAGE:6G072 Ingred Name: ALIPHATIC PETROLEUM DISTILLATE CAS:68476-30-2 Fraction by Wt: >95% Other REC Limits:NONE RECOMMENDED

Ro

utes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic: VAPORS MAY CAUSE DIZINESS OR ASPHYXIATION. INGESTION CAN CAUSE IRRITATION, NAUSEA, VOMITING. ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS. CHRONIC:NOT PROBABLE. Explanation of Carcinogenicity: PRODUCTS OF SIMILAR COMPOSITION CAUSED WEAK - MODERATE POSITIVE MOUSE SKIN CANCER, MIXED RESULTS IN MUTAGENICITY. Effects of Overexpos ure: IRRITATION OF EYES AND SKIN. DERMATITIS IS POSSIBLE. Medical Cond Aggravated by Exposure: RESPIRATORY ILLNESSES First Aid: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR AND GIVE OXYGEN. EYE AND SKIN EXPOSURES SHOULD BE WASHED WITH LARGE AMOUNTS OF WATER. IF INGESTED, DO NOT INDUCE VOMITING. KEEP WARM AND GET MEDICAL HELP. Flash Point Metho d:PMCC Flash Point:#100F,38C Lower Limits:0.7 Upper Limits:5.0 Extinguishing Media: DRY CHEMICAL, FOAM OR FOG, WATER SPRAY AND CARBON DIOXIDE Fire Fighting Procedures: COOL CONTAINERS WITH WATER, WATER OR FOAM SPRAYED INTO CONTAINERS OF HOT BURNING PRODUCT COULD CAUSE FROTHING AND ENDANGER FIRE FIGHTERS. Unusual Fire/Explosion Hazard: EMPTY CONTAINERS CAN EXPLODE WHEN HEAT IS APPLIED. VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL ALONG GROUND/FLOOR, THEN 'FLASH BACK' FROM DISTANT IG NITION SOURCE. Spill Release Procedures: ELIMINATE SOURCES OF IGNITION. STOP LEAK IF POSSIBLE. DIKE AREA TO CONTAIN SPILL AND PREVENT RUN-OFF TO STREAMS, SEWERS, ETC. PUMP MATERIAL TO SALVAGE VESSEL. Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY MFR. Handling and Storage Precautions: KEEP AWAY FROM HEAT SPARKS AND OPEN FLAME.

Other Precaution

s:NONE

Respiratory Protection: CHEMICAL CARTRIDGE RESPIRATOR IF VAPOR CONCENTRATION EXCEEDS TLV.

Ventilation:EXPLOSION PROOF IF NEEDED TO MAAINTAIN EXPOSURES BELOW TLV. Protective Gloves:NEOPRENE, OR NITRILE, OTHER RESISTANT Eye Protection:SPLASH PROOF CHEMICAL SAFETY GOGGLES Other Protective Equipment:"WHERE OPERATIONS AND EXPOSURE WARRENT." Work Hygienic Practices:MFR: ? HMIS:USE GOOD INDUSTRIAL HYGIENE PRACTICE. AVOI D UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health

KEY2:KT MSDS IS SKETCHY. THEY CITE ASHLAND PETROLEUM CO AS SOURCE OF CARCINOGENICITY INFO, HMIS SUPPLIED THE YES/NO CARCINOGENS. FIELDS STARTING WITH "#" INDICATE THAT THE INFORMATION WAS TAKEN FROM THE SPECIFICATION RATHER THAN THE MSDS.

HCC:F4 NRC/State Lic Num:NONE Boiling Pt:B.P. Text:#