

DEFT INC -- COMP B, MIL-P-53030 PC 44W007 CAT -- 8010-01-193-0521

===== Product Identification =====

Product ID:COMP B, MIL-P-53030 PC 44W007 CAT

MSDS Date:06/30/1992

FSC:8010

NIIN:01-193-0521

Kit Part:Y

MSDS Number: BQYLL

=== Responsible Party ===

Company Name:DEFT INC

Address:17451 VON KARMAN AVENUE

City:IRVINE

State:CA

ZIP:92714

Country:US

Info Phone Num:714-474-0400

Emergency Phone Num:714-47

4-0400 800-424-9300(CHEMTREC)

Preparer's Name:MIKE SMITH

CAGE:33458

=== Contractor Identification ===

Company Name:DEFT INC

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Phone:800 424-9300

CAGE:33458

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:NITROETHANE

CAS:79-24-3

RTECS #:KI5600000

Fraction by Wt: 15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:AROMATIC HYDROCARBON

CAS:64742-95-6

Fraction by Wt: < 5%

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: VAPORS IRRITATING TO EYES, NOSE & THROAT. INHALATION: HEADACHES, DIFFICULT BREATHING & LOSS OF CONSCIO

USNESS. CHRONIC: PROLONGED CONTACT WILL CAUSE DRYING & CRACKING TO SKIN, DUE TO DEFATTING A CTION. SKIN SENSITIZATION, ASTHMA OR OTHER ALLERGIC RESPONSES MAY DEVELOP.

Effects of Overexposure:INHALATON:

IRRITATION.HEADACHE,DIZZINESS,STAGGERING

GAIT,CONFUSION,UNCONSCIOUS./COMA.INGESTION: ACUTE: CORROSIVE ACTION TO MOUTH,STOMACH,DIGESTIVE TRACT.VOMITING ASPIRATION OF

SOLVENT,CHEMICAL PNEUMON ITIS.SKIN&EYES:

IRRITATION.SWELLING,REDNESS,RASH.LIQUID,AREOSOLS,VAPORS,TEARING.

SKI

N-PROLONGED CONTACT DRYING/CRACKING.

Medical Cond Aggravated by Exposure:ASTHMA AND ANY OTHER RESPIRATORY DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMITITIS.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION AS NEEDED. ASTHMATIC TYPE SYMPTOMS DEVELOP IMMED. OR DELAY.GET MEDICAL ATTENTION. SKIN: REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH AFFECTED AREAS WITH SOAP & WATER

. EYES: FLUSH

WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITIN. DON'T GIVE ANYTHING TO AN UNCONSCIOUS PERSON. GET MEDICAL ATTENT.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:87.0F,30.6C

Lower Limits:1.00%

Extinguishing Media:FOAM, DRY CHEMICAL, WATER FOG, ALCOHOL FOAM, CO2.

Fire Fighting Procedures:FULL FIRE FIGHTING EQUIP. WITH SCBA & FULL PROTECTIVE CLOTHING. WATER MAY BE USED TO COO

L CLOSED CONTAINERS TO

PREVENT PRESSURE BUILD-UP,AUTO IGNITION/EXPLOSION

Unusual Fire/Explosion Hazard:ISOLATE HEAT,SPARKS,ELECTRICAL

STATIC,FLAMES.CLOSED CONTAINERS EXPLODE EXPOSED HEAT.EMERGENCY
CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS HEALTH HAZARD.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE
ALL SOURCES OF IGNITION (FLAMES,SPARKS,HOT SURFACES). VENTILATE
AREA CONTAIN A
ND REMOVE WITH INERT ABSORBENT AND NON-SPARKING
TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED TO COMPLY
WITH OSHA 1910.106 AVOID STORING NEAR HIGH TEMPERATURES, FIRE, OPEN
FLAMES, SPARKS, STORE IN WELL VENTIL. AREA.

Other Precautions:PREVENT PROLONGED BREATHING OF VAPORS/MIST. PROLONGED
OVEREXPOSURE ALLERGIC REACTION.DO NOT TAKE INTERNALLY. WASH HANDS
BEFORE EATING, SMOKING, OR USING W
ASHROOM. SMOKE IN DESIGNATED
AREAS ONLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR RECOMMENDED. FRESH AIR SUPPLY IS
NECESSARY. OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE. VENTILATION
SHOULD BE PROVIDED TO KEEP EXPOSURE LEVELS BELOW THE OSHA
PERMISSIBLE LIMITS.

Ventilation:AIRBORNE CONCENTRATIONS OF SOLVENT VAPORS/MIST BELOW
RESPECTIVE TLV'S.REMOVE ALL IGNITION SOURCES (SPARKS,FLAME,ETC).

Protective Gloves:COTTON,
NEOPRENE, RUBBER, POLYETHYLENE.

Eye Protection:SAFETY GLASSES, CHEMICAL GOGGLES.

Other Protective Equipment:USE OF LONG SLEEVE & LONG LEG CLOTHING
RECOMMENDED. REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE.
EYES: FACE SHIELD.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:237 TO 335F

Vapor Density:> AIR

Spec Gravity:1.12845

Evaporation Rate & Reference:..96

Solubility in Water:INSOLUBLE

Appearance and Odor:

AMBER LIQUID WITH SOLVENT ODOR

Percent Volatiles by Volume:21.8

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS AND STRONG LEWIS OR MINERAL ACIDS.

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, OR OPEN FLAMES.

AVOID UNCONTROLLED REACTIONS WITH AMINES.

Hazardous Decomposition Products:HIGH HEAT/TEMPERATURE: CARBON

MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN. ALDEHYDES & ACIDS

FORMED DURI

NG COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MUST BE DISPOSED OF IN ACCORDANCE WITH
FEDERAL, STATE, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY
CONTAINERS MUST BE HANDLED WITH CARE, DUE TO PRODUCT RESIDUE AND
FLAMMABLE VAPOR DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of De

fense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.