View NSN Online: https://aerobasegroup.com/nsn/8010-01-353-3693

Product ID:CAT, 1-COAT, TT-P-2756, 34097 PC 03 GN 226 MSDS Date:12/21/1992 FSC:8010 NIIN:01-353-3693 Kit Part:Y MSDS Number: BQYQP === Responsible Party === Company Name: DEFT INC CHEMICAL COATING DIV Address:17451 VON KARMAN AVE City:IRVINE State:CA ZIP:92714-6205 Cou ntry:US Info Phone Num:714-474-0400 Emergency Phone Num:800-424-9300 CHEMTREC Preparer's Name:NORM GAUL CAGE:33461 === Contractor Identification === Company Name: DEFT, INC. Address:17451 VON KARMAN AVE City:IRVINE State:CA ZIP:92614 Country:US Phone:949-474-0400 CAGE:33461

Ingred Name:ALIPHATIC ISOCYANATE CAS:28182-81-2 RTECS #:HQ9170000 Fraction by Wt: 60% Other REC Limits:NONE SPECIFIED

Ingred Name: ETHYL-3-ETHOXYPROPIONAT

E CAS:763-69-9 RTECS #:UF3325000 Fraction by Wt: 20% Other REC Limits:NONE SPECIFIED

Ingred Name:N-BUTYL ACETATE CAS:123-86-4 RTECS #:AF7350000 Fraction by Wt: 15% Other REC Limits:NONE SPECIFIED OSHA PEL:150 PPM/STEL 200 PPM ACGIH TLV:150 PPM/STEL 200 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:VOC: 400 G/L RTECS #:9999999VO Other REC Limits:NONE SPECIFIED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:

NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: VAPORS ARE IRRITATING TO EYES, NOSE, & THROAT. INHALATION MAY CAUSE HEADACHES, DIFFICULT BREATHING AND LOSS OF CONSCIOUSNESS. CHRONIC: AS A RESULT OF OVEREXPOSURE OR SINGLE LARGE DOSE, SOME IND IVIDUALS MAY DEVELOP ISOCYANATE SENSITIZATION WHICH MAY LATER CAUSE THEM TO REACT TO EXPOSURE OF ISOCYANATE LEVELS.

Effects of Overexposure:INHALATION: HEADACHE, DIZZINESS, STAGGERING GA

IT, CONFUSION, UNCONSCIOUSNESS OR COMA. EYES: LIQUID, AREOSOLS, VAPORS TEARING, REDNESS, SWELLING, STINGING. SKIN: ISOCYANATES REACT W/SKIN PROTEIN & MOIS TURE, IRRITATING. RASH. SKIN ABSORPTION: DRYING, SKIN CRACK.INGESTION: MOUTH/STOMACH CORROSIVE. DO NOT INDUCE VOMITING.

Medical Cond Aggravated by Exposure:ASTHMA AND ANY OTHER RESPIRATORY DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMITITIS. ISOCYANATE SENSITIZATION.

First Aid:INHALATION: REMOVE TO FRESH AIR. ARTIFICIAL RESPIRATION AS NEEDED. ASTHMATIC TYPE SYMPTOMS. GET MEDICAL ATTENTION. SKIN: WASH AFFECTED AREAS WITH SOAP & WATER. REMOVE & WASH CONTAMINATED CLOTHING BEFO RE REUSE. EYES: FLUSH FOR 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION. DO NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON.

Flash Point Meth od:TCC Flash Point:76.0F,24.4C Lower Limits:1.05% Upper Limits:7.60% Extinguishing Media:FOAM,DRY CHEMICAL,WATER FOG,CO2,ALCOHOL FOAM. Fire Fighting Procedures:H2O TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP, AUTO IGNITION/EXPLOSION. DURING A FIRE HDI VAPORS MAY BE GENERATED BY COMBUSTION OR THERMAL DECOMP. Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, SPARKS, ELECTRICAL STATIC. MAY EXPLODE WHEN EXPOSED TO HEAT. OVEREXPOSURE TO DECOMPOSITION PRODUCTS HEALTH HAZARD. NOT IMMEDIATELY APPARENT

Spill Release Procedures: EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES). VENTILATE AREA CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106 AVOID STORING NEAR

HEAT, FIRE, FLAMES, SPARKS.

STORE IN WELL VENTILATED AREAS.TIGHTLY CLOSED.

Other Precautions: KEEP UPRIGHT TO PREVENT LEAKAGE. PREVENT PROLONGED BREATHING. PROLONGED OVEREXPOSURE ALLERGIC REACTION. AVOID CONTACT WITH SKIN & EYES. DO NOT TAKE INTERNALLY. WASH HANDS BEFORE EATING OR SMOKING OR U SING WASHROOM. SMOKE IN DESIGNATED AREAS

======= Exposure Controls/Personal Protection ===============

Respiratory Protection:OBSERVE OSHA REGUALTIONS FOR RESPIRATOR. PROPER VEN

TILATION. KEEP EXPOSURE LEVELS DOWN AND AIR VAPORS.
Ventilation: AIRBORNE CONCENTRATIONS OF SOLVENT, HDI & POLYISOCYANATED BELOW TLV'S.REMOVE ALL IGNITION SOURCES. HEAT, FLAME, SPARKS.
Protective Gloves: COTTON, NEOPRENE, RUBBER, POLYETHYLENE.
Eye Protection: SAFETY/CHEMICAL GOGGLES, FULL-FACE SHIELD
Other Protective Equipment: THE USE OF LONG SLEEVE & LONG LEG CLOTHING IS RECOMMENDED. REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health

HCC:F2

Boiling Pt:B.P. Text:260 TO 401F Vapor Density:> AIR Spec Gravity:1.03121 Evaporation Rate & amp; Reference:.47 Solubility in Water:INSOLUBLE Appearance and Odor:AMBER LIQUID WITH SOLVENT ODOR Percent Volatiles by Volume:41.7

Stability Indicator/Materials to Avoid:YES
WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS AND SURFACE ACTIVE MATERIALS.
Stability Condition to Av
oid:CONTACT WITH MOISTURE, MATERIAL WHICH REACT WITH ISOCYANATES AND HIGH TEMPERATURES.
Hazardous Decomposition Products:BY HIGH HEAT/TEMPERATURE: CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN, TRACES OF HCN AND HDI.

Waste Disposal Methods:WASTE MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL REGULATIONS. EMPTY CONTAINERS MUST BE HANDLED WITH CARE, DUE TO PRODUCT RESIDUE AND FLAMMAB LE VAPOR DO

NOT INCINERATE CLOSED CONTAI NERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitabil ity of this information to their particular situation.