

FARWEST PAINT MANUFACTURING CO -- EXTERIOR ACRYLIC LATEX FOR WOOD AND MASONRY
-- 8010-00-055-5100

===== Product Identification =====

Product ID:EXTERIOR ACRYLIC LATEX FOR WOOD AND MASONRY

MSDS Date:06/01/1992

FSC:8010

NIIN:00-055-5100

MSDS Number: BRFKV

=== Responsible Party ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 S 133RD ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Info Pho

ne Num:206-244-8844

Emergency Phone Num:206-941-1619

Preparer's Name:NORMA HABEEB

CAGE:2F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 S 133RD ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:2F266

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 1.59%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM

EPA Rpt Qty:1

LB
DOT Rpt Qty:1 LB

Ingred Name:GYLCOL ETHER (SARA 313)
CAS:25265-77-4
RTECS #:UF6000000
Fraction by Wt: 1.04%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM

Ingred Name:VOC 94 G/L (LESS WATER)
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: PROLONGED INHALATION, IN

CONFINED AREAS, MAY LEAD TO MUCOUS MEMBRANE IRRITATION, DIZZINESS,
HEADACHE. SKIN: IRRITATION OF THE SKIN. EYE: IRRITATION OF THE
EYES. INGESTION: AMOUNTS INGESTED INCIDENTAL TO CONSUMER AND
INDUSTRIAL HANDLING ARE NOT LIKELY TO CAUSE INJURY, HOWEVER,
INGESTION OF LARGER AMOUNTS

Effects of Overexposure:COULD CAUSE SERIOUS INJURY
Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH
SAFE HANDLING INSTRUCTIONS.

=====
===== First Aid Measures =====
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS
DEVELOP, SEEK MEDICAL ATTENTION AT ONCE. SKIN: WASH OFF QUICKLY
WITH PLENTY OF WATER, THEN SOAP AND WATER. REMOVE AND WASH
CONTAMINATED CLOTHIN G BEFORE REUSE. EYE: FLUSH IMMEDIATELY WITH
LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS, FOR AT LEAST 15
MINUTES. OBTAIN EMERGENCY MEDICAL TREATMENT.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:TC

C

Extinguishing Media:FOAM, DRY CHEMICAL, WATER OR WATER FOG

Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT ADJACENT CONTAINERS

Unusual Fire/Explosion Hazard:WILL NOT BURN. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT OR FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID TEMPERATURES BELOW 40F. KEEP FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND APPROPRIATELY LABELED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA FOR PROTECTION AGAINST MATERIALS IN SECTION II.

Ventilation:LOCAL EXHST PREFERABLE. GEN EXHST ACCEPTABLE IF THE EXPOS TO MATLS IN SECTION II IS MAINTAINED BELOW APPLIC EXPOS LIMITS

Protective Gloves:WEAR GLOVES RECOMMENDED-GLOVE SUPPLIER

Eye Protection:SFTY SPECTACLES W/UNPERFORATED SIDESHLDs

Other Protective Equipment:EYE WASH, SAFETY SHOWERS, GOGGLES, SAFETY GLASSES, IMPERVIOUS GLOVES

Work Hygienic Practices:KEEP WORK AREA CLEAN AND FREE FROM SPILLS AND LEAKS. ALWAYS WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE HANDLING#

Supplemental Safety and Health #FOOD, DRINK OR SMOKING.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Vapor Pres:23.8 @ 68F

Vapor Density:> THAN AIR

Spec Gravity:11.58 LB/GL

pH:7.0

Viscosity:75-85 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:INFINITE

Appearance and Odor:THIXOTROPIC LIQUID WITH SLIGHT ODOR, COLOR OF TINT Per

cent Volatiles by Volume:3.50%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS AND/OR HYDROFLUORIC ACID

Stability Condition to Avoid:ELEVATED TEMPERATURES. CONTACT WITH
OXIDIZING AGENTS

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL
REGULATIONS. AVOID DI
SCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information
to their
particular situation.