

TEXACO INC. -- 00375 UNLEADED PLUS GASOLINE -- 9130-00-148-7102

===== Product Identification =====

Product ID:00375 UNLEADED PLUS GASOLINE

MSDS Date:10/24/1990

FSC:9130

NIIN:00-148-7102

MSDS Number: BRFL

=== Responsible Party ===

Company Name:TEXACO INC.

Box:509

City:BEACON

State:NY

ZIP:12508-0509

Country:US

Info Phone Num:914-831-3400

Emergency Phone Num:914-831-3400

Preparer's Name:M.J. VONALL

MEN

CAGE:38431

=== Contractor Identification ===

Company Name:DIGITAL CONTROL SYSTEMS INC

Address:3160 GRAND MARAIS E

Box:City:WINDSOR, N8W 4W5

State:ON

Country:CN

Phone:NONE

CAGE:38431

Company Name:SCHULTE OIL CO

Address:1516 S ROCK ISLAND

Box:188

City:EL RENO

State:OK

ZIP:73036

Country:US

Phone:405-262-3120

CAGE:4R019

Company Name:TEXACO INC

Box:509

City:BEACON

State:NY

ZIP:12508-0509

Country:US

Phone:914-831-3400

CAGE:7B131

===== Composition/Information on Ingredients =====

Ingred Name: BENZENE (SARA III)  
CAS: 71-43-2  
RTECS #: CY1400000  
Fraction by Wt: 1-3.99%  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 1PPM/5STEL; 1910.1028  
ACGIH TLV: 10 PPM; A2; 9192  
EPA Rpt Qty: 10 LBS  
DOT Rpt Qty: 10 LBS

Ingred Name: TOLUENE (SARA III)  
CAS: 108-88-3  
RTECS #: XS5250000  
Fraction by Wt: 4-10.99%  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 200 PPM/150 STEL  
ACGIH TLV: 50 PPM; 9293  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS

Ingred Name: ETHYL BENZENE (SARA III)  
CAS: 100-41-4  
RTECS #: DA0700000  
Fracti  
on by Wt: 1-3.99%  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 100 PPM/125 STEL  
ACGIH TLV: 100 PPM/125 STEL 9192  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS

Ingred Name: XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS: 1330-20-7  
RTECS #: ZE2100000  
Fraction by Wt: 4-10.99%  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 100 PPM/150 STEL  
ACGIH TLV: 100 PPM/150 STEL; 9192  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS

Ingred Name: 1,2,4-TRIMETHYLBENZENE (SARA III)  
CAS: 95-63-6  
RTECS #: DC3325000  
Fraction by Wt: 1-3.99%  
Other REC L

imits:NONE SPECIFIED  
OSHA PEL:25 PPM  
ACGIH TLV:25 PPM; 9192

Ingred Name:METHYL TERT-BUTYL ETHER (SARA III)  
CAS:1634-04-4  
RTECS #:KN5250000  
Fraction by Wt: 0-15%  
Other REC Limits:NONE SPECIFIED  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:GASOLINE  
CAS:8006-61-9  
RTECS #:LX3300000  
Fraction by Wt: 95-99.9%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:300 PPM/500 STEL  
ACGIH TLV:300 PPM/500STEL;9293

Ingred Name:ALIPHATIC PETROLEUM SOLVENT  
CAS:8008-20-6  
RTECS #:OA5500000  
Fraction by Wt: .01-.09%  
Othe  
r REC Limits:NONE RECOMMENDED  
OSHA PEL:400 PPM PETR. DIST.  
ACGIH TLV:400 PPM RUBBER SOLV.

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) = 18.75 ML/KG  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:EYES:SLIGHT TO MODERATE  
IRRITATION.SKIN:MODERATELY IRRITATING.DERMALLY ABSORBED;LD50 DERMAL  
RABBIT>5MG/KG.INHAL:IRRITATES EYES,NOSE,THRO  
AT.CAUSES CNS EFFECTS.  
INGEST:MAY CAUSE LUNG DAMAGE IF VOMITTED AFTER  
SWALLOWING.CHRONIC-GASOLINE VAPORS MAY CAUSE LIVER AND KIDNEY  
DAMAGE.  
Explanation of Carcinogenicity:CONTAINS B [71-43-2] WHICH IS  
LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.  
Effects of Overexposure:SKIN:REDNESS,EDEMA,DRYING.INHAL:CNS  
EFFECTS-DIZZINESS,BLUIISH SKIN COLOR.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

=====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: REMOVE CONTAMINATED CLOTHING;WASH EXPOSED AREA WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING! CALL A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. G IVE ARTIFICIAL RESPIRATION OR OXYGEN IFNEEDED.CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:-40F,-40C

Lower Limits:1.4 %

Upper Limits:7.6 %

Extinguishing Media:DRY CHEMICAL, FOA M, CARBON DIOXIDE.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE ON FLAMES, BUT SHOULD BE USED TO COOL FIRE-EXPOSED CONTAINERS. USE A SELF-CONTAINED BRETAHING APPARATUS AND FULL PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND TRAVEL ALONG THE FLOOR;FLOWING GASOLINE GENERATES STATIC ELECTRICITY ...THIS PRESENTS A FLASHBACK HAZARD.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. VENTILATE AREA.

AVOID BREATHING VAPORS. USE SCBA FOR LARGE SPILLS OR IN CONFINED AREAS. CONTAIN SPILL IF POSSIBLE. REMOVE WITH NON-FLAMMABLE ADSORBANT(EG.DIATOMACEOUS EARTH );PLACE IN APPROPRIATE CONTAINER FOR DISPOSAL.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:TRANSPORT, HANDLE AND STORE IN ACCORDANCE WITH OSHA REGULATION 1910.106 AND APPLICABLE D.O.T. REGULATIONS.

Other Precautions:DANGER! EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED!

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SCBA OR SUPPLIED AIR RESPIRATORY PROTECTION REQUIRED FOR ENTRY INTO TANKS, VESSELS, OR OTHER CONFINED SPACES.

Ventilation:ADEQUATE TO MEET PERMISSIBLE CONCENTRATIONS.

Protective Gloves:NITRILE, TEFLON, VITON

Eye Protection:CHEMICAL-TYPE GOGGLES, FACE SHIELD

Other Protective Equipment:PROTECTIVE CLOTHING SUCH AS UNIFORMS, COVERA

LLS OR LAB COATS SHOULD BE WORN.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:>90F,>32C

Vapor Pres:465-775

Vapor Density:3 - 4.0

Spec Gravity:0.7 - .77

Evaporation Rate & Reference:N.D.

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID;LIGHT STRAW TO

LIGHT RED;GASOLINE ODOR

Percent Volatiles by Volume:100 %

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:HEAT, SPARKS, FLAME AND OTHER SOURCES OF IGNITION.

Hazardous Decomposition Products:TOXIC LEVELS OF CARBON MONOXIDE, CARBON DIOXIDE, IRRITATING ALDEHYDES AND KETONES.

===== Disposal Considerations =====

Waste Disposal Methods:CONSIDERED RCRA

HAZARDOUS WASTE;IT IS

TOXIC(BENZENE) AND IGNITABLE(FP=-40F).DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should see

k competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.