View NSN Online: https://aerobasegroup.com/nsn/6135-00-823-3034

Product ID:LIQUID CAUSTIC POTASH,45% (FOR GAP4005G BAT MSDS Date:05/13/1992 FSC:6135 NIIN:00-823-3034 Kit Part:Y **MSDS Number: BRFQF** === Responsible Party === Company Name: CHEMTECH INDUSTRIES INC MANUFACTURED PRODUCTS DIV Address:1655 DES PERES ROA D Box:31000 City:ST. LOUIS State:MO ZIP:63131-1821 Country:US Info Phone Num:314-966-9900 Emergency Phone Num:314-966-9900/800-424-9300(CHEMTREC) CAGE:56894 === Contractor Identification === Company Name: CHEMTECH INDUSTRIES INC MANUFACTURED PRODUCTS DIV Address:1655 DES PERES RD Box:31000 City:ST. LOUIS State:MO ZIP:63131-1821 Country:US Phone:314-966-9934 CAGE:56894 Company Name: EAGLE-PICHER INDUSTRIES, INC. Address: C AND PORTER STS Box:47 City: JOPLIN State:MO ZIP:64801 Country:US Phone:417-623

-8000 CAGE:81855

Ingred Name:POTASSIUM HYDROXIDE (SARA III) CAS:1310-58-3 RTECS #:TT2100000 Fraction by Wt: 45% Other REC Limits:NONE RECOMMENDED OSHA PEL:C, 2 MG/M3 ACGIH TLV:C 2 MG/M3; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

LD50 LC50 Mixture:LD50 ORAL RAT IS 273 MG/KG
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Health Hazards Acute and
Chronic:SUPPLIER STATES BATTERY IS AN ARTICLE, THEREFORE, NO EXPOSURE IS EXPECTED.
Explanation of Carcinogenicity:MANUFACTURER STATES THIS PRODUCT CONTAINS DETECTABLE AMOUNTS OF A CHEMICAL KNOWN TO CAUSE CANCER/BIRTH DEFECTS.
Effects of Overexposure:NO EXPOSURE EXPECTED. ARTICLE. IF BATTERY LEAKS, IT MAY CAUSE SEVERE IRRITATION AND BURNS TO EYES AND SKIN.
Medical Cond Aggravated by Exposure:NONE. NO EXPOSURE NORMALLY EXPECTED.

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. DO NOT NEUTRALIZE. GET IMMEDIATE MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND PLENTY OF WATER. GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESHAIR. GIVE CPR/OXYGEN IF NEEDED. SEE DOCTOR. INGESTION: GIVE LARGE AMOUNTS OF WATER OR MILK. DO NOT INDUCE VOMITING. SEE DOCTOR IMMEDIATELY.

=

Flash Point:NONE

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:HOT OR MOLTEN MATERIAL WILL REACT VIOLENTLY WITH WATER LIBERATING HEAT AND CAUSING SPATTERING.

Spill Rel

ease Procedures:NEUTRALIZE WITH 5% SOLUTION OF ACETIC ACID. ABSORB IN INERT MATERIAL AND PLACE IN APPROPIATE DISPOSAL CONTAINER AND COVER. FLUSH AREA WITH WATER FOLLOWED WITH SODIUM BICARBONATE. Neutralizing Agent:5% ACETIC ACID SOLUTION.

Handling and Storage Precautions: KEEP TERMINAL PLASTIC CAPS IN PLACE. STORE AWAY FROM ACIDS. AVOID PHYSICAL DAMAGE. Other Precautions: NONE.

======= Exposure Controls/Perso

nal Protection ==========

Respiratory Protection:NONE.

Ventilation:NONE.

Protective Gloves:NONE. RUBBER GLOVES IN CASE OF A SPILL.

Eye Protection:NONE. SAFETY GLASSES IN CASE OF A SPILL.

Other Protective Equipment:NONE.

Work Hygienic Practices:NORMAL PRACTICES AND RECOMMENDED PROCEDURES. Supplemental Safety and Health

KEY1:N1. THIS IS PART A OF A TWO PART MSDS. SUPPLIER DID NOT HAVE A SINGLE MSDS FOR THE BATTERY. SUPPLIER STATES BATTERY IS AN ARTICLE. PART B IS UNDER CAGE CODE 40057 . SAME NSN.

HCC:N1 Boiling Pt:B.P. Text:271F,133C Vapor Pres:17.5 Spec Gravity:1.45 pH: