

KBI/KOLD BAN INTERNATIONAL LTD -- ENGINE STARTING FLIUD - KBI 21 OZ. - DIESEL --  
8120-01-234-5336

=====  
Product Identification  
=====

Product ID:ENGINE STARTING FLIUD - KBI 21 OZ. - DIESEL  
MSDS Date:12/30/1992  
FSC:8120  
NIIN:01-234-5336  
MSDS Number: BRFVB  
=== Responsible Party ===  
Company Name:KBI/KOLD BAN INTERNATIONAL LTD  
Address:900 PINGREE RD  
City:LAKE IN THE HILLS  
State:IL  
ZIP:60102-9837  
Count  
ry:US  
Info Phone Num:708-658-8561 / FAX 708-685-9280  
Emergency Phone Num:708-658-8561 800-424-9300(CHEMTREC)  
CAGE:53203  
=== Contractor Identification ===  
Company Name:KBI/KOLD BAN INTERNATIONAL LTD  
Address:900 PINGREE RD  
Box:City:LAKE IN THE HILLS (FORMERLY ALGONQUIN)  
State:IL  
ZIP:60102-9670  
Country:US  
Phone:708-658-8561  
CAGE:53203

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CARBON DIOXIDE  
CAS:124-38-9  
RTECS #:FF6400000  
Fraction by Wt: 10-15%  
Other REC Limi  
ts:NONE RECOMMENDED  
OSHA PEL:5000 PPM  
ACGIH TLV:5000PPM/30000STEL;93

Ingred Name:ETHYL ETHER (SARA III)  
CAS:60-29-7  
RTECS #:KI5775000  
Fraction by Wt: 65-75%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400PPM/500STEL; 9293  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:N-HEPTANE  
CAS:142-82-5  
RTECS #:MI7700000  
Fraction by Wt: 10-20%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:500 PPM/500 STEL

LATES, HYDROTREATED LIGHT

NAPHTHENIC/PETROLATUM

CAS:64742-53-6

RTECS #:PY8036000

Fraction by Wt: 400 PPM OR

ACCUMULATION OF VAPORS ALONG THE FLOOR.

Protective Gloves:NOT NORMALLY NEEDED.NITRILE RECOMMENDED.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:CLOTHING TO AVOID CONTACT WITH SKIN.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET

CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.

Supplemental Safety and Heal

th

NONE

===== Physical/Chemical Properties =====

HCC:V3

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:94F ET2O

Vapor Density:2.5

Spec Gravity:0.7

Evaporation Rate & Reference:6.0

Solubility in Water:MODERATE 8%

Appearance and Odor:AEROSOL;PALE YELLOW TO CLEAR(FOR THE LIQUID);STRONG ETHEREAL ODOR.

Percent Volatiles by Volume:56.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS.

St

ability Condition to Avoid:DO NOT EXPOSE CONTENTS OF CAN TO LIGHT.KEEP CANS AWAY FROM HEAT,SPARKS,FLAMES.

Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF I A SEALED METAL CONTAINER IAW FEDERA,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Def

ense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.