

COURTAULDS AEROSPACE INC -- PR-2911 BLACK PART A -- 8030-01-357-3567

=====
Product Identification
=====

Product ID:PR-2911 BLACK PART A

MSDS Date:09/23/1991

FSC:8030

NIIN:01-357-3567

Kit Part:Y

MSDS Number: BRGPP

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE INC

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-549-7586

Emergency

Phone Num:818-549-7586

Preparer's Name:SR

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====
Composition/Information on Ingredients
=====

Ingred Name:DIETHYLTOLUENEDIAMINE (DETDA)

CAS:68479-98-1

Fraction by Wt: < 5%

Other REC Limits:NONE SPECIFIED

Ingred Name:PROPYLENE GLYCOL /METHYL ETHER ACETAT

E (VAPOR PRESSURE 2 MM
HG @ 20 C) (SOLVENT)
CAS:108-65-6
RTECS #:AI8925000
Fraction by Wt: 85%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: EXPECTED TO BE AN EYE IRRITANT.
SKIN: EXPECTED TO BE TOXIC BY DERMAL ABSORPTION. INHALATION: NOT
EXPECTE
D TO BE A ROUTE OF EXPOSRE DUE TO LOW VOLATILITY OF DETDA AT
ROOM TEMPERATURE. HOWEVER, HEATED OR SPRAYED MATERIAL MAY GIVE
OFFSIGNIFICANT AMOUNTS OF VAPOR. INGESTION: EXPECTED TO BE TOXIC.
Effects of Overexposure:A TWO YEAR FEEDING STUDY IN RATS SHOWED DETDA
CAUSED EFFECTS IN THE PANCREAS, LIVER, THYROID AND EYES. AN
INCREASE IN THE NUMBER OF TUMORS IN THE LIVER AND THYROID OF MALE
RATS WAS FOUND.

=====
First Aid Measures
=====

First
Aid:EYES: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES, CONSULT A
PHYSICIAN. SKIN: IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR
AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING & SHOES.
GET MEDIC AL ATTENTION. WASH CLOTHING BEFORE REUSE. INHALATION:
REMOVE TO FRESH AIR. INGESTION: GIVE MILK OR WATER TO DRINK.
INDUCE VOMITING. CONSULT A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:PMCC
Flash Point:124F,51C
Lower
Limits:1.5
Upper Limits:7-PM ACETATE
Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER FOG.
Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL
HEAT EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:HIGH TEMPERATURES MAY CAUSE PRESSURE
BUILDUP IN CLOSED CONTAINERS.

=====
Accidental Release Measures
=====

Spill Release Procedures:WEAR AIR-SUPPLIED RESPIRATOR FOR MAJOR
UNVENTILATED SPILL. COVER WITH ABSORBENT. SCOOP INTO CONTAINERS.

CLEAN-UP RESIDUE WITH 1,1,1-TRICHLOROETHANE.

===== Handling and Storage =====

Handling and Storage Precautions:SPRAY APPLYING,FULLY PROTECTED.OPEN AREAS ATLEAST 100 FT. SHOULD SEPERATE.INSIDE PROTECT. BY WALLS & VENTILATED. PROPERLY OPERAT. IN ACCRD. W/ACGIH.

Other Precautions:UNPROTECTED PERSONS MUST BE PREVENTED FROM CONTACTING UNCURED RESIDUE ON EQUIPMENT AND AREA SURFACES UNTIL THE PRODUCT HAS CURED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR SUPPLIED RESPIRATOR.

Ventilation:GENERAL VENITLATION MAINTAIN VAPORS BELOW TLV. IN CONFINED AREAS USE AN ORGANIC VAPOR CARTRIDGE RESPIRATOR.

Protective Gloves:NEOPRENE, NITRILE GLOVES

Eye Protection:CHEMICAL GOGGLES OR FULL-FACE SHIELD

Other Protective Equipment:IF CONTACT ON SKIN OR CLOTHING IS LIKELY, SARAN COATED DISPOSABLE COVERALLS MUST BE WORN.

Supplemental Safety and Health

DURING SPRAY APPLICATION, STRINGENT PRECAUTIONS MUST BE TAKEN TO ENSURE

THE SAFETY OF THE PERSONS INVOLVED WITH THE APPLICATION, OTHER PERSONS WORKING IN THE AREA, AND THE GENERAL PUBLIC. SEE SECTION IX.

===== Physical/Chemical Properties =====

HCC:F4

Vapor Density:4.61 *

Spec Gravity:1.0

Evaporation Rate & Reference:0.4 * (PM ACETATE)

Solubility in Water:MODERATE

Appearance and Odor:BLACK VISCOUS LIQUID

Percent Volatiles by Volume:90

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:OXIDES OF CARBON AND NITORGEN

===== Disposal Considerations =====

Waste Disposal Methods:EPA WASTE NO. D-001. DISPOSE OF SPILLAGE IN COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The Uni

ted States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.