View NSN Online: https://aerobasegroup.com/nsn/8030-01-364-7360

Product ID: EPOXY POLYAMIDE ACTIVATOR 910X624 MSDS Date:12/18/1991 FSC:8030 NIIN:01-364-7360 Kit Part:Y MSDS Number: BRGPZ === Responsible Party === Company Name: COURTAULDS AEROSPACE Address:11601 UNITED ST City:MOJAVE State:CA ZIP:93501 Country:US Info Phone Num:805-824-4532 Emergency Phone Num:805-824-4532 CAGE:83574 === Contractor Identification === Company Name: DESOTO INC PACIFIC PLANT IS COURTLANDTS AEROSPACE Address:1608 4TH ST Box:City:BERKELEY State:CA ZIP:94710 Country:US Phone:800-228-5635 /800-424-9300 CHEMTREC CAGE:85570 Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574

======= Composition/Information on Ingredients =========

==

Ingred Name: TOLUENE (SARA III) (VAPOR PRESSURE 22 MM HG) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 15% Other REC Limits:NONE SPECIFIED OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM: 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: ISOPROPYL ALCOHOL (SARA III) (VAPOR PRESSURE 33 MM HG) CAS:67-63-0 RTECS #:NT8050000 Fraction by Wt: 55% Other REC Limits:NONE SPECIFIED OSHA PEL:400 PPM/STEL 500 PPM ACGIH TLV:400 PPM/STEL 500 PPM Ingred Name:XYLENE (SARA III) (VAPOR PRESSURE 10 MM HG) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 10% Other REC Limits:NONE SPECIFIED OSHA PEL:100 PPM/STEL 150 PPM ACGIH TLV:100 PPM/STEL 150 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: ETHYL BENZENE (SARA III) (VAPOR PRESSURE 7.1 MM HG) CAS:100-41-4 RTECS #:DA0700000 Fraction by Wt: 120F.STORE FLAMM LIQ IN ACCORD W/NFPA CODES & GOVERNMNTL REGS.DONT SMOKE WHERE STORED/USED. Other Precautions: GROUND/BOND WHEN TRANSFERRING. AVOID FREE FALL. DONT APPLY TO HOT SURFCS.DONT IN **GEST/CONC & INHAL.EMPTY DRUMS CONTAIN** EXPLOS VAPOR.DONT CUT, PUNCTURE, WELD ON/NEAR DRUM. VAPOR HEAVIER THAN AIR, COLLECT IN L OW AREAS. DONT ENTER W/O AIR MONITORING.

Respiratory Protection: ABOVE TLV/SPRAY MIST IS PRESENT, USE NIOSH/MSHA RESPIRATORY PROTECTION APPROPRIATE FOR INDICATED COMPONENTS. IN CONFINED AREAS USE NIOSH APPROVED AIR SUPPLIED RESPIRATOR. FOLLOW RESPIRATOR MFR'S DIREC TION & OSHA REGS (29 CF R 1910.134).
Ventilation: IF EMPLOYEES PRESENT, PROVIDE GENERAL DILUTION/LOCAL EXHAUST TO KEEP BELOW TLV/PEL. NO EMPLOYEES, KEEP BELOW 25% LEL.
Protective Gloves: WEAR CHEMICALLY RESISTANT GLOVES
Eye Protection: SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES
Other Protective Equipment: AVOID SKIN CONTACT BY USE OF OTHER PROTECTIVE CLOTHING. SAFETY SHOWER, EYE BATH & WASHING FACILITIES SHOULD BE AVAILABLE
Work Hygienic Practices: PREVENT PROLONGED CONTACT WITH CONTAMINATED CLOTHING. WASH CON
TAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health

HCC:F2 Boiling Pt:B.P. Text:180 TO 277F Vapor Density:> AIR Spec Gravity:0.84 Evaporation Rate & amp; Reference:SLOWER THAN N-BUTYL AC Appearance and Odor:AMBER LIQUID, SOLVENT ODOR Percent Volatiles by Volume:84.5

Stability Indicator/Materials to Avoid:YES NONE RECOGNIZED Stability Condition to Avoid:NONE RECOGNIZED Hazardous Decomposition Products:PRODUCTS OF COMBUSTION ARE HAZARDOUS INCLUDING CARBON MONOXIDE AND CARBON DIOXIDE.

Waste Disposal Methods:PACKAGE, STORE, TRANSPORT, MANAGE IN ACCORD W/LOCAL, STATE, & FEDERAL REGULATIONS. USE NO DISPOSAL METHOD THAT WOULD POSE ENVIRONMENTAL OR HUMAN HEALTH THREAT INCLUDING ANY WHICH WOULD CONTAMINATE GRO UND OR SURFACE WATER.

Disclaimer (provided with t

his information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.