

HEXAGON CHEMICAL COMPANY -- HEXAFLOC M-20 -- 6850-01-167-5318

=====  
Product Identification  
=====

Product ID:HEXAFLOC M-20

MSDS Date:12/18/1990

FSC:6850

NIIN:01-167-5318

MSDS Number: BRGQT

=== Responsible Party ===

Company Name:HEXAGON CHEMICAL COMPANY

Box:23163

City:LOUISVILLE

State:KY

ZIP:40223

Country:US

Info Phone Num:502-244-1172

Emergency Phone Num:502-244-1172,502-228-4001(AFTER HR)

CAGE:0A

643

=== Contractor Identification ===

Company Name:HEXAGON CHEMICAL COMPANY

Box:City:LOUISVILLE

State:KY

ZIP:40223

Country:US

Phone:502-244-1172

CAGE:0A643

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NONHAZARDOUS INGREDIENT.APPROVED BY EPA FOR CLARIFICATION  
OF DRINKING WATER UP TO 50 MG/L.

Other REC Limits:NOT KNOWN

OSHA PEL:NOT KNOWN

ACGIH TLV:NOT KNOWN

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:NOT KNOWN

R

outes of Entry: Inhalation:NO Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:CONTACT WITH EYES WILL INJURE EYE  
TISSUE IF NOT WASHED OFF THOROUGHLY AND PROMPTLY WITH WATER.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:EYES:IRRITATING. SKIN:IRRITATING.LOW ORDER OF  
TOXICITY. INGESTION:LOW ORDER OF TOXICITY. INHALATION:NO HAZARD IN  
NORMAL INDUSTRIAL USE.VERY LOW VAPOR PRESSURE.  
Medical Cond Aggravated by Exposur  
e:NOT KNOWN

=====  
First Aid Measures  
=====

First Aid:EYES:IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR AT  
LEAST 15 MIN.GET PROMPT MED ATTN. SKIN:FLUSH WITH LARGE AMOUNTS OF  
WATER,USE SOAP IF AVAILABLE.REMOVE GROSSLY CONTAMINATED  
CLOTHING,INCLUDING SHOES,LAUNDRER BEFORE REUSE.IF IRRITATION  
PERSISTS,SEEK MED ATTN. INGESTION:IF SWALLOWED,DO NOT INDUCE  
VOMITING.KEEP AT REST.GET PROMPT MED ATTN. INHALATION:FIRST AID IS  
NORMALLY NOT R  
EQUIRED.

=====  
Fire Fighting Measures  
=====

Flash Point Method:SCC  
Flash Point:210F,99C  
Extinguishing Media:USE ALCOHOL TYPE FOAM,DRY CHEMICAL OR WATER SPRAY  
TO EXTINGUISH FIRE.  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS (SCBA)  
AND FULL TURNOUT GEAR .USE WATER SPRAY TO COOL FIRE EXPOSED  
SURFACES & TO PROT PERS.ISOLATE "FUEL" SUPPLY.  
Unusual Fire/Explosion Hazard:NO UNUSUAL OR TOXIC PRODUCTS.LIQUID CAN  
BURN UPON HEATING TO  
TEMP AT OR ABOVE THE FLASHPOINT.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:LAND SPILL:USE DRY ABSORBENT MATL.DIKE &  
ABSORB SPILL WITH INERT MATL,SUCH AS SAND,EARTH,OR VERMICULITE &  
TRANSFER TO SUITABLE CONTR FOR DISP.PVNT FROM ENTERING  
SEWERS,WATERCOURSES,OR LOW AREAS.RECOVE R BY PUMPING OR WITH  
SUITABLE ABSORB.(SEE SUPP)  
Neutralizing Agent:NOT KNOWN

=====  
Handling and Storage  
=====

Handling

and Storage Precautions:STORAGE/LOADING/UNLOADING  
TEMP:AMBIENT.STORAGE PRESSURE:ATMOSPHERIC.  
Other Precautions:"EMPTY" CONTR RETAIN PRODUCT RESIDUES.DO NOT  
PRESS,CUT,WELD,BRAZE,SOLDER,DRILL,GRIND,OR EXPOSE TO SOURCES OF  
IGNITION,THEY MAY EXPLODE.EMPTY DRUMS SHOULD BE COMPLETELY  
DRAINED,PROPERLY BUNGED & RETURN ED TO DRUM RECONDITIONER/DISPOSED  
OF.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CONTACT LOCAL SAFETY/INDUSTRIAL HYGI  
ENE OFFICE  
TO DETERMINE IF RESPIRATORY PROTECTION IS REQUIRED .  
Ventilation:NO SERIOUS VAPOR EXPOSURE PROBLEMS UNDER NORMAL CONDITIONS.  
Protective Gloves:NOT KNOWN  
Eye Protection:CHEMICAL SAFETY GOGGLES .  
Other Protective Equipment:WHERE CONTACT MAY OCCUR,WEAR LONG SLEEVES.  
Work Hygienic Practices:NOT KNOWN  
Supplemental Safety and Health  
DENSITY:8.7 LBS/GAL @ 60F,16C.MP:25-30F,77-86C.VISCOSITY AT  
LOADING/UNLOADING TEMP:10-100 CPS AT 77F,25C.SPILL PROC:WATER  
SPILL:PRVT ADDNL DISCHARGE  
OF MATL,IF POSSIBLE TO DO SO WITHOUT  
HAZARD.ADVISE AUTHORITIES.CONSULT HEALTH INFO & PROT REGARDING  
POSSIBLE HAZARDS.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C  
Melt/Freeze Pt:M.P/F.P Text:SEE SUPP  
Decomp Temp:Decomp Text:NOT KNOWN  
Vapor Pres:SEE SUPP  
Vapor Density:>1 (AIR=1)  
Spec Gravity:1.02-1.03  
Viscosity:10-150CP@77F  
Evaporation Rate & Reference:1.5 (BUTYL ACETATE=1)  
Solubility in Water:SOLUBLE  
Appearance and Odor:LIGHT  
AMBER VISCOUS FLUID WITH MILD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid:NONE  
Hazardous Decomposition Products:NONE  
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISP MUST BE IAW FED,STATE,& LOC REGS.COORDINATE  
W/ SUPPORTING INSTALLATION/MACOM ENVIRON OFFICE PRIOR TO

DISP .

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.