View NSN Online: https://aerobasegroup.com/nsn/9140-00-247-4363

NAVAJO REFINING COMPANY -- NO. 2 FUEL OIL -- 9140-00-247-4363

=========== Product Identification ==============

Product ID:NO. 2 FUEL OIL MSDS Date:03/09/1992

FSC:9140

NIIN:00-247-4363

MSDS Number: BRGTD === Responsible Party ===

Company Name: NAVAJO REFINING COMPANY

Box:159

City:ARTESIA

State:NM

ZIP:88211-0159 Country:US

Info Phone Num:505-748-3311

Emergency Phone Num:505-748-3311(CHEMTREC 800-424-9300)

CAGE:4K

236

=== Contractor Identification ===

Company Name: BIG BEAR OIL CO INC

Address:421 FREDRICK ST

Box:2036

City:EL PASO

State:TX ZIP:79950

Country:US

Phone:915-775-1945

CAGE:0BMM6

Company Name: NAVAJO REFINING COMPANY

Box:159

City:ARTESIA

State:NM

ZIP:88211-0159

Country:US

Phone:505-748-3311

CAGE:4K236

======= Composition/Information on Ingredients ========

Ingred Name:PETROLEUM MID-DISTILLATE

CAS:68476-34-6 Fraction by Wt: 490F Lower Limits:0.7 Upper Limits:5

Extinguishing Media:DRY

CHEMICAL, FOAM, CARBON DIOXIDE, OR HALON. Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. USE WATER FOG TO COOL FIRE EXPOSED CONTAINERS AND TO DIPERSE VAPORS. Unusual Fire/Explosion Hazard: VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A GREAT DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. ======== Accidental Release Measures ============ Spill Release Procedures: CONTAIN SPILL. ABSORB ON SUITABLE MATERIAL, SCOOP UP AND PLACE IN CONTAINER FOR DISPOSAL. VENTILATE AREA. AVOID BREATHING VAPORS. AVOID ALL PERSONAL CONTACT. USE SELF-CONTAINED BREATHING APPARATUS IN CONFINED AREA. Neutralizing Agent:NONE ============ Handling and Storage =========================== Handling and Storage Precautions: STORE AWAY FROM HEAT AND IGNITION SOURCES. HANDLE AND STORE IN ACCORDANCE WITH OSHA REG. 1910.106. Other Precautions: AVOID BREATHING VAPORS. DO NOT CUT, WELD OR DRILL "EMPTY" CONTAINERS AS THEY MAY CONTAIN RESIDUE WHICH CAN IGNITE OR EXPLODE. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: USE SELF-CONTAINED BREATHING APPARATUS IF PEL/TLV EXCEEDED AS IN A LARGE SPILL OR CONFINED AREA. Ventilation: USE ADEQUATE MECHANICAL VENTILATION. Protective Gloves:NITRIL, PVA Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices: USE GOOD PERSONAL HYGENE. LAUNDER CONTAMI **NATED** CLOTHING BEFORE REUSE. Supplemental Safety and Health ======== Physical/Chemical Properties =========== HCC:F4 Boiling Pt:B.P. Text:>315F,>157C Vapor Pres:25 MM HG Spec Gravity:>0.7 (WATER=1) Solubility in Water: NEGLIGIBLE Appearance and Odor: CLEAR TO YELLOW LIQUID. OILY, PETROLEUM ODOR ======== Stability and Reactivity Data ===========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HEAT, FLAME AND

===== Disposal Considerations ====	=======================================
OTHER SOURCES OF IGNITION. CONTACT WITH STRONG OXIDIZERS. Hazardous Decomposition Products:OXIDES OF CARBON	N AND SULFUR DIOXIDE

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner what soever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.