

PRATTVILLE BUILDERS INC -- PRIMER, EPOXY CTG CORINHIB, LEAD & CR FREE --
8010-01-187-9820

=====
Product Identification
=====

Product ID:PRIMER, EPOXY CTG CORINHIB, LEAD & CR FREE

MSDS Date:05/26/1992

FSC:8010

NIIN:01-187-9820

Kit Part:Y

MSDS Number: BRHBS

=== Responsible Party ===

Company Name:PRATTVILLE BUILDERS INC

Address:474 E MAIN ST

Box:2153

City:PRATTVILLE

State:AL

ZIP:36067

Country:US

Inf

o Phone Num:205-365-2396/2145/312-455-2662NIGHT

Emergency Phone Num:205-365-2396/2145/312-455-2662NIGHT

Preparer's Name:W. A. ELLISON

CAGE:0EAH4

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

Company Name:PRATTVILLE BUILDERS INC

Address:474 E MAIN ST

Box:2153

City:PRATTVILLE

State:AL

ZIP:36067

Country:US

Phone:205-365-2396/2145/312-455-2662NIGHT

CAGE:0EAH4

=====
Composition/In

formation on Ingredients =====

Ingred Name: DIGLYCIDYL ETHER OF BISPHENOL-A (RESIN)
CAS: 25068-38-6
RTECS #: KC2100000
Fraction by Wt: 25%
Other REC Limits: NONE SPECIFIED

Ingred Name: N-BUTYL ALCOHOL (SARA III) (SOLVENT) (LFL 1.4; UFL 11.2)
(VAPOR PRESSURE 6 MM HG @ 20C) (SKIN)
CAS: 71-36-3
RTECS #: EO1400000
Fraction by Wt: 10%
Other REC Limits: NONE SPECIFIED
OSHA PEL: 100 PPM
ACGIH TLV: S, C 50 PPM; 9293
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Ingred Name: TALC (PIGMENT)
CAS: 14807-96-6
RTECS #: WW2710000
Fraction by Wt: 5%
Other REC Limits: NONE SPECIFIED
OSHA PEL: 2 MG/M3 /20 MPPCF
ACGIH TLV: 2 MG/M3 /15 MPPCF

Ingred Name: SILICA, CRYSTALLINE
CAS: 14808-60-7
RTECS #: VV7330000
Fraction by Wt: AIR
Spec Gravity: 1.5
pH: 4-7
Evaporation Rate & Reference: SLOWER THAN DIETHYL ETHER
Solubility in Water: SLIGHT
Appearance and Odor: LIQUID, SOLVENT ODOR
Percent Volatiles by Volume: 44

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Av

oid:YES

ALKALIS & AMINES. STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>115F) AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE, AND CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORD W/FED, STATE & LOCAL LAWS/REGS. INCINERATE IN EPA PERMITTED FACILITY. DONT INCINERAT

E

CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MAT'LS. CONTAM ABSORBENT MAY BE DISPOSED IN HAZARD WASTE LANDFILL. EPAHZD #D001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing

this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.