View NSN Online: https://aerobasegroup.com/nsn/6140-01-204-5432

DELCO REMY DIV OF GENERAL MOTORS CORP -- ALL MODELS OF DELCO BATTERIES 6140-01-204-5432

============= Product Identification ==================

Product ID:ALL MODELS OF DELCO BATTERIES

MSDS Date:02/22/1993

FSC:6140

NIIN:01-204-5432

MSDS Number: BRHBX === Responsible Party ===

Company Name: DELCO REMY DIV OF GENERAL MOTORS CORP

Address:2401 COLUMBUS AVE

Box:2439

City: ANDERSON

State:IN

ZIP:46018-9986

Country:US

Info

Phone Num:317-646-7800

Emergency Phone Num:317-646-7800 Preparer's Name:RICHARD GALLAGHER

CAGE:LO728

=== Contractor Identification ===

Company Name: DELCO REMY DIV OF GENERAL MOTORS CORP

Address:2401 COLUMBUS AVE

Box:2439

City: ANDERSON

State:IN ZIP:46018 Country:US

Phone:317-646-3080

CAGE:LO728

Company Name: GENERAL MOTORS CORP, DELCO REMY DIV

Address:2401 COLUMBUS AVE

Box:640

City: ANDERSON

State:IN ZIP:48011 Country:US

Phone:EMER:313/556-1597 OR 6200

CAGE:16764

====== Composition/Informa

tion on Ingredients ========
Ingred Name:SULFURIC ACID (SARA III) CAS:7664-93-9 RTECS #:WS5600000 Fraction by Wt: 37% Other REC Limits:NONE SPECIFIED OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: BALANCE Other REC Limits:NONE SPECIFIED
Ingred Name:LEAD (SARA III) CAS:7439-92-1 RTECS #:OF7525000 Fraction by Wt: >90% Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV :0.15 MG/M3;DUST 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB
======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:CONTACT WITH SULFURIC ACID RESULTS IN RAPID DESTRUCTION OF BODY TISSUE (BURNS).  Explanation of Carcinogenicity:LEAD IS LISTED AS A POSSIBLE CARCINOGEN IN IARC  Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.  Me dical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================
First Aid:INHALATION-REMOVE TO FRESH AIR. GET MEDICAL ATTENTION. EYE OR SKIN CONTACT-FLUSH WITH LARGE VOLUMES OF WATER. GET MEDICAL ATTENTION. INGESTION-DO NOT INDUCE VOMITING. GIVE MILK MIXED WITH EGG WHITES I F CONSCIOUS. GET MEDICAL ATTENTION.
======================================
Flash Point:NONE Extinguishing Me

dia: NONE SPECIFIED BY MANUFACTURER.

Fire Fighting Procedures:RECOMMENDED SELF CONTAINED BREATHING APPARATUS IF BATTERIES ARE INVOLVED IN FIRE DUE TO TOXIC FUMES FROM BURNING PLASTIC & ACID FUMES & VAPORS.

Unusual Fire/Explosion Hazard:WHILE BATTERIES ARE BEING CHARGED, HYDROGEN GAS IS GENERATED. AVOID OPEN FLAMES, SPARKS OR LIGHTED MATCHES. ACID & POWERFUL OXIDIZERS, CAN IGNITE COMBUSTIBLES.

======== Accidental Release Measures ===========

Spill Release Proce

dures:LIME OR SODA MAY BE USED TO NEUTRALIZE AND/ OR FLUSH WITH LARGE VOLUMES OF WATER. CONTAIN SPILL. Neutralizing Agent:LIME OR SODA-TYPE COMPOUNDS

Handling and Storage Precautions:AVOID SKIN CONTACT. WHEN CHARGING BATTERIES, AVOID PLACING IN AREAS WHERE HYDROGEN CAN BUILD UP. DO NOT PLACE NEAR OPEN FLAME, SPARKS OR LIGHT MATCHES Other Precautions:PAY ATTENTION TO LABELS ON BATTERY AND CARTONS CONTAINING BATT ERIES.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: USE NIOSH APPROVED RESPIRATORY PROTECTION IF 1 MG/M3 TWA IS EXCEEDED (ACID).

Ventilation:LOCAL EXHAUST AT CHARGING STATION.

Protective Gloves: RUBBER

Eye Protection: SPLASH-PROOF SAFETY GOGGLES

Other Protective Equipment: USE RUBBER BOOTS AND ACID PROOF CLOTHING FOR MAJOR SPILLS.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

NONE

\_\_\_\_\_

Physical/Chemical Properties =========

HCC:C1

Boiling Pt:=111.7C, 233.F Vapor Pres:2.730 MMHG Spec Gravity:AVERAGE 1.280

pH: