View NSN Online: https://aerobasegroup.com/nsn/9140-00-247-4366

FARMLAND INDUSTRIES, INC., BULK PERTOLEUM PROD DIV. -- #1 DISTILLATE FUEL, Y GRADE -- 9140-00-247-4366

Product ID:#1 DISTILLATE FUEL, Y GRADE MSDS Date:02/22/1991 FSC:9140 NIIN:00-247-4366 MSDS Number: BRJHT === Responsible Party === Company Name: FARMLAND INDUSTRIES, INC., BULK PERTOLEUM PROD DIV. Box:7305 City:KANSAS CITY State:MO ZIP:64116-0005 Country:US Info Pho ne Num:316-251-4000 Emergency Phone Num:316-251-4000, CHEMTREC 800-424-9300 CAGE:6G072 === Contractor Identification === Company Name: FARMLAND INDUSTRIES, INC., BULK PERTOLEUM PROD DIV. Box:7305 **City:KANSAS CITY** State:MO ZIP:64116-0005 Country:US Phone:316-251-4000, CHEMTREC 800-424-9300 CAGE:6G072 Ingred Name: ALIPHATIC PETROLEUM SOLVENT CAS:8008-20-6

RTECS #:OA5500000 Fraction by Wt: >98% Other REC Limits:NONE SPECIFIED

Ingre

d Name:1,2,4-TRIMETHYLBENZENE (SARA III) CAS:95-63-6 RTECS #:DC3325000 Fraction by Wt: 1.1% Other REC Limits:NONE RECOMMENDED OSHA PEL:25 PPM ACGIH TLV:25 PPM; 9293

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: PRODUCT IS MILDLY IRRITATING TO BODY TISSUES. BREATHING VAPORS MAY PRODUCE CENTRAL NERVOUS SYSTEM DEPRESSION, AN D PROLONGED AND/OR REPEATED SKIN CONTACT MAY CAUSE DERMATITIS. TARGET ORGAN:CNS, BLOOD. Effects of Overexposure: EYE: IRRITATION. SKIN: MILD IRRITATION. INHALATION: RESPIRATORY IRRITATION, NAUSEA, DIZZINESS, HEADACHE. INGESTION: G/I IRRITATION, NAUSEA, VOMITING. Medical Cond Aggravated by Exposure: SKIN AND RESPIRATORY DISORDERS. First Aid:SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. GET MEDICAL ATTE NTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION. EYE: I MMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: GET IMMEDIATE

MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS.

Flash Point Method:TCC Flash Point:120F,49C Lower Limits:0.7 Upper Limits:5.0 Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:WATER SPRAY MAY CAUSE FROTHING. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG GROUND, AND MAY FLASH BACK FROM A DISTANT IGNITION SOURCE. CONTAINER MAY BURST.

======== Accidental Release Measures

===================

Spill Release Procedures: ELIMINATE SOURCES OF IGNITION. MINOR: ABSORB MATERIAL WITH CLAY, VERMICULITE, OR SIMILAR ABSORBENT MATERIAL. PLACE IN DISPOSAL CONTAINERS. MAJOR: DIKE & CONTAIN SPILL. SHUT OFF LEAKS. REMOVE LIQUID BY VACUUM OR ABSORBENT.

Handling and Storage Precautions:STORE IN AREA AWAY FROM HEAT, SPARKS AND OTHER SOURCES OF IGNITION. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

DETACHED STORAGE IS PREFERABLE.

Other Precautions: EMPTY CONTAINERS RETAIN RESIDUE. DO NOT PRESSURIZE, CUT, WELD OR EXPOSE TO HEAT, FLAME, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY.

Respiratory Protection: RESPIRATOR WILL NOT NORMALLY BE NECESSARY. USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR OR RESPIRATOR FOR ORGANIC VAPOR IF EXPOSURE IS ABOVE THE TLV/PEL. SEE 29 CFR 1910.134

FOR REGULATIONS PERTAIN ING TO RESPIRATOR USE. Ventilation:LOCAL AND MECHANICAL EXHAUST RECOMMENDED.

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY GLASSES OR SPLASH GOGGLES

Other Protective Equipment: EYE WASH STATION & SAFETY SHOWER. IMPERVIOUS CLOTHING TO PREVENT PROLONGED OR REPEATED SKIN CONTACT.

Work Hygienic Practices:USE GOOD CHEMICAL HYGIENE PRACTICES. AVOID PROLONGED/REPEATED CONTACT. DO NOT EAT, DRINK OR SMOKE IN WORK AREA.

Supplemental Safety and Health NO

HCC:F4 Boiling Pt:B.P. Text:340F,171C Vapor Pres: