

AGE REFINING INC -- DIESEL FUEL OIL -- 9140-00-286-5296

=====
Product Identification
=====

Product ID:DIESEL FUEL OIL
MSDS Date:04/13/1992
FSC:9140
NIIN:00-286-5296
MSDS Number: BRKDF
=== Responsible Party ===
Company Name:AGE REFINING INC
Address:7811 S PRESA
City:SAN ANTONIO
State:TX
ZIP:78223
Country:US
Info Phone Num:512-532-5300
Emergency Phone Num:512-532-5300
CAGE:LO175

=== Contractor Iden
tification ===
Company Name:AGE REFINING AND MARKETING
Address:7811 S PRESA
Box:City:SAN ANTONIO
State:TX
ZIP:78223-3531
Country:US
Phone:512-532-5300
CAGE:0T116
Company Name:AGE REFINING INC
Address:7811 S PRESA
Box:City:SAN ANTONIO
State:TX
ZIP:78223
Country:US
Phone:512-532-5300
CAGE:LO175

=====
Composition/Information on Ingredients
=====

Ingred Name:DISTILLATES,STREIGHT RUN MIDDLE
CAS:64741-44-2
RTECS #:LX3296000
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED

==

=====
Hazards Identification
=====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS = 5-15 G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CENTRAL NERVOUS SYSTEM

DEPRESSION WITH EXTREME EXPOSURE; EFFECTS MAY INCLUDE ANESTHESIA, COMA, RESPIRATORY ARREST, AND IRREGULAR HEART RATE. OXYGEN DEPRIVATION IS POSSIBLE IF WORKING IN A CONFINED AREA. CHRONIC: NO K

NOWN MAJOR CUMULATIVE OR LATENT EFFECTS HAVE BEEN REPORTED.

Explanation of Carcinogenicity:NOT CARCINOGENIC.

Effects of Overexposure:INHALATION-IRRITATION OF THE UPPER RESPIRATORY TRACT, DEPRESSION, DIZZINESS, HEADACHE, UNCOORDINATION, ANESTHESIA, COMA & RESPIRATORY ARREST. SKIN-DEFATTING, IRRITATION & BURNING SENSATION & SWELLING OF LIDS. EYE-SEVERE BURNING SENSATION. INGESTION-IRRITATION OF THROAT, ESOPHAGUS & STOMACH, VOMITING.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYES-FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MIN. SEEK MEDICAL ATTENTION. SKIN-WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHES & FOOTWARE. SEEK MEDICAL ATTENTION. INHALATION-REMOVE TO FRESH AIR; RESTORE BREATHING IF NEEDED; ADMINISTER OXYGEN; SEEK MEDICAL HELP. INGESTION-DO NOT INDUCE VOMITING. IF VOMITING OCCURS, KEEP AIRWAY CLEAR. SEEK MEDICAL ATTENTION IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:PMCC

Flash Point:100F,38C

Lower Limits:1

Upper Limits:5

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE. WATER MAY BE INEFFECTIVE. USE WATER TO COOL & PROTECT MATERIAL & MEN, FLUSH SPILL.

Fire Fighting Procedures:MINIMIZE BREATHING GASES, VAPOR, FUMES OR DECOMPOSITION PRODUCTS. USE SUPPLIED AIR BREATHING APPARATUS IN ENCLOSED OR CONFINED AREAS OR AS OTHERWISE NEEDED.

Unusual

Fire/Explosion Hazard:NA

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. CONFINE AREA TO CLEANUP PERSONNEL. VENTILATE CONFINED AREAS. USE EXPLOSION PROOF EQUIPMENT. ABSORB &/OR CONFINE LIQUID WITH SAND, EARTH OR OTHER SUITABLE MATERIAL. KEEP PRODUCT OUT OF SEWERS OR WATERCOURSES.

===== Handling and Storage =====

Handling and Storage Precautions:PROTECT AGAINST PHYSICAL DAMAGE.

OUTSIDE OR DETACHED STORAGE PREFERRED. STORE IN COOL, WELL-VENTILATED AREA AWAY FROM IGNITION SOURCES & OXIDIZERS.

Other Precautions:TO PREVENT FIRE OR EXPLOSION RISK FROM STATIC ACCUMULATION & DISCHARGE, GROUND PRODUCT TRANSFER SYSTEM IN ACCORDANCE WITH THE NATIONAL FIRE PROTECTION ASSOCIATION FOR PETROLEUM PRODUCTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATORY PROTECTION NOT REQUIRED UNDER NORMAL USE. U

SE NIOSH.MSHA APPROVED ORGANIC VAPOR RESPIRATOR FOLLOWING MANUFACTURERS RECOMMENDATIONS WHERE SPRAY, MIST OR VAPORS MAY CAUSE SUGGESTED TLV TO BE EXCEEDED.

Ventilation:WORK IN VENTILATED AREAS. SPECIAL VENTILATION IS NOT REQUIRED UNDER NORMAL USE.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:FACE SHIELD & GOGGLES, CHEMICAL GOGGLES.

Other Protective Equipment:STANDARD WORK CLOTHING. CLOTHES OR FOOTWARE THAT CANNOT BE DECONTAMINATED SHOULD BE DISCARDED.

Work Hygienic Practi

ces:SHOWER AND EYE WASH FACILITIES SHOULD BE ACCESSIBLE.

Supplemental Safety and Health

NOTE TO PHYSICIAN-GASTRIC LAVAGE ONLY IF LARGE QUANTITIES HAVE BEEN INGESTED. GUARD AGAINST ASPIRATION INTO LUNGS WHICH MAY RESULT IN CHEMICAL PNEUMONITIS. IRREGULAR HEART BEAT MAY OCCUR; USE OF ADRENALIN IS NOT ADVISABLE. TREAT SYMPTOMATICALLY.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:360-572F

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Tem

p:Decomp Text:NA
Vapor Pres:0.1
Vapor Density:NA
Spec Gravity:0.81-0.86
pH:NA
Evaporation Rate & Reference:NA
Solubility in Water:TRACE
Appearance and Odor:CLEAR TO YELLOW, TYPICAL HYDROCARBON ODOR.
Percent Volatiles by Volume:100
Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGEN, SODIUM
HYPOCHLORITE OR CALCIUM HYPOCHLORITE.
Stability Condition to
Avoid:UNDER NORMAL CONDITIONS, THE MATERIAL IS
STABLE.
Hazardous Decomposition Products:FUMES, SMOKE, CARBON MONOXIDE,
ALDEHYDES AND OTHER DECOMPOSITION PRODUCTS.
Conditions to Avoid Polymerization:MATERIAL IS NOT KNOWN TO POLYMERIZE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL OF WASTE MATERIAL ARE REGULATED AND
ACTION TO HANDLE OR DISPOSE OF SPILLED OR RELEASED MATERIALS MUST
MEET ALL APPLICABLE LOCAL, STATE AND FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
part
icular situation.