View NSN Online: https://aerobasegroup.com/nsn/7930-00-298-1947

INDUSTRIAL FLOOR FINISHES -- AA1550 WAX, PASTE -- 7930-00-298-1947

Product ID:AA1550 WAX, PASTE MSDS Date:04/15/1993 FSC:7930 NIIN:00-298-1947 **MSDS Number: BRKFF** === Responsible Party === Company Name: INDUSTRIAL FLOOR FINISHES Address:605 SPRINGS ROAD City:BEDFORD State:MA ZIP:01730 Country:US Info Phone Num:508-667-5161 Emergency Phone Num:800-255-3924 OR POISO N CENTER Preparer's Name: TPITROLFFY CAGE:0J4J4 === Contractor Identification === Company Name: PERMA, INCORPORATED Address:605 SPRINGS ROAD Box:City:BEDFORD State:MA ZIP:01730 Country:US Phone:978-667-5161 CAGE:0J4J4 Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 72-80% Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9293

======== Hazards Identification =======

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE; EYE IRRITATION, DRYING OF SKIN, DIZZINESS, NAUSEA. VAPORS MAY BE NARCOTIC. CHRONIC; RESPIRATORY TRACT IRRITATION, COULD DAMAGE LIVER AND KIDNEY. Effects of Overexposure: IRRITATION AND REDNESS OF SKIN, DIZZY FEELING, PALE AND NAUSEOUS. Medical Cond Aggravated by Exposure: KIDNEY, LIVER AND LUNG PROBLEMS. _____ First Aid: EYE & SKIN CONTACT: FLUSH WITH PLENTY OF WATER. INHALATION: REMOVE TO FRESH AIR, BEGIN ARTIFICIAL RESPIRATION IF NEEDED. INGESTION: DO NOT INDUCE VOMITING, GET IMMEDIATE MEDICAL ATTENTION. Flash Point Method:TCC Flash Point:103F,39C Autoignition Temp: Autoignition Temp Text: 510 F Lower Limits:0.7 Upper Limits:6.0 Extinguishing Media:CO2, FOAM, DRY CHEMICAL Fire Fighting Procedures: COOL CONTAINERS WITH WATER, USE SELF-CONTAINED BREATHING APPARATUS, BURNING PRODUCT IS TOXIC. Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY BURST WHEN EXPOSED TO EXTREME HEAT. ISOLATE FROM HEAT, SPARKS, OPEN FLAME. Spill Release Procedures: COLLECT MATERIAL INTO METAL CONTAINER. AVOID SPARKS FLAME, HOT SURFACES. WIPE OFF RESIDUE WITH RAG. ================== Handling and Storage _____ Handling and Storage Precautions: COMBUSTIBLE, KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. USE ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED CONTACT. KEEP CONTAINERS CLOSED. Other Precautions: STORE IN SECURE AREA. DISPOSE OF EMPTY CONTAINERS SAFELY. KEEP OUT OF REACH OF CHILDREN.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: USE SELF-CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE THRESHOLD LIMIT VA

LUE.

Ventilation:LOCAL EXHAUST RECOMMENDED. MECHANICAL-ASSURE FRESH AIR CIRCULATION. Protective Gloves:RUBBER Eye Protection:GOGGLES Other Protective Equipment:EYE BATH, SHOWER. Work Hygienic Practices:DO NOT EAT/DRINK OR SMOKE NEXT TO MATERIAL. WASH HANDS/FACE AFTER WORK.

Supplemental Safety and Health

HCC:F4

Boiling Pt:B.P. Text:320F,160C Melt/Freeze Pt:M.P/F.P Text:130F,54C Vapor Pres:2.0 Vapor Density:4.7 Spec Gra vity:0.8 (WATER=1) Evaporation Rate & amp; Reference:0.21 (BU AC=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:WAXY PASTE, SOLVENT ODOR. Percent Volatiles by Volume:72-80

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME Hazardous Decomposition Products:THEMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE

======= Disposal Considerations

Waste Disposal Methods:RECYCLE, INCINERATE, OR USE HAZARDOUS WASTE MANAGEMENT FACILITY FOR DISPOSAL ACORDING TO STATE AND FEDERAL REGULATIONS. EPA WASTE NO D001.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for

its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.