View NSN Online: https://aerobasegroup.com/nsn/8010-00-579-9533

ROSES QUALITY PAINT, DBA ROSE TALBERT PAINT CO. -- PREMIUM VELVET VINYL LATEX FLAT-LTB -- 8010-00-579-9533

============= Product Identification =================

Product ID:PREMIUM VELVET VINYL LATEX FLAT-LTB

MSDS Date:10/30/1992

FSC:8010

NIIN:00-579-9533

MSDS Number: BRLYF

=== Responsible Party ===

Company Name: ROSES QUALITY PAINT, DBA ROSE TALBERT PAINT CO.

Address:901 FRINK STREET

City:CAYCE State:SC ZIP:29033

Co

untry:US

Info Phone Num:803-796-0324

Emergency Phone Num:803-796-0324 Preparer's Name:DOD/HMIS (DGSC-SSH)

CAGE:GO531

=== Contractor Identification ===

Company Name: ROSE TALBERT PAINT CO

Address:901 FRINK ST

Box:City:CAYCE

State:SC ZIP:29033 Country:US

Phone:803-796-0324

CAGE:0CUY5

Company Name: ROSES QUALITY PAINT INC DBA ROSE TALBERT PAINT CO

Address:901 FRINK ST

City:CAYCE State:SC

ZIP:29033-5000

Country:US

Phone:803-796-0324

CAGE:GO531

======= Composition/Information on Ingredients ==

========

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 15.42%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name: ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000 Fraction by Wt: 1.82%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM, VAPOR; 9293

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Other REC Limits: NONE RECOMMENDED

**OSHA PEL** 

:0.05 MG/M3;1910.1025

ACGIH TLV:0.15 MG/M3;DUST 9293

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: CHROMATES

Other REC Limits: NONE RECOMMENDED

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: PULMONARY EDEMA MAY DEVELOPE WITH INHALATION OF HIGH CONCENTRATIONS. THIS MAT

## **ERIAL MAY**

CAUSE NOSE AND THROAT IRRITATION. EYES: THIS PRODUCT CAN BE IRRITATING TO THE EYES. SKIN: MAY CAUSE S KIN IRRITATION AND DRYING/DEFATTING OR CRACKING AND DERMATITIS ON REPEATED OR PROLONGED EXPOSURE TO THE SKIN.

- Explanation of Carcinogenicity: MANUFACTURER STATE THIS PRODUCT CONTAINS NO REPORTED CARCINOGENS OR SUSPECTED CARCINOGENS.
- Effects of Overexposure:EYE, SKIN AND LUNG IRRITATION. CONTINUED BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT CAUSING HEAD
- ACHE, NAUSEA AND DIZZINESS. THIS PRODUCT MAY BE FATAL FROM SWALLOWING LARGE AMOUNTS. MAY CAUSE N AUSEA, VOMITING, HEADACHES, DIZZINESS, STUPOR, AND KIDNEY DAMAGE. INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.
- Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, RESPIRATORY TRACT OR KIDNEY MAY BE AT INCREASED RISK FROM EXPOSURE.

## Fir

St Aid:INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. CONTACT A PHYSICIAN IMMEDIATELY. EYES: IMMEDIATELY FLUSH WITH LUKE WARM WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMI NATED CLOTHING. WASH WITH SOAP AND WATER. CONTACT A PHYSICIAN IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING. RINSE MOUTH IMMEDIATELY. GIVE 6 TO 8 OUNCES OF WATER IF CONSCIOUS. GET PHYSICIAN IMMEDIATE


Flash Point Method:TCC Flash Point:241F,116C

Lower Limits: 3.2 Upper Limits: 15.3

Extinguishing Media: CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures: WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP AND POSSIBLE AUTOIGNITION. USE FOG NOZZLES WITH WATER.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE W



COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40 CFR 372. ETHYLENE GL

YCOL, CAS NUMBER 107-21-1, % BY WEIGHT=1.82%. \*\*THIS MSDS COPIED

HEN EXPOSED TO EXTREME HEAT.

## FROM ONE OF A SIMILAR PRODUCT FROM THE SAME MFR.

HCC:N1
Boiling Pt:B.P. Text:379F,193C
Vapor Pres:10 @68F
Appearance and Odor:LIQUID
Percent Volatiles by Volume:47

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG ACIDS

particular situation.

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:MAY PRODUCE HAZ ARDOUS FUMES, INCLUDING CARBON DIOXIDE, CARBON MONOXIDE AND OXIDES OF NITROGEN.

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their