

MET-L-CHEK COMPANY -- E-59 REMOVER -- 6850-00-357-7926

=====
Product Identification
=====

Product ID:E-59 REMOVER

MSDS Date:01/01/1995

FSC:6850

NIIN:00-357-7926

MSDS Number: BRMFY

=== Responsible Party ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID ST

City:SANTA MONICA

State:CA

ZIP:90404-3770

Country:US

Info Phone Num:310-450-1111

Emergency Phone Num:310-450-1111/800-424-9300(CHEMTREC)

C

AGE:98733

=== Contractor Identification ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID ST

Box:00000

City:SANTA MONICA

State:CA

ZIP:90404

Country:US

Phone:310-450-1111/FAX 310452-4046

CAGE:98733

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC; (ALIPHATIC
PETROLEUM DISTILLATES)

CAS:64742-88-7

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of

Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:LIQUID IS MINIMALLY IRRITATING TO THE EYES AND SLIGHT IRRITATING TO THE SKIN. VAPORS MAY BE IRRITATING TO THE NOSE, THROAT AND UPPER RESPIRATORY TRACT, AND CAUSE CNS DEPRESSION.

Effects of Overexposure:EYES/SKIN:SLIGHT IRRITATION.
INHALATION:IRRITATION AND COUGHING, GIDDINESS AND HEADACHE.
INGESTION:NAUSEA, VOMITING.

Medical Cond Aggravated by E
xposure:PRE-EXISTING SKIN AND RESPIRATORY
DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED.
EYE CONTACT:FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. SKIN CONTACT:WASH WITH SOAP AND WATER. GET MED ATTENTION IF SYMPTOMS PERSIS T. INGESTION:DO NOT INDUCE VOMITING, DRINK 1-2 GLASSES OF WATER. GET MEDICAL HELP IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:145F,63C
Lower Limits:1
Upper Limits:5
Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. DO NOT USE DIRECT STREAM OF WATER.
Fire Fighting Procedures:DO NOT ENTER CONFINED FIRE SPACE W/O FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:CONTAINERS EXPO TO INTENSE HEAT FRM FIRE SHOULD BE COOLE
D W/WATER TO PREVENT VAP PRESSURE BUILD-UP WHICH
COULD RUPTURE CONTAINER.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. WEAR APPROPRIATE PROTECTIVE PROTECTIVE CLOTHING & RESPIRATOR.DIKE & TRANSFER LIQ TO A SALVAGE TANK.SOAK UP RESIDUE WITH ABSORBENT CLAY,SAND OR OTHR MATL.PLACE RAGS & ABSORB ED MATERL IN COVERED CONTAINERS FOR DISPOSAL.

=====
===== Handling and Storage =====

====

Handling and Storage Precautions:KEEP AWAY FROM HEAT/IGNITION SOURCES.
STORE IN DRY,COOL,& VENTILATED LOCATION.DO NOT STORE NEAR OXIDIZING
MATERIAL. AVOID PHYSICAL DAMAGE TO CANS.

Other Precautions:MINIMIZE CONTACT. USE IN WELL VENTILATED AREA.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE EXCEEDS TLV,USE NIOSH APPRVD
RESPIRATOR TO PREVENT OVEREXPOSURE.

Ventilation:PER MANUFACTURER,PROVIDE LOCAL EXHAUST, OR MECHANICAL

(GENERAL) VENTILATION TO MAINTAIN TLV.

Protective Gloves:CHEMICAL RESISTANT.

Eye Protection:GOGGLES.

Other Protective Equipment:EYE WASH FOUNTAINS AND SAFETY SHOWERS.

Work Hygienic Practices:WASH WITH SOAP AND WATER BEFORE
EATING,DRINKING, SMOKING OR USING TIOLET FACILITIES.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:355F,179C

Vapor Pres: