

INDIUM CORP OF AMERICA -- #5R LIQUID FLUX -- 3439-00-220-3827

=====
Product Identification
=====

Product ID:#5R LIQUID FLUX

MSDS Date:07/10/1990

FSC:3439

NIIN:00-220-3827

MSDS Number: BRNJV

=== Responsible Party ===

Company Name:INDIUM CORP OF AMERICA

Address:1676-80 LINCOLN AVE

City:UTICA

State:NY

ZIP:13502

Country:US

Info Phone Num:315-768-6400

Emergency Phone Num:315-768-6400

Preparer's Name:G

REG EVANS

CAGE:74858

=== Contractor Identification ===

Company Name:INDIUM CORP OF AMERICA

Address:1676-80 LINCOLN AVE

Box:City:UTICA

State:NY

ZIP:13502

Country:US

Phone:315-768-6400

CAGE:74858

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 60-75%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:MODIFIED GUM ROSIN

Fraction by Wt: 3

0-40%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:TLV PROPANOL=400PPM

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL:PROLONGED OVEREXPOSURE MAY CAUSE
COUGHING,INTOXICATION.EYES:MODERATE IRRITATION.SKIN:NO ADVERSE
EFFECTS EXPECTED.INGEST:POSSIBLE HEALTH HAZARD(MFR. NOT SPECIFIC).

Effects of Overexposure:INHAL:CO

UGHING,SHORTNESS OF

BREATH,COUGHING,DIZZINESS.EYES:BURNING,TEARING,REDNESS,SWELLING.

Medical Cond Aggravated by Exposure:ANY EXISTING CONDITIONS MAY BE
AGGRIVATED.

=====
===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL
RESPIRATION IF NEEDED.GET PROMPT QUALIFIED MEDICAL
ATTENTION.EYE:RINSE WITH CLEAN WATER FOR 20-30 MINUTES,WHILE
LIFTING LIDS.CALL PHYSICIAN.SKIN:REM OVE CONTAMINATED CLOTHING;WASH

WITH SOAPAND WATER;FLUSH WITH LUKEWARM WATER.IF STICKY,USE
WATERLESS CLEANER FIRST.INGEST:GIVE 1 PT LUKEWARM WATER(IF
CONSCIOUS).DO NOT INDUCE VOMITING.GET MEDICAL HELP

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:53.0F,11.7C

Autoignition Temp:Autoignition Temp Text:750F

Lower Limits:2

Upper Limits:12

Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE.

Fire Fighting Procedures:USE PROTECTIVE EQUIPMENT.FIGHT FIRE FROM SAFE

DISTANCE.WATER MAY BE INEFFECTIVE(LOW FLASHPOINT).USE A
SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE FROM HEAT.VAPORS
ARE RELEASED AT AMBIENT TEMPERATURES WHICH TRAVEL ALONG THE GROUND
AND CAN FLASHBACK OR EXPLODE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE AREA.REMOVE SOURCES OF IGNITION.STOP
RELEASE.PREVENT RUNOFF INTO WATERWAYS.NOTIFY FIRE AND ENVIRONMENTAL
AUTHORITIE

S.
Neutralizing Agent:NONE

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE TIGHTLY CLOSED,VENTED
CONTAINERS,AWAY FROM HEAT,SPARKS AND FLAME,STRONG OXIDIZERS.USE
NON-SPARKING TOOLS.INCOMAPATIBLE WITH PLASTIC,AL,RUBBER.
Other Precautions:GROUND CONTAINERS WHEN TRANSFERRING LIQUID.EMPTY
CONTAINERS MAY CONTAIN EXPLOSIVE RESIDUE.CHECK ATMOSPHERE FOR
OXYGEN DEFICIENCY AND EXPLOSIVITY WHEN ENTERING CONFINED
SPACES(EG.TANK)

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR.
Ventilation:LOCAL AND/OR MECHANICAL EXHAUST ...AS NEEDED.
Protective Gloves:CHEMICALLY RESISTANT
Eye Protection:FACE SHIELD
Other Protective Equipment:APRON
Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET
CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK
AREA.
Supplemental Safety and Health
PREVENT EYE CONTACT.

=====
Physical/Chemical Properties
=====

HCC:F2
NRC/State Lic Num:NONE
Boiling Pt:B.P. Text:180F,82C
Melt/Freeze Pt:M.P/F.P Text:LIQUID @RT
Vapor Pres:33@20C
Vapor Density:2.1
Spec Gravity: