

TRIANGLE COATINGS INC -- PRIMER COATING: LIQUID VEHICLE COMP A -- 8010-00-787-8856  
===== Product Identification =====

Product ID:PRIMER COATING: LIQUID VEHICLE COMP A

MSDS Date:04/11/1990

FSC:8010

NIIN:00-787-8856

Kit Part:Y

MSDS Number: BRNPG

=== Responsible Party ===

Company Name:TRIANGLE COATINGS INC

Address:1930 FAIRWAY DR

City:SAN LEANDRO

State:CA

ZIP:94577-5631

Country:US

Info Phone Num:510

-895-8000

Emergency Phone Num:510-895-8000

Preparer's Name:JTK

CAGE:0GB20

=== Contractor Identification ===

Company Name:TRIANGLE COATINGS INC

Address:1930 FAIRWAY DR

Box:City:SAN LEANDRO

State:CA

ZIP:94577-5631

Country:US

Phone:800-895-8000

CAGE:0GB20

===== Composition/Information on Ingredients =====

Ingred Name:PHENYL DIMETHYL (XYLENE) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 1%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100.00 PPM

ACGIH TLV:100 PPM/STEL 15

0 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)  
CAS:100-41-4  
RTECS #:DA0700000

Fraction by Wt: FEW INCHES. KEEP AWAY FROM HEAT, SPARKS, OPEN  
FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:DO NOT STORE >120F. SUITABLE STORAGE SHOULD BE  
PROVIDED IN ACCORD W/OSHA REGS 1910.10A. EMPTY CNTNRS MAY CONTAIN  
RESIDUE. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR CONTAINER. OBSERVE  
ALL LABEL WARNING UNTIL CONTAINER CLEANED/RECONDITIONED.

=  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR FITTED RESPIRATOR (NIOSH/MSHA) DURING &  
AFTER APPLICATION UNLESS AIR MONITORING VAPOR/MIST LEVELS ARE BELOW  
APPLICABLE LIMITS. FOLLOW RESPIRATOR MANUFACTURERS DIRECTIONS FOR  
RESPIRATOR USE.

Ventilation:REQUIRED FOR SPRAYING OR IN CONFINED AREA, VENTILATION  
EQUIPMENT SHOULD BE EXPLOSION PROOF. ELIMINATE IGNITION SOURCES.

Protective Gloves:HAND PROTECTION FOR PAINT APPLICATION

Eye Protec

tion:EYE PROTECTION FOR APPLYING PAINT

Other Protective Equipment:USUAL CLOTHING FOR PAINTING OPERATIONS.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:156F,69C

Vapor Pres:78.0 @ 68F

Vapor Density:4.1

Spec Gravity:1.05

Evaporation Rate & Reference:5.6 (BU AC=1)

Solubility in Water:NO

Appearance and Odor:NORMAL FOR A COATING PRODUCT.

Percent Volatiles by Volume:59.73

===== Stability and Reactivit

y Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS

Stability Condition to Avoid: NONE

Hazardous Decomposition Products: SILICON DIOXIDE, NITROGEN OXIDES,  
CARBON DIOXIDE, CARBON MONOXIDE, METAL OXIDES.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN CHEMICAL DISPOSE AREA OR IN A MANNER  
THAT COMPLIES WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT  
INCINERATE CLOSED CONTAINERS.

Disclaimer (prov

ided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.