

DEL PAINT MFG. -- TT-E-506K ENAMEL ALKYD GLOSS WHITE 17886 -- 8010-00-901-8035

=====
Product Identification
=====

Product ID:TT-E-506K ENAMEL ALKYD GLOSS WHITE 17886

MSDS Date:05/10/1993

FSC:8010

NIIN:00-901-8035

MSDS Number: BRNPY

=== Responsible Party ===

Company Name:DEL PAINT MFG.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

Country:US

Info Phone Num:405-672-1431

Emergency Phone Num:800-4

24-9300 CHEMTREC

CAGE:DELPA

=== Contractor Identification ===

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

Company Name:DEL PAINT MFG.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

Country:US

Phone:405-672-1431

CAGE:DELPA

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM DISTILLATE (VAPOR PRESSURE 2.0 MM HG @ 20C)

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 27

.66%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM

Ingrid Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 0.24%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL;9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:IF TLV'S ARE
EXCEEDED. VAPORS ARE INTOXICATING
& NARCOTIC. THEY ALSO CAUSE IRRITATION TO THE MUCOUS MEMBRANES OF
THE LUNG. SKIN CONTACT PRODUCES REDNESS. EYE CONTACT PRODUCES
REDNESS & PAIN. INHALATION GIVES LABORED BREATHING. DULLNESS &
DROWSINESS. INGESTION CAN CAUSE ABDOMINAL PAIN & NAUSEA.
Medical Cond Aggravated by Exposure:DISEASES OF THE RESPIRATORY SYSTEM.

===== First Aid Measures =====

First Aid:SKIN-REMOVE CONTAMINATED CLOTHING. SHOWER OR RI
NSE SKIN WITH
PLENTY OF WATER. EYE-RINSE WITH COPIUS AMOUNTS OF WATER. TRANSPORT
TO PHYSICIAN IF NECESSARY. INHALATION-REMOVE TO FRESH AIR. GIVE
ARTIFICIAL RESPIRATION IF NECESSARY & CONTACT A PHYSICIAN.
INGESTION-RINSE MOUTH & DRINK PLENTY OF WATER. DO NOT INDUCE
VOMITING, SEEK MEDICAL ASSISTANCE.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:100F,38C
Lower Limits:1.1
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY

CHEMICAL

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE MODE.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL ALONG THE GROUND OR MAY BE MOVED BY VENTILATION & IGNITED BY PILOT LIGHTS, & OTHER IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A CLEAN DRY AREA. KEEP AWAY FROM FOOD PRODUCTS. KEEP AWAY FROM SPARKS, FIRES & REMOTE IGNITION SOURCES.

Other Precautions:THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH DEL PAINT OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENTLY APPLICABLE & SUITABLE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV OF THE PRODUCT OR ANY COMPONENT IS EXCEEDED. A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS UNDER SPECIFIED COND.

Ventilation:PROVIDE VENTILATION SUFFICIENT TO MAINTAIN EXPOSURE BELOW TLV'S.

Protective Gloves:WEAR RESISTANT GLOVES SUCH AS: BUNA-N

Eye Protection:SPLASH GOGGLES, SAFETY GLASSES

Other Protective Equipment:TO PREVENT REPEATED OR PROLONGED SKIN CONTACT. WEAR IMPERVIOUS CLOTHING AND BOOTS.

Work Hygienic Practices:WASH HANDS AND FACE BEFORE EATING

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300 TO 360F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:49.42

===== S

Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: DO NOT STORE NEAR HEATED SURFACES. OPEN
FLAMES, OR IGNITION SOURCES.

Hazardous Decomposition Products: CARBON DIOXIDE AND WATER ARE FORMED ON
COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSAL OF WASTE MATERIAL MUST COMPLY WITH
LOCAL, STATE & FEDERAL REGULATION

S. IF APPROVED, IT MAY BE REMOVED
TO A LICENSED LAND FILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for
the suitability of this information to their
particular situation.