

CHEM-TREND INC -- LUMOR X -- 6850-01-196-5472

=====  
Product Identification  
=====

Product ID:LUMOR X  
MSDS Date:07/09/1993  
FSC:6850  
NIIN:01-196-5472  
MSDS Number: BRNSN  
=== Responsible Party ===  
Company Name:CHEM-TREND INC  
Address:3205 E GRAND RIVER  
City:HOWELL  
State:MI  
ZIP:48843-8552  
Country:US  
Info Phone Num:517-546-4520  
Emergency Phone Num:800-248-4056 OR 517-546-4520  
Preparer's Name:JLG  
CAGE:2W7  
38

==== Contractor Identification ===  
Company Name:CHEM-TREND INC  
Address:1445 W. MCPHERSON PARK DR  
Box:860  
City:HOWELL  
State:MI  
ZIP:48844-0860  
Country:US  
Phone:800-727-7730  
CAGE:2W738  
Company Name:DUNN R G ASSOCIATES INC  
Address:15104 LEE RD SUITE 203-B  
Box:City:HUMBLE  
State:TX  
ZIP:77396-2078  
Country:US  
Phone:281-441-2001/FAX: 281-441-7772  
CAGE:0A272

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HYDROTREATED LIGHT PETROLEUM DISTILLATE (HYDROCARBON  
NAPHTHA

)  
CAS:64742-47-8  
Fraction by Wt: 99%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3 OIL MIST  
ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:ADDITIVE BLEND (INGREDIENTS REGISTERED IN TSCA INVENTORY)

Fraction by Wt: 220F,>104C

Lower Limits:0.6

Upper Limits:7

Extinguishing Media:USE FOAM, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRE IN CONFINED SPACE. COOL CONTAINERS EXPOSED TO INTENSE HEAT WITH WATER TO PREVENT RUPTURE.

Unus

ual Fire/Explosion Hazard:'EMPTY' CONTAINERS MAY CONTAIN RESIDUE OR VAPOR. TREAT THEM WITH THE RESPECT DUE FULL ONES. DO NOT CUT,WELD,ETC. ON THEM.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL:SOAK UP WITH ABSORBENT MATERIAL.  
LARGE:ELIMINATE IGNITION SOURCES. VAPORS HEAVIER THAN AIR AND MAY SPREAD LONG DISTANDES OR COLLECT IN LOW SPOTS. DIKE TO PREVENT RUNOFF. RECOVER LIQUID. SOAK UP REMAINDER WITH ABSORBENT MATERIAL.

N

utralizing Agent:NO INFORMATION GIVEN ON MSDS BY MFR.

===== Handling and Storage =====

Handling and Storage Precautions:GROUND CONTAINERS AND EQUIPMENT WHEN TRANSFERRING LIQUID. PROTECT FROM STATIC ELECTRIC SPARKS & OTHER IGNITION SOURCES. KEEP AWAY FROM OXIDIZERS.

Other Precautions:DO NOT STORE ABOE 110F TO AVOID PRESSURE IN CLOSED CONTAINERS. KEEP CLOSED WHEN NOT IN USE.

===== Exposure Controls/Personal Protection =====

Resp

iratory Protection:RESPIRATORS MAY BE USED WHEN ENGINEERING OR WORK PRACTICE CONTROLS ARE NOT FEASIBLE. IF USE OF A RESPIRATOR IS NECESSARY USE ONLY A MSHA/NIOSH APPROVED AIR SUPPLIED OR AIR PURIFYING RESPIRATOR.

Ventilation:GOOD PRACTICES RECOMMEND THAT LOCAL AND/OR MECHANICAL VENTILATION BE USED TO REDUCE ENVIRONMENTAL CONCENTRATIONS TO PEL.

Protective Gloves:IMPERVIOUS (NEOPRENE, PVA, NITRILE)

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:A

PPROPRIATE CLOTHING TO AVOID SKIN CONTACT.

Work Hygienic Practices:MFR: ? HMIS:USE GOOD CHEMICAL HYGIENE

PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health

KEY2:KT MSDS NUMBER 18055

===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:459F,237C

Vapor Pres:1 MM

Vapor Density:>1

Spec Gravity:0.79

Evaporation Rate & Reference: