

SCOT LABORATORIES -- AEROQUIP HOSE ASSEMBLY LUBRICANT, 222070 -- 9150-01-359-6563
===== Product Identification =====

Product ID:AEROQUIP HOSE ASSEMBLY LUBRICANT, 222070

MSDS Date:01/26/1988

FSC:9150

NIIN:01-359-6563

MSDS Number: BRNZC

=== Responsible Party ===

Company Name:SCOT LABORATORIES

Address:16841 PARK CIRCLE DR

City:CHAGRIN FALLS

State:OH

ZIP:44022

Country:US

Info Phone Num:216-543-3033

E

mergency Phone Num:216-543-3033

CAGE:SCTLA

=== Contractor Identification ===

Company Name:SCOT LABORATORIES

Address:16841 PARK CIRCLE DR

Box:City:CHAGRIN FALLS

State:OH

ZIP:44022

Country:US

Phone:216-543-3033

CAGE:SCTLA

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM DISTILLATE(S)

CAS:8002-05-9

RTECS #:SE7449000

ACGIH TLV:500 PPM (MFR)

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTUR

ER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: SKIN: PROLONGED CONTACT MAY CAUSE DERMATITIS. EYE: POSSIBLE IRRITANT. INGEST: HARMFUL IF SWALLOWED. NAUSEA, DIARRHEA.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:RESPIRATORY CONDITIONS.

=====
===== First Aid Measures =====

Firs

First Aid:EYE: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS CONSULT A PHYSICIAN IMMEDIATELY. SKIN: WASH WITH SOAP AND WATER. CHANGE SOAKED CLOTHING. INGEST: DO NOT INDUCE VOMITING. CONTAINS PETROLEUM DISTILLATES. CONSULT A PHYSICIAN. INHAL: REMOVE TO FRESH AIR. SUPPORT BRTHG (GIVE O*2/ARTF RESP) .

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>405F,>207C

Extinguishing Media:TREAT AS CLASS B FIRE. USE CARBON DIOXIDE, FOAM OR POWDER.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:DO NOT USE ON HOT SURFACES AND NEAR SOURCES OF IGNITION SUCH AS FIRE, SPARKS, OR WELDING EQUIPMENT.

=====
===== Accidental Release Measures =====

Spill Release Procedures:MOP UP, WET VACUUM OR USE AN ABSORBENT MATERIAL (SAND, EARTH, CLAY, OR SAWDUST). RINSE AREA WITH WATER AND DETERGENT TO COMPLETELY REMOVE PRODUCT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:HANDLE IN VENTILATED AREA. DO NOT STORE NEAR OPEN FIRE OR DIRECT HEAT. VENT LARGE TANKS TO OUTSIDE.

Other Precautions:NONE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:LOCA

L EXHAUST: NORMALLY ADEQUATE. MECHANICAL(GENERAL): IF

TLV'S ARE EXCEEDED USE MECHANICAL.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE NEEDED FOR NORMAL USE.

Work Hygienic Practices:FOLLOW GOOD MANUFACTURING AND HOUSEKEEPING PRACTICES.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>578F,>303C

Vapor Pres:NEGLIGIBLE

V

apor Density:>1

Spec Gravity:0.8900(H*2O=1)

Evaporation Rate & Reference: