View NSN Online: https://aerobasegroup.com/nsn/6810-00-978-1878

Product ID:BENZENE, 9156 MSDS Date:11/02/1992 FSC:6810 NIIN:00-978-1878 **MSDS Number: BRQFH** === Responsible Party === Company Name: ABSOLUTE STANDARDS INC Address:498 RUSSELL ST City:NEW HAVEN State:CT ZIP:06513 Country:US Info Phone Num:800-368-1131 Emergency Phone Num:800-368-1131 CAGE:0TZV1 === Contrac tor Identification === Company Name: ABSOLUTE STANDARDS INC Address:44 ROSSOTTO DR Box:5585 **City:HAMDEN** State:CT ZIP:06518 Country:US Phone:203-281-2917 CAGE:0TZV1 Ingred Name: BENZENE (SARA III) CAS:71-43-2 RTECS #:CY1400000 Fraction by Wt: 99-100% OSHA PEL:10 PPM ACGIH TLV:10 PPM EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

LD50 LC50 Mixture:LD50:(ORAL RAT)4894

MG/KG. Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:INHALATION MAY CAUSE HEADACHE, NAUSEA, VOMITING, DIZZINESS, NARCOSIS, SUFFOCATION, LOWER BLOOD PRESSURE, CENTRAL NERVOUS SYSTEM DEPRESSION. INHALATION OF VAPORS MAY CAUSE SEVERE IRRITATION OR BURNS OF RESPIRATORY SYSTEM, PULMONARY EDEMA, OR LUNG INFLAMMATION. CONTACT WITH SKIN OR EYES MAY CAUSE IRRIT. (EFTS OF OVEREXP)
Expl
anation of Carcinogenicity:BENZENE:GRP1(IARC VOL SUPP 7,P.120,'87); CARCIN(NTP 6'TH ANN RPT ON CARCIN,'91)OSHA REGULATD,29 CFR 1910.1028,J-1 02,92.
Effects of Overexposure:HLTH HAZ:PRLNGD SKIN CNTCT MAY RSLT IN DERM. EYE CNTCT MAY RSLT IN TEMPORARY CORNEAL DMG. INGEST MAY CAUSE HDCH, NAUS, VOMIT, DIZZ, GI IRRIT, BLURRED VISION, & LOW BLOOD PRESS. IRREVERSIBLE INJURY TO BLOOD FORMING TISS MAY RSLT FROM CHRONIC EXPOS. TARGET ORGANS:BLOOD, CNS, EYES, SKIN, BONE MARROW, RESP SYS, LUNGS.
Medical Cond Aggravated by Exposure:NONE IDENTIFIED.
======================================
First Aid:INGEST:DO NOT INDUCE VOMITING. INHAL:REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. EYE/SKIN:IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 M INUTES.
======================================
Flash Point Method:CC Flash Point:12F,-11C Lower Limits:1 .3%
 Upper Limits:8% Extinguishing Media:USE ALCOHOL FOAM, DRY CHEMICAL OR CARBON DIOXIDE. WATER MAY BE INEFFECTIVE. Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROT EQUIP. MOVE CNTNRS FROM FIRE AREA IF IT CAN BE DONE W/OUT RISK. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL.
Unusual Fire/Explosion Hazard: VAPORS MAY FLOW ALONG SURFS TO DISTANT IGNIT SOURCES & FLASH BACK. CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE. CONTACT WITH STRONG OXIDIZERS MAY CAUSE F

======================================
Spill Release Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROT CLTHG. SHUT OFF IGNIT SOURCES; NO FLARES, SMKNG OR FLAMES IN AREA. STOP LEAK IF YOU CAN DO SO W/OUT RISK. USE WATER SPRAY TO REDUCE VAPS. TAKE UP W/SAND OR OT HER NON-COMBUST ABSORB MATL & PLACE IN (SUPDAT)
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
Handling and S torage Precautions:KEEP CONTAINER TIGHTLY CLOSED. STORE IN A COOL, DRY, WELL-VENTILATED, FLAMMABLE LIQUID STORAGE AREA. Other Precautions:GROUND CONTAINERS WHEN TRANSFERRING LIQUID TO AVOID SPARKS.
======================================
Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATORY PROTECTION REQUIRED IF AIRBORNE CONCENTRATION EXCEEDS TLV. AT CONCENTRATIONS UP TO 10 PPM, A NIOSH/MSHA APPROVED SCBA IS ADVISED. Ventilation:USE GENERAL OR LOCA L EXHAUST VENTILATION TO MEET TLV REQUIREMENTS.
Protective Gloves:POLYVINYL ALCOHOL GLOVES. Eye Protection:CHEM WORK GOGG & FULL LNGTH FSHLD Other Protective Equipment:UNIFORMS AND PROTECTIVE SUITS. Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health
SPILL PROC:CONTAINER FOR FURTHER DISOPSAL. FLUSH AREA WITH WATER.
======================================
Boiling Pt:B.P. Text:176F,80C Melt/Freeze Pt:M.P/F.P Text:42.8F,6.0C Vap or Pres:74.6 Vapor Density:2.77 Spec Gravity:0.88 (H*2O=1)

Spec Gravity:0.88 (H*2O=1) Solubility in Water:NEGLIGIBLE (