

SHERWIN-WILLIAMS CO SPRAYON PRODUCTS DIV -- 55230W25 LUBRICATING OIL GENERAL --
9150-00-458-0075

===== Product Identification =====

Product ID:55230W25 LUBRICATING OIL GENERAL

MSDS Date:08/13/1993

FSC:9150

NIIN:00-458-0075

MSDS Number: BRQPD

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS CO SPRAYON PRODUCTS DIV

Address:26300 FARGO AVE

City:BEDFORD HEIGHTS

State:OH

ZIP:44146-1310

Country:

US

Info Phone Num:216-292-7400

Emergency Phone Num:216-292-7400

CAGE:DO642

=== Contractor Identification ===

Company Name:SHERWIN-WILLIAMS CO THE SPECIALTY DIV.

Address:6830 COCHRAN RD.

Box:6709

City:SOLON

State:OH

ZIP:44139-3908

Phone:216-292-7400

CAGE:DO642

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400 OR 216-595-8634

CAGE:09800

===== Composition/Information on Ingredients =

=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST') (PARAFFIN OIL)

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 93C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM. WATER MAY BE INEFFECTIVE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER MAY BE USED TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:CONTENTS UNDER PRESSURE. DO NOT PUNCTURE, INCINERATE, OR EXPOSE TO TEMPERATURES ABOVE 120F. HEAT MAY CAUSE CONTAINER TO BURST.

Other Precautions:KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IN ACCORDANCE WITH 29 CFR 1910.134.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW REGULATORY LIMITS.

Protective Gloves:NONE NORMALLY REQUIRED.

Eye Protection:SAFETY GLASSES WITH UNPERFORATED SIDES

Other Protective Equipment:SAFETY SH

OWER AND EYE BATH. INDUSTRIAL TYPE

WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED OR REPEATED CONTACT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V2

Boiling Pt:B.P. Text:1 (ETHER=1)

Appearance and Odor:AEROSOL LUBRICANT

Percent Volatiles by Volume:2

===== Stability and Rea
ctivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE KNOWN.

Stability Condition to Avoid:DO NOT STORE ABOVE 120F.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE. DEPRESSURIZE CONTAINER.
DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This inf

ormation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.