View NSN Online: https://aerobasegroup.com/nsn/6850-01-113-4821

Product ID:CAB-O-SIL MSDS Date:04/01/1990 FSC:2040 NIIN:01-113-4821 Kit Part:Y **MSDS Number: BRQRR** === Responsible Party === Company Name: CABOT CORP CARBOSIL DIVISION Box:188 City:TUSCOLA State:IL ZIP:61953-0188 Country:US Info Phone Num:800-222-6745 FAX: 217-253-4334 Emergency Phone Num:217-253-3370 С AGE:3F733 === Contractor Identification === Company Name: CABOT CORP CARBOSIL DIVISION Address:700 E. U.S. HIGHWAY 36 Box:City:TUSCOLA State:IL ZIP:61953-0188 Country:US Phone:217-253-3370 CAGE:3F733 Ingred Name: SILICA, AMORPHOUS, FUMED, CRYST-FREE CAS:112945-52-5 Fraction by Wt: >99% Other REC Limits:NONE RECOMMENDED OSHA PEL:6 MG/M3 ACGIH TLV:10 MG/M3

Rou

tes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: INHALATION OF DUST MAY CAUSE MILD, TEMPORARY IRRITATION OF RESPIRATORY SYSTEM. EYE: MECHANICAL IRRITAION. CHRONIC: NONE KNOWN. Explanation of Carcinogenicity:SILICA IS NOT LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN. Effects of Overexposure:COUGHING, WHEEZING, SNEEZING, IRRITATION. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFA CTURER.
======================================
First Aid:INHALATION: MOVE TO FRESH AIR. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES. SEE DOCTOR IF ANY SYMPTOMS PERSIST. INGESTION:SEEK MEDICAL HELP IMMEDIATELY.
======================================
Flash Point:NONE Extinguishing Media:MEDIA APPROPRIATE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. Unusua
I Fire/Explosion Hazard:DRY POWDERED MATERIALS CAN BUILD STATIC ELECTRICAL CHARGES WHEN SUBJECTED TO FRICTION. PROPER CARE SHOULD BE TAKEN WHEN USING IN PRESENCE OF FLAMMABLES.
======================================
Spill Release Procedures:SWEEP UP OR VACUUM UP. WEAR DUST MASK. Neutralizing Agent:NONE
======================================
Handling and Storage Precautions:PRECAUTIONS SHOULD BE TAKEN AGAINST STATIC BUILD U P. AVOID FRICTION. Other Precautions:NONE.
======================================
Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR CONCENTRATIONS GREATER THAN TLV. Ventilation:USE ADEQUATE MECHANICAL VENTILATION. Protective Gloves:NONE NORMALLY REQUIRED. Eye Protection:SAFETY GLASSES Other Protective Equipment:NONE NORMALLY REQUIRED. Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. Supplemental Safety and He

alth

=

	Physical/Chemical Properties	
--	------------------------------	--

HCC:V7 Spec Gravity:2.2 pH:4.0 4% Solubility in Water:INSOLUBLE Appearance and Odor:FINE WHITE POWDER, ODORLESS. (PH OF 4% SLURRY = 4.0) Percent Volatiles by Volume:0

Stability Indicator/Materials to Avoid:YES NONE Stability Condition to Avoid:NONE Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

====== Disposal Co

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. CAB-O-SIL FUMED SILICA IS NOT A HAZARDOUS SUBSTANCE UNDER EPA CRCLA AND SARA TITLE III.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate an d

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.