

UNION CARBIDE CORP LINDE DIV -- CARBON DIOXIDE -- 4210-01-078-3669

===== Product Identification =====

Product ID:CARBON DIOXIDE

MSDS Date:05/01/1991

FSC:4210

NIIN:01-078-3669

MSDS Number: BRRKS

=== Responsible Party ===

Company Name:UNION CARBIDE CORP LINDE DIV

Address:39 OLD RIDGEBURY RD

City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Info Phone Num:203-744-3487

Emergency Phone Num:203-744-3487

CAGE:36346

=== Contractor Identification ===

Company Name:HILLER SYSTEMS INC

Address:833 PRINCIPAL LN

Box:City:CHESAPEAKE

State:VA

ZIP:23320

Country:US

Phone:757-549-9123

CAGE:1DA54

Company Name:KIDDE FENWAL INC

Address:400 MAIN ST

Box:City:ASHLAND

State:MA

ZIP:01721-2150

Country:US

Phone:508-881-2000

CAGE:0KDP7

Company Name:UNION CARBIDE CORP LINDE DIV

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Phone:800-822-4357; 304-744-3487

CAGE:36346

===== Co

Composition/Information on Ingredients =====

Ingred Name:CARBON DIOXIDE
CAS:124-38-9
RTECS #:FF6400000
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;95

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INGEST:UNLIKELY ROUTE OF EXPO.PROD GAS
@NORMAL TEMP/PRESSURES.SKIN A
BSORP:NO EVIDENCE OF ADVERSE EFFECTS
FRM AVAILABLE INFO.INHAL:ASPHYXIAN.T.MODERATE CONCEN MAY CAUSE
HEAD,DROW,DIZZ,STINGING OF NOSE/T HROAT,EXCITATION,RAPID BREATHING
& HEART RATE,EXCESS SALIVATION,VOMIT,UNCONSC.SKIN/EYE:NO HARMFUL
EFFECT EXPECTED (SUPP)
Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT
IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN.
Effects of Overexposure:DAMAGE TO RETINAL GANGLION CELLS & CNS MAY
OCCUR. FROSTBITE. HEADACHE, DROWSINE
SS, DIZZ, STINGING OF
NOSE/THROAT,ESCITATION, RAPID BREATHING & HEART RATE, EXCESS
SALIVATION, VOMITING, UNCONSCIOUSNESS.
Medical Cond Aggravated by Exposure:KNOWLEDGE OF AVAILABLE TOXICOLOGY
INFO & OF PHYSICAL & CHEM PROPERTIES OF MATL SUGGEST THAT OVEREXPO
IS UNLIKELY TO AGGRAVATE EXISTING MED CONDITIONS.

===== First Aid Measures =====

First Aid:SKIN:EXPO TO COLD VAP/SOLID IMMED WARM FROSTBITE AREA W/WARM
WATER(NOT TO EXCEED 105F).MAS
SIVE EXPO REMOVE CLOTH WHILE SHOWERING
W/WARM WATER.OBTAIN MED ATTN.INHAL:REMOVE TO FRESH AIR.NOT BREATH
GIVE ART RESP.QUALIFIED PERSONNEL MAY GIVE OXY IF BREATH IS
DIFFICULT.OBTAIN MED ATTN.EYE:EXPO TO COLD VAP/SOLID IMMED FLUSH
WELL W/WATER FOR @LEAST 15MINS.OBTAIN MED ATTN PREFERABLY
OPHTHALMOLOGIST (SUPP)

===== Fire Fighting Measures =====

Extinguishing Media:CARBON DIOXIDE CANNOT CATCH FIRE. USE MEDIA
APPROPRIATE FOR SURROUNDING F

IRE.

Fire Fighting Procedures:EVACUATE ALL PERSONNEL FROM DANGER AREA.IMMED
DELUGE CNTNRS W/WATER SPRAY FROM MAXIMUM DISTANCE UNTIL COOL THEN
MOVE CNTNRS AWAY FROM FIRE AREA IF W/O RISK.

Unusual Fire/Explosion Hazard:GAS CANNOT CATCH FIRE.CNTNR MAY RUPTURE
DUE TO FIRE HEAT.NO PART OF CNTNR SHOULD BE SUBJ TO TREMP >52C.MOST
CNTNRS ARE PROVIDED W/PRESS RELIEF DEVICE (SUPPLEME)

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE PE
PERSONNEL.USE SCBA WHERE NEEDED.SHUT
OFF W/O RISK.VENTI & MOVE CNTNR TO WELL VENTIL AREA.TEST ESPECIALLY
CONFINED AREAS FOR SUFFI OXY CONTENT PRIO TO PREMITTING RE-ENTRY OF
PERSONNEL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE PIPE/EQPMT ADEQ DESIGNED TO
W/STAND PRESS.CAN CAUSE RAPID SUFFOCATION DUE TO OXY
DEFICIENCY.STORE/USE W/ADEQ VENTIL.CLS VAL WHEN NOT IN USE/
EMPTY.

Other Precautions:GAS HEAVIER THAN AIR ACCUMULATE NEAR FLOOR DISPLACING
AIR.VENTI AREA BEF ENTRY.VERIFY SUFF OXY CONCEN.WHEN 2 OR MORE
GASES MIXED HAZ PROP MAY COMBINE.CONSULT INDUST HYGIENIST TO
EVALUATE MIXTURE.READ/ UNDERSTAND LABELS/INSTURCTIONS W/MATL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELECT IAW OSHA29CFR1910.134/ANSI Z88.2.CONCEN
10X APPLICABLE EXPO LIMIT ANY NIOSH/MSHA APPROVED SUPPLIED AIR
RESP.UP 50X

NIOSH/MSHA APPROVED RESP W/FULL FACEPC OR SCBA.HIGHER
CONCEN USE ONLY SCBA OPE RATED IN PRESSURE-DEMAND MODE.

Ventilation:LOCAL EXHAUST:PREFERRED. MECHANICAL(GENERAL):ACCEPTABLE.

Protective Gloves:INSULATED NEOPRENE GLOVES.

Eye Protection:SELECT IAW OSHA 29CFR1910.133.

Other Protective Equipment:METATARSAL SHOES FOR CYL HANDLING.SELCE IAW
OSHA 29CFR1910.132 & 1910.133.

Work Hygienic Practices:PAMPHLET P-1 FRM COMP GAS ASSOC INC,1235 JEF
DAVID HYWAY,ARLINGTON,VA22202.NEVER WORK ON PRE

SSURIZED SYSTEM.

Supplemental Safety and Health

SUBLIM PT 760MM HG:-78.5C. FIRE/EXPLO HAZ:DESIGNED TO VENT WHEN EXPO HI
TEMP. HEALTH HAZ:FROM GAS.COLD VAP/SOLID CARBON DIOXIDE MAY CAUSE
FROSTBITE.CHRONIC:NO EVIDENCE FROM AVAILABLE INFO. 1ST AID:IMME
D.NOTE TO DR:NO SPECIFIC ANTIDOTE.TREATMENT OF OVEREXPO SHOULD BE
DIRECTED @CNTRL OF SYMPTOMS/CLINICAL VICTIM CONDITONS.

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:SEE SUPPLEM

Vap

or Pres:830 @21C

Vapor Density:1.522 @21C

Evaporation Rate & Reference:HIGH,(N-BUTYL ACETATE=1)

Solubility in Water:SLIGHT

Appearance and Odor:COLORLESS GAS AT NORMAL TEMPERATURE & PRESSURE;
ODORLESS.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALKALI METALS,ALKALINE EARTH METALS,METAL ACETYLIDES,CHROMIUM,TITANIUM
>550C,URANIUM >750C.

Stability Condition to Avoid:NONE SPECIFIED BY MAN
UFACTURER.

Hazardous Decomposition Products:IN THE PRESENCE OF ELECTRICAL
DISCHARGE, CARBON DIOXIDE IS DECOMPOSED TO FORM CARBON MONOXIDE &
OXYGEN.

===== Disposal Considerations =====

Waste Disposal Methods:SLOWLY RELEASE INTO ATM OUTDOORS.DISCARD ANY
PROD/RESIDUE/DISPOSABLE CNTNR OR LINER IN ENVIRONMENTALLY
ACCEPTABLE MANNER IN FULL COMPLIANCE W/LOCAL, STATE AND FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compili

ng agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.