

ELECTROCHEM INDUSTRIES,DIV.OF WILSON GREATBATCH -- LITHIUM OXYHALIDE PRIMARY BATTERY (BCX) -- 6135-01-218-3660

===== Product Identification =====

Product ID:LITHIUM OXYHALIDE PRIMARY BATTERY (BCX)

MSDS Date:01/19/1993

FSC:6135

NIIN:01-218-3660

MSDS Number: BRRLB

=== Responsible Party ===

Company Name:ELECTROCHEM INDUSTRIES,DIV.OF WILSON GREATBATCH

Address:10000 WEHRLE DR.

City:CLARENCE

State:NY

Z

IP:14031-2033

Country:US

Info Phone Num:716-759-6901

Emergency Phone Num:716-759-6901

CAGE:62713

=== Contractor Identification ===

Company Name:BATTERY OUTLET INC

Address:1608 CAMPOSTELLA RD

Box:City:CHESAPEAKE

State:VA

ZIP:23324

Country:US

Phone:757-545-4442

CAGE:0FGN2

Company Name:ELECTROCHEM INDUSTRIES, DIV. OF WILSON GREATBATCH

Address:10000 WEHRLE DR.

City:CLARENCE

State:NY

ZIP:14031-2033

Country:US

Phone:716-759-5384

CAGE:62713

===== Composition/Information on Ingredients =====

=====

Ingred Name:LITHIUM METAL
CAS:7439-93-2
RTECS #:OJ5540000
Other REC Limits:NONE SPECIFIED

Ingred Name:THIONYL CHLORIDE
CAS:7719-09-7
RTECS #:XM5150000
Other REC Limits:NONE SPECIFIED
OSHA PEL:C 1 PPM
ACGIH TLV:C 1 PPM; 9192

Ingred Name:BROMINE (SARA III)
CAS:7726-95-6
RTECS #:EF9100000
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.1 PPM/0.3 PPM STEL
ACGIH TLV:0.1 PPM/0.3STEL;9293

Ingred Name:CHLORINE (SARA III)
CAS:7782-50-5
RTECS #:FO2100000
Other REC Limits:NONE SPECIFIED
OSHA PEL:(C)
1 PPM
ACGIH TLV:0.5 PPM/1 STEL; 9293
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:THIS PRODUCT IS CLASSIFIED AS AN
ARTICLE UNDER OSHA REGULATION 1910.1200.
Explanation of Carcinogenicity:NOT CARCINOGENIC.
Effects of Overexposure:BURNS TO THE SKIN MAY RESULT FROM THE HEAT
GENERATED BY A S

HORT-CIRCUIT.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:IN CASE OF ACCIDENTAL INGESTION OF A CELL OR ITS CONTENTS, OBTAIN PROMPT MEDICAL ADVICE.

===== Fire Fighting Measures =====

Extinguishing Media:IF CELLS ARE DIRECTLY INVOLVED IN FIRE, DO NOT USE WATER, CARBON DIOXIDE, DRY CHEMICAL OR HALON.

Fire Fighting Procedures:A LITH-X (GRAPHITE BASE) FIRE EXTINGUISHER OR

MATERIAL IS THE ONLY RECOMMENDED EXTINGUISHING MEDIA FOR FIRES INVOLVING METAL OR CELLS. AVOID FUME INHALATION.

Unusual Fire/Explosion Hazard:IF A FIRE IS IN ADJACENT AREA, AND CELLS ARE PACKED IN THEIR ORIGINAL CONTAINERS, THE FIRE CAN BE FOUGHT BASED ON FUELING MATERIAL, E.G.,PAPER & PLASTICS.

===== Accidental Release Measures =====

Spill Release Procedures:NONE SPECIFIED BY MANUFACTURER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL BUT PREVENT CONDENSATION ON CELLS OR BATTERIES. ELEVATED TEMPERATURES CAN RESULT IN SHORTENED BATTERY LIFE.

Other Precautions:IF SOLDERING OR WELDING TO THE TERMINALS OF THE CELL IS REQUIRED, EXERCISE PROPER PRECAUTIONS TO PREVENT DAMAGE TO THE CELL WHICH MAY RESULT IN LOSS OF CELL CAPACITY, SEAL, LEAKAGE, AND/OR CELL EXPLOSION. DO NOT SOLDER TO THE CASE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.

Ventilation:NONE SPECIFIED BY MANUFACTURER.

Protective Gloves:NONE SPECIFIED BY MANUFACTURER.

Eye Protection:NONE SPECIFIED BY MANUFACTURER.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

MECHANICAL CONTAINMENT: ENCAPSULATION (POTTING OF THESE CELLS) WILL NOT

ALLOW FOR CELL EXPANSION. SUCH ENCLOSURE CAN RESULT IN HIGH PRESSURE EXPLOSION FROM HEATING DUE TO INADVERTENT CHARGING OR HIGH TEMPERATURE ENVIRONMENTS (I.E., IN EXCESS OF 100C.)

===== Physical/Chemical Properties =====

HCC:R2

Appearance and Odor:CYLINDRICAL.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

JEWELRY, SUCH AS RINGS AND BRACELETS, SHOULD BE REMOVED OR INSULATED FROM BATTERIES TO PREVENT SHORT CIRCUITING.

Stability Condition to Avoid: BATTERIES SHOULD ALWAYS BE PACKAGED & TRANSPORTED IN SUCH A MANNER AS TO PREVENT DIRECT CONTACT WITH EACH OTHER.

Hazardous Decomposition Products: SHORT-CIRCUITING WILL CAUSE HEAT AND REDUCE CELL CAPACITY.

===== Disposal Considerations =====

Waste Disposal Methods: DO NOT INCINERATE OR SUBJECT CELLS TO TEMPERATURES IN EXCESS OF 212F(100C). SUCH ABUSE CAN RESULT IN LOSS OF SEAL, LEAKAGE AND/OR CELL EXPLOSION. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.