

BENDIX CORP THE FRICTION MATERIALS DIV -- BENDIX FRICTION MATERIAL -- 2530-01-068-6451
===== Product Identification =====

Product ID:BENDIX FRICTION MATERIAL

MSDS Date:03/01/1988

FSC:2530

NIIN:01-068-6451

MSDS Number: BRTCD

=== Responsible Party ===

Company Name:BENDIX CORP THE FRICTION MATERIALS DIV

Address:GREEN ISLAND

Box:238

City:TROY

State:NY

ZIP:12181

Country:US

Info Phone Num:518-270-0200

Emergency Phone Num:518-270-0200

Preparer's Name:E.L. ROGERS

CAGE:76126

=== Contractor Identification ===

Company Name:BENDIX CORP THE FRICTION MATERIALS DIV-ALLIED CORP

Address:GREEN ISLAND

Box:238

City:TROY

State:NY

ZIP:12181

Country:US

Phone:518-273-6550/518-270-0200

CAGE:76126

Company Name:KALMAR AC HANDLING SYSTEMS INC

Address:777 MANOR PARK DR

Box:City:COLUMBUS

State:OH

ZIP:43228

Country:US

CAGE:0AHU0

===== Composition/Information on Ingredients =====

Ingred Name:ASBEST

OS, CHRYSOTILE
CAS:12001-29-5
RTECS #:CI6478500
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:2 FIBERS/CC; A1;9293

Ingred Name:SILICA, ALPHA QUARTZ
CAS:14808-60-7
RTECS #:VV7330000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:SILICATE(S)
CAS:14407-96-6
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Other REC Limits:NONE RECOMMENDED
OSHA PE
L:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9293

Ingred Name:COKE-PETROLEUM DERIVED
Other REC Limits:NONE RECOMMENDED

Ingred Name:PHENOLIC AND CASHEW RESINS,CURED
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:GRAPHITE
CAS:7782-42-5
RTECS #:MD9659600
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MPPCF RDUST
ACGIH TLV:2 MG/M3 RDUST; 9293

Ingred Name:IRON
CAS:7439-86-6
RTECS #:NO6925000
Other REC Limits:NONE RECOMMENDED

Ingred Name:IRON OXIDE
CAS:1309-37-1
RTECS #:NO7

400000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:ZINC (SARA III)
CAS:7440-66-6
RTECS #:ZG8600000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG ZNO/M3
ACGIH TLV:10 MG ZNO/M3; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ZINC OXIDE
CAS:1314-13-2
RTECS #:ZH4810000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15MG/M3 TDUST/5 FUME
ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name:ALUMINUM (SARA III)
CAS:7429-90-5
RTECS #:BD0330000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15MG/M3 DUST/5 FUME
ACGIH TLV:10MG/M3 DUST; 9293

Ingred Name:ALUMINUM OXIDE
CAS:1302-74-5
RTECS #:GN0231000
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:SKIN:PARTIALLY CURED PHENOLIC OR
CASHEW RESIN MAY CAUSE DERMATITIS.INHAL:SILICA DUST MAY CAUS

E

SILICOSIS.ASBESTOS CAN CAUSE ASBESTOSIS,LUNG CANCER,MESOTHELIOMA.
METAL DUST MAY CAUSE IRRITATION.EYES:MA Y CAUSE
IRRITATION.INGEST:MAY CAUSE GASTROINTESTINAL DISTURBANCES. PEOPLE
WHO SMOKE ARE AT INCREASED RISK FROM ASBESTOS.

Explanation of Carcinogenicity:CONTAINS A [1332-21-4] WHICH IS
LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure:PARTIALLY CURED CASHEW RESINS-SKIN ERUPTIONS
RESEMBLING POISON IVY.ASBESTOS/SILICA-COUGHING,WHEEZ
ING,SHORTNESS

OF BREATH,IMPAIRED PULMONARY FUNCTION. DUSTS IN EYE MAY CAUSE
IRRITATION. G/I DISTURBANCE S ARE POSSIBLE FROM INGESTION.

Medical Cond Aggravated by Exposure:SMOKERS ARE AT INCREASED RISK IN
WORKING WITH AIRBORNE ASBESTOS FIBERS.

=====
First Aid Measures
=====

First Aid:MANUFACTURER STATES THAT NONE SHOULD BE NESCESSARY WITH THE
PROPER HANDLING OF THIS MATERIAL.

=====
Fire Fighting Measures
=====

Extinguishing Media:WATER(TYPE A,B,C EXTINGUISHER),FOG,FOAM.
Fire Fighting Procedures:"N/A" (NONE SPECIFIED BY MANUFACTURER.)
Unusual Fire/Explosion Hazard:"N/A" (ONE SPECIFIED BY MANUFACTURER.)

=====
Accidental Release Measures
=====

Spill Release Procedures:HMIS: PICK UP PIECES. IF ASBESTOS DUST HAS
BEEN PRODUCED, WEAR HEPA FILTERED RESPIRATOR AND FOLLOW REGULATION
29CFR1900.1001, ASBESTOS STANDARD. CLEAN BY WET METHODS AND/OR HEPA
VACUUM.

Neut
ralizing Agent:NO INFORMATION GIVEN ON MSDS BY MFR.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT BREATH ASBESTOS DUST!
Other Precautions:NONE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NOT NORMALLY NEEDED. IF AIRBORNE ASBESTOS DUSTS
ARE BEING PRODUCED, WEAR NIOSH APPROVED HEPA RESPIRATOR OR SUPPLIED
AIR RESPIRATOR.

Ventilation:LOCAL EXHAUST IS PREFERRED.

Protective Gloves:CO

TTON OR CANVAS GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:USE CLOTHING TO COVER THE SKIN AGAINST CONTACT FROM DUST.

Work Hygienic Practices:USE PROPER DUST CONTROL MEASURES.USE A HEPA VACUUM;DO NOT DRY SWEEP.WET CLEAN SURFACES. SEE 29CFR1910.1001

Supplemental Safety and Health

KEY2:KT

===== Physical/Chemical Properties =====

HCC:T6

NRC/State Lic Num:NONE

Spec Gravity:1.6-3.7

Evaporation Rate & Reference:0

Solubility in Water:0

Appe

arance and Odor:SOLID,ODORLESS,LIGHT TAN TO DARK GREY COLOR.

Corrosion Rate:UNKNOWNN

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE KNOWN

Stability Condition to Avoid:NONE KNOWN

Hazardous Decomposition Products:INCOMPLETE COMBUSTION WILL RESULT IN CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR NONE KNOWN

===== Disposal Considerations =====

Waste Di

posal Methods:PLACE IN PROPER RECEPTACLES.DISPOSE OF IN AUTHORIZED LANDFILLS IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document shou

Id seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.