View NSN Online: https://aerobasegroup.com/nsn/9150-00-071-4712

TEXACO INC CORPORATE HQ -- 01562 CAPELLA WF 68 -- 9150-00-071-4712

Product ID:01562 CAPELLA WF 68 MSDS Date:01/04/1995 FSC:9150 NIIN:00-071-4712 MSDS Number: BRTDN === Responsible Party === Company Name: TEXACO INC CORPORATE HQ Address:2000 WESTCHESTER AVE **City:WHITE PLAINS** State:NY ZIP:10604-3613 Country:US Info Phone Num:914-838-7204, 800-782-7852 **Emergency Pho** ne Num:914-831-3400(CHEMTREC 800-424-9300) CAGE:59595 === Contractor Identification === Company Name: SALATHE OIL CO INC Address:2226 PETERS RD Box:City:HARVEY State:LA ZIP:70058 Country:US Phone:504-366-4542 CAGE:0T5C6 Company Name: TEXACO INC CORPORATE HQ Address:2000 WESTCHESTER AVE **City:WHITE PLAINS** State:NY ZIP:10604 Country:US Phone:914-253-4000 CAGE:59595

Ingred Name:DISTILLATES, ACID-TREATED HEAVY NAPHTHENIC CAS:64742-1

8-3 RTECS #:PY8032000 Fraction by Wt: 80-95% Other REC Limits:NONE RECOMMENDED OSHA PEL:300 PPM ACGIH TLV:300 PPM

Ingred Name:MINERAL OIL CAS:64742-53-6 RTECS #:PY8036000 Fraction by Wt: 10-20% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

LD50 LC50 Mixture:LD50 (ORAL RAT) IS >5000 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO I ARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHALATION OF VAPORS OR MIST, IN EXCESS OF THE RECOMMENDED LIMITS MAY CAUSE IRRITATION OF NOSE & THROAT, CNS EFFECTS. EYE CONTACT MAY CAUSE MINIMAL IRRITATION. PROLONGED SKIN CONTACT MAY CAUSE IRRITATION. INGESTION OR LARGE AMOUNTS MAY CAUSE GI TRACT IRRITATION. CHRONIC: NONE KNOWN.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN. Effect

s of Overexposure: PROLONGED SKIN CONTACT-IRRITATION, DISCOMFORT, LOCALIZED REDNESS. EYES-IRRITATION. DISCOMFORT. INHALED-IRRITATION OF NOSE & THROAT, HEADACHE, NAUSEA, DIZZINESS. INGESTED-ABDOMINAL DISCOMFORT, NAUSEA, DIARRHEA.

Medical Cond Aggravated by Exposure:BECAUSE OF ITS DEFATTING PROPERTIES, PROLONGED & REPEATED SKIN CONTACT MAY AGGRAVATE AN EXISTING DERMATITIS (SKIN CONDITION).

First Aid:EYES-FLU

SH EYES WITH PLENTY OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN-WASH SKIN WITH PLENTY OF SOAP & WATER. GET MEDICAL ATTENTION. INGESTION-IF CONSCIOUS, GIVE 2 GLASSES OF WATER. GET MEDI CAL ATTENTION. INHALATION-IF IRRITATION, HEADACHE, NAUSEA OR DROWSINESS OCCURS, REMOVE TO FRESH AIR. GET MEDICAL ATTENTION.

Flash Point Method:COC Flash Point:355F,179C Extinguishing Media:USE WATER SPRAY, DRY CHEMICAL, FOAM, OR CARBON DIOXIDE. WATER OR FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL FIRE FIGHTER'S PROTECTIVE GEAR. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:NONE.

Spill Release Procedures: VENTILATE AREA. AVOID BREATHING VAPOR. USE SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED AIR FOR LARGE SPILLS OR CONFINED AREAS. CONTAIN SPI

LL IF POSSIBLE. WIPE UP OR ABSORB ON SUITABLE MATERIAL & SH OVEL UP. PREVENT ENTRY INTO SEWERS. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: MINIMUM FEASIBLE HANDLING TEMPERATURES
 SHOULD BE MAINTAINED. WATER CONTAMINATION SHOULD BE AVOIDED.
 Other Precautions: DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID
 PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES.

USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:AIRBORNE CONCENTRATIONS SHOULD BE KEPT TO LOWEST LEVEL POSSIBLE. IF VAPOR, MIST OR DUST IS GENERATED, USE RESPIRATOR APPROVED BY MSHA OR NIOSH AS APPROPRIATE. SUPPLIED AIR RESPIRATORY PROTECTION SHOUL D BE USED FOR CLEANING LARGE SPILLS. Ventilation:ADEQUATE TO MEET OCCUPATIONAL EXPOSURE LIMITS. Protective Gloves:WASH SKIN SEVER AL TIMES DAILY.
Eye Protection: CHEMICAL-TYPE GOGGLES OR FACE SHIELD.
Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER.
Work Hygienic Practices: SOILED CLOTHING SHOULD BE LAUNDERED OR DRY-CLEANED AT LEAST ONCE A WEEK.
Supplemental Safety and Health
AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO

NOT BREATHE VAPORS OR MISTS.

HCC:V6 Spec Gravity:0.8950 Viscosity:64.6 CST @40C Evaporat ion Rate & amp; Reference:NONE SPECIFIED BY MFR. Appearance and Odor:CLEAR, YELLOW LIQUID; BLAND ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:TOXIC LEVELS OF CARBON MONOXIDE, CARBON DIOXIDE, IRRITATING ALDEHYDES AND KETONES. Conditions to Avoid Polymerization:WILL NOT OCCUR.

====== Dispo

Waste Disposal Methods: THIS PRODUCT HAS BEEN EVALUATED FOR RCRA CHARACTERISTICS & DOES NOT MEET THE CRITERIA OF A HAZARDOUS WASTE IF DISCARDED IN ITS PURCHASED FORM. IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE AT THE TIME OF DISPOSAL IF MATERIAL IS HAZARDOUS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States

of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.