View NSN Online: https://aerobasegroup.com/nsn/9150-00-186-6668

## CITGO PETROLEUM CORP -- CITGO NO 93423, 10W, MILITARY -- 9150-00-186-6668

Product ID:CITGO NO 93423, 10W, MILITARY

MSDS Date:03/15/1993

FSC:9150

NIIN:00-186-6668

MSDS Number: BRTDX === Responsible Party ===

Company Name: CITGO PETROLEUM CORP Address: 6100 S YALE BLDG 1 WARREN PL

Box:3758 City:TULSA State:OK ZIP:74102 Country:US

Info Phone Num:918-495-5933

Emergenc

y Phone Num:318-491-6215, CHEMTREC 800-424-9300

CAGE:7X110

=== Contractor Identification ===

Company Name: CITGO PETROLEUM CORP

Address:6100 S YALE AVE

Box:3758 City:TULSA State:OK ZIP:74102 Country:US

Phone:918-495-5933

CAGE:7X110

======= Composition/Information on Ingredients ========

Ingred Name: REFINED HEAVY PARAFFINIC DISTILLATES CONTAINING: CAS #

64741- 89-5 CAS:64741-88-4 Fraction by Wt: 75-90%

Other REC Limits:NONE SPECIFIED OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3

(OIL MIST)

Ingred Name:VI IMPROVER (CONTAINS DIALKYLDITHIOPHOSPHATE) Fraction by Wt: 10-15% Other REC Limits:NONE RECOMMENDED
Ingred Name:POUR DEPRESSANT Fraction by Wt: < 1% Other REC Limits:NONE SPECIFIED
======================================
LD50 LC50 Mixture:PRACTICALLY NON-TOXIC Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION-LOW RISK AT AMBIENT TEM
DERATURES. DERMAL-TRANSIENT, SLIGHT IRRITATION. EYE-PRACTICALLY NON-IRRITANT. INGESTION-LOW TOXICITY. IF LESS THAN ONE OUNCE IS INGESTED, MATERIAL MAY PASS THROUGH SY STEM WITHOUT HARM. INJECTION-SUBCUTANEOUS OR INTRAMUSCULAR INJECTION MAY CAUSE IRRITATION, ERYTHEMA, EDEMA. Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS
CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.  Effects of Overexposure:INHALATION-MIST OR FUMES MAY CAUSE DIZZINESS,  HEADACHE,
NAUSEA, RESPIRATORY IRRITATION, OR CHEMICAL PNEMONITIS. INGESTION-ON INGESTION OF LARGE QUANTITIES SLIGHT GI DISCOMFORT, DIARRHEA, HEADACHE MAY OCCUR. Medical Cond Aggravated by Exposure:NONE.
======================================
First Aid:INHALATION: REMOVE FROM EXPOSURE TO INCIDENTAL FUMES AND PROVIDE RESPIRATORY SUPPORT IF NECESSARY. DERMAL: WASH WITH SOAP AND WATER. EYES: FLUSH WITH LARGE AMOUNTS OF WATER. INGESTION: INDUCE VOMITING AN DISEEK MEDICAL AID.
======================================
Flash Point Method:COC Flash Point:414F,212C Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG. Fire Fighting Procedures:NONE. Unusual Fire/Explosion Hazard:WATER MAY CAUSE FROTHING.
========= Accidental Release Measures ============
Spill Release Procedures:REMOVE SOURCES OF HEAT OR IGNITION. PROVIDE

Spill Release Procedures:REMOVE SOURCES OF HEAT OR IGNITION. PROVIDE ADEQUATE VENTILATION. SMALL SPILL: TAK

E UP WITH NONCOMBUSTIBLE ABSORBENT SUCH AS FULLERS EARTH OR SAND. PLACE INTO CONTAINERS FOR LATER DISPOSAL. Neutralizing Agent: NOT APPLICABLE. ============= Handling and Storage ========================== Handling and Storage Precautions: KEEP CONTAINER TIGHTLY CLOSED AND AWAY FROM HEAT AND FLAME. Other Precautions: AVOID PROLONGED SKIN CONTACT WITH USED MOTOR OILS. CONTINUOUS CONTACT WITH USED OIL HAS CAUSED CANCER IN LABORATORY ANIMALS. AFTER DRAINING OIL, WASH SKIN T HOROUGHLY WITH SOAP AND WATER. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: IF HIGH VAPOR CONCENTRATION IS EXPECTED, USE RESPIRATOR APPROVED FOR ORGANIC VAPORS. Ventilation: USE IN WELL VENTILATED AREA. IN CONFINED SPACES, MECHANICAL VENTILATION MAY BE REQUIRED TO KEEP LEVELS BELOW STANDARD. Protective Gloves:OIL IMPERVIOUS GLOVES. Eye Protection: SAFETY GOGGLES, CHEMICAL SPLASH GOGGLES. Other Protective Equipment:WEAR BODY-COVERING WORK **CLOTHES TO AVOID** PROLONGED EXPOSURE. LAUNDER SOILED WORK CLOTHES BEFORE REUSE. Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR. Supplemental Safety and Health NOTE TO PHYSICIAN: FOLLOWING INGESTION, AT A SAYBOLT VISCOSITY OF ABOUT 187 AT 100F, THE RISK OF ASPIRATION INTO THE LUNGS IS REDUCED. FOR QUANTITIES ABOVE 1 OUNCE, EMESIS OR LAVAGE MAY BE CONSIDERED. SUBCUTANEOUS INJECTION RE

QUIRES PROMPTSURGICAL DEBRIDEMENT. IF NOT FAMILIAR WITH TECHNIQUE, SEEK SKILLED ADVICE.

======== Physical/Chemical Properties ============

HCC:V4 Boiling Pt:B.P. Text:650F,343C Vapor Pres:< 0.001 Vapor Density:>1

Spec Gravity:0.89

Evaporation Rate & Deference: