

LA GLORIA OIL & GAS COMPANY -- TURBINE FUEL, AVIATION, JP-8

=====  
MSDS Safety Information  
=====

FSC: 9130  
NIIN: 01-031-5816  
MSDS Date: 06/10/1993  
MSDS Num: BRTGN  
Product ID: TURBINE FUEL, AVIATION, JP-8  
MFN: 01  
Responsible Party  
Cage: MO636  
Name: LA GLORIA OIL & GAS COMPANY  
Box: 840  
City: TYLER TX 75710  
Info  
Phone Number: 903-535-2244  
Emergency Phone Number: 903-535-2244  
Review Ind: Y  
Published: Y

=====  
Contractor Summary  
=====

Cage: MO636  
Name: LA GLORIA OIL & GAS COMPANY  
Address: UNKNOWN  
Box: 840  
City: TYLER TX 75710  
Phone: 903-535-2244  
Cage: 3K472  
Name: LA GLORIA OIL AND GAS CO  
Address: 1702 E COMMERCE  
City: TYLER TX 75710  
Phone: 214-535-2244

=====  
Item Description Information  
=====

Item Name: TURBINE FUEL,AVIATION  
Unit of Issue: GL  
UI Container Qty: X

=====  
Ingredients  
=====

Name: PETROLEUM MIDDLE DISTILLATE  
% Wt: 100 %  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: NOT ESTABLISHED

=====  
Health Hazards Data  
==

=====

LD50 LC50 Mixture: NOT SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: IT MAY CAUSE IRRITATION TO EYES, LUNGS OR SKIN AFTER PROLONGED EXPOSURE.

Explanation Of Carcinogenicity: PRODUCT CONTAINS NO INGREDIENTS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Signs And Symptoms Of Overexposure: EYE IRRITATION, RESPIRATORY IRRITATION, SKIN IRRITATION.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL AID. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH LARGE AMOUNTS OF SOAP AND WATER. IF IRRITATION PERSISTS GET MEDICAL AID. INHALATION: REMOVE TO FRE SH AIR. IF BREATHING HAS STOPPED ADMINISTER ARTIFICIAL RESPIRATION. GET MEDICAL AID. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL AID.

=====

=====

Handling and Disposal

=====

Spill Release Procedures: CONTAIN SPILL. REMOVE AS MUCH AS POSSIBLE BY VACUUMING OR SOAK UP USING ABSORBENT MATERIALS. KEEP AWAY FROM HEAT OR FLAME.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Handling And Storage Precautions: KEEP AWAY FROM HEAT OR FLAME.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

=====

Fire and Explosion Hazard Information

=====

Flash Point Method: TCC

Flash Point Text: 122F,50C

Autoignition Temp Text: 425F

Lower Limits: 0.9 %

Upper Limits: 6.0 %

Extinguishing Media: FOAM, WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE

Fire Fighting Procedures: DO NOT USE STRAIGHT

WATER STREAM ON FIRE AS IT WILL  
SCATTER FIRE.

Unusual Fire/Explosion Hazard: DO NOT ENTER CONFINED AREA WITHOUT PROPER  
PROTECTIVE EQUIPMENT INCLUDING RESPIRATORY PROTECTION. VAPOR MAY EXPLODE.

=====  
Control Measures  
=====

Respiratory Protection: NORMALLY NOT REQUIRED. NIOSH APPROVED ORGANIC VAPOR  
RESPIRATOR TO PREVENT INHALATION WHEN IN CONFINED AREAS.

Ventilation: MECHANICAL EXPLOSION PRO  
OF IN ENCLOSED AREAS.

Protective Gloves: IMPERVIOUS

Eye Protection: CHEMICAL SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment: PROTECTIVE CLOTHING AS NECESSARY TO PREVENT SKIN  
CONTACT.

Work Hygienic Practices: WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT AND  
BEFORE EATING DRINKING OR SMOKING.

Supplemental Safety and Health: NONE SPECIFIED BY MANUFACTURER.

=====  
Physical/Chemical Properties  
=====

=====  
HCC: F4

B.P. Text: 330F,166C

M.P/F.P Text: UNKNOWN

Decomp Text: UNKNOWN

Vapor Pres: 2

Vapor Density: 4.2

Spec Gravity: 0.825

Evaporation Rate & Reference: 0.5 (ETHER=1)

Solubility in Water: SLIGHT

Appearance and Odor: CLEAR LIQUID, PETROLEUM ODOR

Percent Volatiles by Volume: 100 %

Corrosion Rate: UNKNOWN  
=====

Reactivity Data  
=====

Stability Indicator: YES

Stability Condition T

o Avoid: KEEP AWAY FROM HEAT OR FLAME.

Materials To Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: CARBON MONOXIDE

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NONE. WILL NOT OCCUR.  
=====

Toxicological Information  
=====

=====  
Ecological Information  
=====

=====  
=====

MSDS Transport Information

=====

=====

Regulatory Information

=====

=====

Other Information

=====

=====

Transportation Information

=====

Responsible Party Cage: MO636  
Trans ID NO: 100427  
Product ID: TURBINE FUEL, AVIATION, JP-8  
MSDS Prepared Date: 06/10/1993  
Review Date: 11/05/1993  
MFN: 1  
Net Unit Weight: BULK  
Multiple KIT Number: 0  
Review IND: Y  
Unit Of Issue: GL  
Container QTY: X  
Additional Data: FILM OR SHEEN UPON THE WATER SURFACE OR DISCOLORATION OF THE  
WATER OR ADJOINING SHORELINE IS REPORTABLE TO THE NATIONAL RESPONSE CENTER  
AT 1-800-424-8802.

=====  
=====

Detail DOT Information

=====

DOT PSN Code: GOA  
DOT Proper Shipping Name: FUEL, AVIATION, TURBINE ENGINE  
Hazard Class: 3  
UN ID Num: UN1863  
DOT Packaging Group: III  
Label: FLAMMABLE LIQUID  
Special Provision: B1,T1  
Packaging Exception: 150  
Non Bulk Pack: 203  
Bulk Pack: 242  
Max Qty Pass: 60 L  
Max Qty Cargo: 220 L  
Vessel Stow Req: A

=====  
=====

Detail IMO Information

=====  
IMO PSN Code: HNV  
IMO Proper Shipping Name: FUEL, AVIATION, TURBINE ENGINE  
IMDG Page Number: 3271  
UN Number: 1863  
UN Hazard Class: 3.2  
IMO Packaging Group: I/II  
Subsidiary Risk Label: -  
EMS Number: 3-07  
MED First Aid Guide NUM: 311  
=====

=====  
Detail IATA Information  
=====

IATA PSN MF  
IATA UN ID Num: 1863  
IATA Proper Shipping Name: FUEL, AVIATION  
, TURBINE ENGINE  
IATA UN Class: 3  
IATA Label: FLAMMABLE LIQUID  
UN Packing Group: III  
Packing Note Passenger: 309  
Max Quant Pass: 60L  
Max Quant Cargo: 220L  
Packaging Note Cargo: 310  
=====

=====  
Detail AFI Information  
=====

AFI PSN MF  
AFI Proper Shipping Name: FUEL, AVIATION, TURBINE ENGINE  
AFI Hazard Class: 3  
AFI UN ID NUM: UN1863  
AFI Packing Group: III  
Special Provisions: P5  
Back Pack Reference: A7.3  
=  
=====

=====  
HAZCOM Label  
=====

Product ID: TURBINE FUEL, AVIATION, JP-8  
Cage: MO636  
Assigned IND: Y  
Company Name: LA GLORIA OIL & GAS COMPANY  
Street: UNKNOWN  
PO Box: 840  
City: TYLER TX  
Zipcode: 75710  
Health Emergency Phone: 903-535-2244  
Label Required IND: Y  
Date Of Label Review: 11/05/1993  
Status Code: C  
MFG Label NO: NONE  
Label Date: 11/05/1993  
Year Procured: 1993  
Origination Code: F  
Eye Protectio

n IND: YES

Skin Protection IND: YES

Signal Word: WARNING

Health Hazard: Moderate

Contact Hazard: Slight

Fire Hazard: Moderate

Reactivity Hazard: None

Hazard And Precautions: KEEP AWAY FROM HEAT OR FLAME. FIRST AID: EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL AID. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH LARGE AMOUNTS OF SOAP AND WATER. IF IRRITATION PERSISTS GET MEDICAL AID. INHALATION: REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED ADMINISTER ARTIFICIAL RESPIRATION. GET MEDICAL AID. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL AID.

=====  
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense

nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.