

VERSATILE MACHINING INC -- 61B25042 SODIUM SULFIDE 3% -- 6630-00-831-5932

=====  
Product Identification  
=====

Product ID:61B25042 SODIUM SULFIDE 3%

MSDS Date:08/26/1987

FSC:6630

NIIN:00-831-5932

Kit Part:Y

MSDS Number: BRYDN

=== Responsible Party ===

Company Name:VERSATILE MACHINING INC

Address:7450 TOWER ST

City:FORT WORTH

State:TX

ZIP:76118-6424

Country:US

CAGE:6S522

=== Contractor Identificatio

n ===

Company Name:ANDERSON LABORATORIES INC

Address:5901 FITZHUGH AVE

Box:City:FORT WORTH

State:TX

ZIP:76119

Country:US

Phone:817-547-4474

CAGE:0E6L4

Company Name:VERSATILE MACHINING INC

Address:7450 TOWER ST

Box:City:FORT WORTH

State:TX

ZIP:76118-6424

Country:US

CAGE:6S522

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SODIUM SULFIDE, NONAHYDRATE

CAS:1313-84-4

RTECS #:WE1925000

Fraction by Wt: 3%

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by

Wt: 97%

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (INTRAPERITONEAL-MOUSE): 53 MG/KG

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:DANGER EYE BURNS. HARMFUL IF

SWALLOWED: CORROSIVE & IRRITATING THROUGH THE LIBERATION OF  
HYDROGEN SULFIDE & FREE ALKALI. HYDROGEN SULFIDE IS ESPECIALLY  
TOXIC. SULFIDES OF HEAVY METALS HAVE LITTLE TOXIC ACTION

EXCEPT

THROUGH THE LIBERATION OF HYDROGEN SULFIDE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN: SOFTENING & IRRITATION. INGESTION:  
CORROSIVE & IRRITATING.

=====  
===== First Aid Measures =====

First Aid:INGESTION: INDUCE VOMITING BY GIVING SYRUP OF IPECAC OR BY  
STICKING FINGER DOWN THROAT. NEVER GIVE ANYTHING BY MOUTH TO AN  
UNCONSCIOUS PERSON. EYES/SKIN: FLUSH W/PLENTY OF WATER FOR 15 MINS.  
OBTAIN MEDICAL ATTENTION IN ALL  
L CASES.

=====  
===== Fire Fighting Measures =====

Unusual Fire/Explosion Hazard:HYDROGEN SULFIDE EVOLVED CAN FORM  
EXPLOSIVE MIXTURES W/AIR.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING. ABSORB OR COVER  
W/INERT ABSORBENT MATERIAL. CAREFULLY PICK UP & PLACE IN CLOSED  
CONTAINER FOR DISPOSAL. FLUSH SPILL W/PLENTY OF WATER.

=====  
===== Handling and Storage =====

=====

Handling and Storage Precautions:DON'T HANDLE UNTIL THE MANUFACTURERS  
SAFETY PRECAUTIONS HAVE BEEN READ & UNDERSTOOD.

Other Precautions:AVOID CONTACT W/EYES, SKIN. DON'T EAT, DRINK OR SMOKE  
WHILE HANDLING.

=====  
===== Exposure Controls/Personal Protection =====

Ventilation:MECHANICAL: AT LEAST 10 AIR CHANGES PER HOUR PER ROOM

Protective Gloves:LATEX

Eye Protection:GLASSES

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE. WASH THOROUGHLY

AFTER HANDLING.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:100C  
Vapor Pres:20  
Spec Gravity:>WATER  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Appearance and Odor:CLEAR, COLORLESS LIQUID W/CHARACTERISTIC ODOR OF  
ROTTEN EGG.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS, STRONG ACIDS  
Hazardous Decomposition Products:HYDROGEN  
SULFIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, &  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person ut  
ilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.