

BREN-TRONICS -- NICKEL-CADMIUM BATTERY, SEALED BB-557/U -- 6140-01-071-5070
===== Product Identification =====

Product ID:NICKEL-CADMIUM BATTERY, SEALED BB-557/U

MSDS Date:08/05/1993

FSC:6140

NIIN:01-071-5070

MSDS Number: BRZYY

=== Responsible Party ===

Company Name:BREN-TRONICS

Address:10 BRAYTON COURT

City:COMMACK

State:NY

ZIP:11725

Country:US

Info Phone Num:(516)-499-5155

Emergency Phone Num:(

516)-499-5155

Preparer's Name:CECOM SAFETY OFFICE

CAGE:DO086

=== Contractor Identification ===

Company Name:BREN-TRONICS

Address:10 BRAYTON CT

Box:City:COMMACK

State:NY

ZIP:11725-5504

Phone:516-499-5155

CAGE:DO086

Company Name:BREN-TRONICS INC

Address:10 BRAYTON CT

Box:City:COMMACK

State:NY

ZIP:11725-3104

Country:US

Phone:631-499-5155

CAGE:51828

===== Composition/Information on Ingredients =====

Ingred Name:CADMIUM (SARA III)

CADMIUM & CADMIUM HYDROXIDE 11-

26%
CAS:7440-43-9
RTECS #:EU9800000
Fraction by Wt: 11-26%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:SEE 1910.1027
ACGIH TLV:0.01 MG/M3 DUST;9394
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:CADMIUM HYDROXIDE
CADMIUM & CADMIUM HYDROXIDE 11-26%
CAS:21041-95-2
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG/M3 (CD FUME)
ACGIH TLV:0.05 MG/M3 (CD FUME)

Ingred Name:COBALT (SARA III)
COBALT & COBALT HYDROXIDE (TRACE AMOUNTS)
CAS:7440-48-4
RTECS #:GF875000
0
Fraction by Wt: TRACE
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG/M3;AS CO
ACGIH TLV:0.05 MG/M3;DUST 9293

Ingred Name:COBALT HYDROXIDE
COBALT & COBALT HYDROXIDE (TRACE AMOUNTS)
CAS:21041-93-0
Other REC Limits:NONE RECOMMENDED

Ingred Name:NICKEL (SARA III)
NICKEL AND NICKEL HYDROXIDE 13-29%
CAS:7440-02-0
RTECS #:QR5950000
Fraction by Wt: 13-29%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9293

Ingred Name:NICKEL HYDROXIDE (

SARA III)

NICKEL & NICKEL HYDROXIDE 13-29%

CAS:12054-48-7

RTECS #:QR7040000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1 MG NI/M3

ACGIH TLV:0.1 MG NI/M3; 9293

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:POTASSIUM HYDROXIDE (SARA III)

CAS:1310-58-3

RTECS #:TT2100000

Fraction by Wt: < 3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:C, 2 MG/M3

ACGIH TLV:C 2 MG/M3; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

==

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:INTACT BATTERIES PRESENT NO SPECIFIC HAZARDS. BURNING BATTERIES MAY EMIT TOXIC FUMES. LEAKING BATTERIES LEAK CORROSIVE MATERIAL IRRITATING TO SKIN, EYES AND MUCOUS MEMBRANES

Explanation of Carcinogenicity:CD, NI, ARE NTP SUSPECT CARCINOGENS. CD IS IARC CARCINOGEN.

Effects of Overexposure:

ELECTROLYTE EXPOSURE TO SKIN/EYES WILL CAUSE SEVERE IRRITATION. INHALATION OF FUMES MAY CAUSE SEVERE RESPIRATORY IRRITATION.

Medical Conditions Aggravated by Exposure:RESPIRATORY ALIMENTATIONS- W/BURNING BATTERIES SKIN CONDITIONS- W/ LEAKING BATTERIES

=====
===== First Aid Measures =====

First Aid:IF BATTERY CONTENTS COME IN CONTACT WITH THE BODY WASH AFFECTED AREA FOR AT LEAST 15 MINUTES WITH CLEAN WATER.DO NOT ATTEMPT TO NEUTRALIZE. SEEK MEDICAL

ICAL ATTENTION PROMPTLY.

===== Fire Fighting Measures =====

Extinguishing Media:CARBON DIOXIDE OR DRY CHEMICAL FIRE EXTINGUISHER,
10-B:C

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE SELF CONTAINED
BREATHING APPARATUS. BATTERY/CELLS MAY RELEASE TOXIC FUMES, IF
SUBJECT TO FIRE/EXTREME HEAT.

Unusual Fire/Explosion Hazard:STRONG OXIDERIZERS (E.G.,ACIDS) AND FIRE.

===== Accidental Release Measures =====

Spill Release P

rocedures:SPILL OR LEAK PROCEDURES (PRECAUTIONS FOR SAFE
HANDLING & USE) AVOID SKIN OR EYE CONTACT. USE NON FLAMMABLE
ABSORBENT MATERIAL FOR CLEAN-UP. COORDINATE WITH INSTALLATION
SAFETY AND ENVIRONMENTAL OFFIC ES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT ABUSE OR SHORT CIRCUIT. STORE
COOL, DRY AND IN A WELL VENT AREA. SEPARATE FROM OTHER HAZARDOUS
MATERIALS

. AREA APPROVED BY LOCAL FIRE DEPARTM

Other Precautions:DO NOT INVERT BATTERY OR CAUSE TO SPILL. RECHARGE
IAW METHODS SPECIFIED IN APPLICIABLE TECHNICAL MANUAL. DO NOT
OVERCHARGE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF BATTERIES ARE BURNING USE SCBA

Ventilation:CONTACT LOCAL SAFETY/INDUSTRIAL HYGIENE OFFICE TO DETERMINE
IF LOCAL EXHAUST VENTILATION IS NEEDED

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:CHEMICAL

SAFETY GLASSES/GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT APRON

Work Hygienic Practices:AVOID SKIN EYE CONTACT WITH ELECTROLYTE. DO NOT
EAT OR SMOKE IN BATTERY SERVICE AREA.

Supplemental Safety and Health

CONTRACT # DAAB07-91-C-R002 THIS MSDS WAS CODED FROM A CECOM MATERIAL
SAFETY DATA SHEET NOT THE MANUFACTUERS. CECOM SAFETY OFFICE, FT
MONMOUTH, NJ 07703-5024 AUTOVON 995-3112.

===== Physical/Chemical Properties =====

pH:UNK

Appearance and

Odor:NICKEL-CADMIUM BATTERY,SEALED

Percent Volatiles by Volume:UNK

Corrosion Rate:UNK

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS (E.G., ACIDS). STORE SEPARATELY FROM OTHER HAZARDOUS MATERIALS

Stability Condition to Avoid:FIRE AND EXTREME HEAT. DO NOT SHORT CIRCUIT OR OVERCHARGE

Hazardous Decomposition Products:WHEN EXPOSED TO FIRE OR EXTREME HEAT, BATTERIES MAY EMIT TOXIC FUMES

=====

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. COORDINATE WITH SUPPORTING INSTALLATION AND/OR MACOM ENVIRONMENTAL OFFICE PRIOR TO DISPOSAL

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.