

SAFT AMERICA INC POWER SOURCES DIV -- NICKEL-CADMIUM BATTERY, VENTED BB 664/A --
6140-01-307-1326

===== Product Identification =====

Product ID:NICKEL-CADMIUM BATTERY, VENTED BB 664/A

MSDS Date:08/03/1993

FSC:6140

NIIN:01-307-1326

MSDS Number: BSBBV

=== Responsible Party ===

Company Name:SAFT AMERICA INC POWER SOURCES DIV

Address:711 INDUSTRIAL BLVD

Box:1886

City:VALDOSTA

State:GA

ZIP:31603

Count

ry:US

Info Phone Num:912-247-2331

Emergency Phone Num:912-247-2331

Preparer's Name:CECOM SAFETY OFFICE

CAGE:09052

=== Contractor Identification ===

Company Name:SAFT AMERICA INC.

Address:711 INDUSTRIAL BLVD

Box:1886

City:VALDOSTA

State:GA

ZIP:31602

Country:US

Phone:912-247-2331

CAGE:09052

===== Composition/Information on Ingredients =====

Ingred Name:CADMIUM (SARA III)

CADMIUM & CADMIUM HYDROXIDE 14-15%

CAS:7440-43-9

RTECS #:EU9800000

Fraction by Wt: 14-15%

Other REC Limits:NONE RECOMMENDED
OSHA PEL:SEE 1910.1027
ACGIH TLV:0.01 MG/M3 DUST;9394
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:CADMIUM HYDROXIDE
CADMIUM & CADMIUM HYDROXIDE 14-15%
CAS:21041-95-2
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG/M3 (CD FUME)
ACGIH TLV:0.05 MG/M3 (CD FUME)

Ingred Name:NICKEL (SARA III)
NICKEL AND NICKEL HYDROXIDE 26%
CAS:7440-02-0
RTECS #:QR5950000
Fraction by Wt: 26%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 M
G/M3
ACGIH TLV:1 MG/M3; 9293

Ingred Name:NICKEL HYDROXIDE (SARA III)
NICKEL & NICKEL HYDROXIDE 26%
CAS:12054-48-7
RTECS #:QR7040000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG NI/M3
ACGIH TLV:0.1 MG NI/M3; 9293
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:POTASSIUM HYDROXIDE (SARA III) 30% SOLUTION
CAS:1310-58-3
RTECS #:TT2100000
Fraction by Wt: 6.5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C, 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INTACT BATTERIES PRESENT NO SPECIFIC
HAZARDS. BURNING BATTERIES MAY EMIT TOXIC FUMES. LEAKING
BATTERIES LEAK CORROSIVE MATERIAL IRRITATING TO SKIN, EYES AND
MUCOUS MEMBRANES
Explanation of Carcinogenicity:CD, NI,
ARE NTP SUSPECT CARCINOGENS. CD
IS IARC CARCINOGEN.
Effects of Overexposure:ELECTROLYTE EXPOSURE TO SKIN/EYES WILL CAUSE
SEVERE IRRITATION. INHALATION OF FUMES MAY CAUSE SEVERE
RESPIRATORY IRRITATION.
Medical Cond Aggravated by Exposure:RESPIRATORY ALIMENTS- W/BURNING
BATTERIES SKIN CONDITIONS- W/ LEAKING BATTERIES

=====
===== First Aid Measures =====

First Aid:IF BATTERY CONTENTS COME IN CONTACT WITH THE BODY WASH
AFFECTED AREA FOR AT LEAST
15 MINUTES WITH CLEAN WATER.DO NOT
ATTEMPT TO NEUTRALIZE. SEEK MEDICAL ATTENTION PROMPTLY.

=====
===== Fire Fighting Measures =====

Extinguishing Media:CARBON DIOXIDE OR DRY CHEMICAL FIRE EXTINGUISHER,
10-B:C
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE SELF CONTAINED
BREATHING APPARATUS. BATTERY/CELLS MAY RELEASE TOXIC FUMES, IF
SUBJECT TO FIRE/EXTREME HEAT.
Unusual Fire/Explosion Hazard:STRONG OXIDERIZERS (E.G.,ACIDS) AND FIRE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SPILL OR LEAK PROCEDURES (PRECAUTIONS FOR SAFE
HANDLING & USE) AVOID SKIN OR EYE CONTACT. USE NON FLAMMABLE
ABSORBENT MATERIAL FOR CLEAN-UP. COORDINATE WITH INSTALLATION
SAFETY AND ENVIRONMENTAL OFFIC ES.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT ABUSE OR SHORT CIRCUIT. STORE
COOL,

DRY AND IN A WELL VENT AREA. SEPARATE FROM OTHER HAZARDOUS MATERIALS. AREA APPROVED BY LOCAL FIRE DEPARTM

Other Precautions:DO NOT INVERT BATTERY OR CAUSE TO SPILL. RECHARGE IAW METHODS SPECIFIED IN APPLICIABLE TECHNICAL MANUAL. DO NOT OVERCHARGE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF BATTERIES ARE BURNING USE SCBA

Ventilation:CONTACT LOCAL SAFETY/INDUSTRIAL HYGIENE OFFICE TO DETERMINE IF LOCAL EXHAUST VENTILATION IS NEED

ED

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:CHEMICAL SAFETY GLASSES/GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT APRON

Work Hygienic Practices:AVOID SKIN EYE CONTACT WITH ELECTROLYTE. DO NOT EAT OR SMOKE IN BATTERY SERVICE AREA.

Supplemental Safety and Health

CONTRACT # ???? THIS MSDS WAS CODED FROM A CECOM MATERIAL SAFETY DATA SHEET NOT THE MANUFACTUERS. CECOM SAFETY OFFICE, FT MONMOUTH, NJ 07703-5024 AUTOVON 995-3112.

=====
===== Physical/Chemical Properties =====

pH:UNK

Appearance and Odor:NICKEL-CADMIUM BATTERY,VENTED

Percent Volatiles by Volume:UNK

Corrosion Rate:UNK

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS (E.G., ACIDS). STORE SEPARATELY FROM OTHER HAZARDOUS MATERIALS

Stability Condition to Avoid:FIRE AND EXTREME HEAT. DO NOT SHORT CIRCUIT OR OVERCHARGE

Hazardous Decomposition Products:WHEN EXPOSED TO FIRE OR EXTREME HEAT, BATTERIES MAY EMIT TOXIC FUMES

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. COORDINATE WITH SUPPORTING INSTALLATION AND/OR MACOM ENVIRONMENTAL OFFICE PRIOR TO DISPOSAL

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The Un

ited States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.